



US007382319B2

(12) **United States Patent**  
**Kawahata et al.**

(10) **Patent No.:** **US 7,382,319 B2**  
(45) **Date of Patent:** **Jun. 3, 2008**

- (54) **ANTENNA STRUCTURE AND COMMUNICATION APPARATUS INCLUDING THE SAME**
- (75) Inventors: **Kazunari Kawahata**, Machida (JP); **Junichi Kurita**, Fleet (GB)
- (73) Assignee: **Murata Manufacturing Co., Ltd.** (JP)
- (\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

- (21) Appl. No.: **10/581,803**
- (22) PCT Filed: **Nov. 30, 2004**
- (86) PCT No.: **PCT/JP2004/017788**  
§ 371 (c)(1),  
(2), (4) Date: **Jan. 8, 2007**
- (87) PCT Pub. No.: **WO2005/055364**  
PCT Pub. Date: **Jun. 16, 2005**

(65) **Prior Publication Data**  
US 2007/0115177 A1 May 24, 2007

(30) **Foreign Application Priority Data**  
Dec. 2, 2003 (JP) ..... 2003-402544


- (51) **Int. Cl.**  
**H01Q 1/38** (2006.01)  
**H01Q 1/24** (2006.01)  
**H01Q 13/10** (2006.01)
- (52) **U.S. Cl.** ..... **343/700 MS; 343/702; 343/770**
- (58) **Field of Classification Search** ..... **343/700 MS, 343/702, 767, 770, 846, 893**  
See application file for complete search history.

- (56) **References Cited**  
U.S. PATENT DOCUMENTS  
6,657,593 B2\* 12/2003 Nagumo et al. .... 343/700 MS  
6,950,072 B2\* 9/2005 Miyata et al. .... 342/702  
FOREIGN PATENT DOCUMENTS  
JP 2-812 1/1990  
JP 10-93332 4/1998  
JP 2001-217643 8/2001  
JP 2002-314330 10/2002  
JP 2003-8326 1/2003  
(Continued)

*Primary Examiner*—Shih-Chao Chen  
(74) *Attorney, Agent, or Firm*—Ostrolenk, Faber, Gerb & Soffen, LLP

(57) **ABSTRACT**  
In an antenna structure including a feeding radiation electrode and a non-feeding radiation electrode that are electromagnetically coupled to each other, due to formation of a main slit, the feeding radiation electrode includes a U-turn portion in the middle of a path circumventing the main slit from a feeding end to an open end. A sub-slit for forming an open stub that is connected to the U-turn portion and that provides the U-turn portion with electrostatic capacitance is formed in the feeding radiation electrode. By changing a value of the electrostatic capacitance to be provided by the open stub to the U-turn portion of the feeding radiation electrode, variable control of a higher-order resonant frequency F2 of the feeding radiation electrode 2 can be achieved while suppressing fluctuations in a resonant state (for example, a fundamental resonant frequency F1 and a Q-value) of a fundamental resonant frequency band of the feeding radiation electrode, in an electromagnetic coupling state between the feeding radiation electrode and the non-feeding radiation electrode, and in an impedance matching state.

**9 Claims, 7 Drawing Sheets**





US007382321B1

(12) **United States Patent**  
**Qin**

(10) **Patent No.:** **US 7,382,321 B1**  
(45) **Date of Patent:** **Jun. 3, 2008**

(54) **BROADBAND ANTENNA**

(75) Inventor: **Xiang-Hong Qin**, Shenzhen (CN)

(73) Assignees: **Hong Fu Jin Precision Industry (ShenZhen) Co., Ltd.**, Shenzhen, Guangdong Province (CN); **Hon Hai Precision Industry Co., Ltd.**, Tu-Cheng, Taipei Hsien (TW)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **11/616,900**

(22) Filed: **Dec. 28, 2006**

(30) **Foreign Application Priority Data**

Nov. 10, 2006 (CN) ..... 2006 1 0063580

(51) **Int. Cl.**  
**H01Q 1/38** (2006.01)  
**H01Q 13/12** (2006.01)  
**H01Q 1/48** (2006.01)

(52) **U.S. Cl.** ..... **343/700 MS; 343/769; 343/848**

(58) **Field of Classification Search** ..... **343/700 MS, 343/769, 846, 848**

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,055,852 A \* 10/1991 Dusseux et al. .... 343/725  
5,548,297 A \* 8/1996 Arai ..... 343/700 MS  
5,675,346 A \* 10/1997 Nishikawa et al. .. 343/700 MS  
2004/0252056 A1 12/2004 Chen et al.


\* cited by examiner

*Primary Examiner*—Shih-Chao Chen  
(74) *Attorney, Agent, or Firm*—Wei Te Chung

(57) **ABSTRACT**

A broadband antenna includes a radiation part (10) for radiating and receiving electromagnetic signals, a feed portion (30) for feeding the electromagnetic signals, and a pair of ground planes (40) respectively disposed on sides of the feed portion. The radiation part comprises an annular first radiation segment (12) and an annular second radiation segment (14) being inscribed within a space defined by the annular shape of the first radiation segment. The feed portion is electrically connected to the radiation part.

**12 Claims, 18 Drawing Sheets**





US007382322B1

(12) **United States Patent**  
**Yang et al.**

(10) **Patent No.:** **US 7,382,322 B1**  
(45) **Date of Patent:** **Jun. 3, 2008**

- (54) **CIRCULARLY POLARIZED PATCH ANTENNA ASSEMBLY**
- (75) Inventors: **Tsai-Yi Yang**, Tainan Hsien (TW);  
**Te-Yi Chu**, Tainan Hsien (TW)
- (73) Assignee: **Cirocomm Technology Corp.**, Tainan Hsien (TW)
- (\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.
- (21) Appl. No.: **11/688,937**
- (22) Filed: **Mar. 21, 2007**
- (51) **Int. Cl.**  
**H01Q 1/38** (2006.01)
- (52) **U.S. Cl.** ..... **343/700 MS**
- (58) **Field of Classification Search** ..... **343/700 MS,**  
**343/846**

See application file for complete search history.



- (56) **References Cited**  
U.S. PATENT DOCUMENTS  
5,061,939 A \* 10/1991 Nakase ..... 343/700 MS  
\* cited by examiner

*Primary Examiner*—Michael C Wimer

(57) **ABSTRACT**

A circularly polarized patch antenna assembly having a relatively compact volume includes a substrate, a radiation metal piece, a grounded metal piece and a signal-inputting body. A plurality of frequency down-conversion metal pieces in a form of elongate stripe extends from four sides of the grounded metal piece, thereby to reduce the resonant frequency. The frequency down-conversion metal pieces are adhered on the side face of the substrate, so that the frequency down-conversion metal piece on one side face is arranged diagonally with respect to the frequency down-conversion metal piece on the opposite side face. When the resonant frequency of the antenna is to be reduced, the position and the area of the frequency down-conversion metal piece can be adjusted but the increased area of the frequency down-conversion metal piece cannot be larger than a half area of the side face of the substrate. Alternatively, the length of the frequency down-conversion metal piece can be increased.

**13 Claims, 9 Drawing Sheets**





US007382323B2

(12) **United States Patent**  
**Hu et al.**

(10) **Patent No.:** **US 7,382,323 B2**  
(45) **Date of Patent:** **Jun. 3, 2008**

(54) **MICRO CHIP ANTENNA**

(56) **References Cited**

(75) Inventors: **Chuan Ling Hu**, Taipei Hsien (TW);  
**Meng Chiu Pan**, Taipei Hsien (TW);  
**Shun Tian Lin**, Taipei (TW); **Chang**  
**Fa Yang**, Taipei (TW); **Kao Chung**  
**Cheng**, Taipei (TW); **Sea Fue Wang**,  
Taipei (TW); **Lisen Chang**, Taipei  
(TW); **Chang Lun Liao**, Taipei (TW);  
**Chia Hung Chen**, Taipei (TW)

U.S. PATENT DOCUMENTS

|              |      |         |                     |            |
|--------------|------|---------|---------------------|------------|
| 5,870,066    | A *  | 2/1999  | Asakura et al. .... | 343/895    |
| 6,023,251    | A *  | 2/2000  | Koo et al. ....     | 343/895    |
| 6,353,443    | B1 * | 3/2002  | Ying .....          | 715/702    |
| 6,686,884    | B2 * | 2/2004  | Back et al. ....    | 343/700 MS |
| 6,734,825    | B1 * | 5/2004  | Guo et al. ....     | 343/700 MS |
| 6,950,065    | B2 * | 9/2005  | Ying et al. ....    | 343/700 MS |
| 2003/0214441 | A1 * | 11/2003 | Back et al. ....    | 343/700 MS |
| 2004/0263420 | A1 * | 12/2004 | Werner et al. ....  | 343/909    |
| 2005/0110684 | A1 * | 5/2005  | Liu .....           | 343/700 MS |

\* cited by examiner

(73) Assignee: **Chant Sincere Co., Ltd.**, Taipei Hsien  
(TW)

*Primary Examiner*—Huedung Mancuso  
(74) *Attorney, Agent, or Firm*—Bacon & Thomas, PLLC

(\* ) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 0 days.

(57) **ABSTRACT**

A method for manufacturing microchip antenna comprises a dielectric substrate having antenna radiation conductor paths composing of at least one feeding point and multiple-curved paths; a dielectric substrate having the antenna radiation conductor paths being packaged by the material capable of adjusting easily dielectric constant; and an antennal object including antenna radiation conductor paths, feeding ends, welding spots and packaging materials. The main body of the antenna has multi-folded paths, feeding ends, welding spots, and a packaging body. The radiation wires of the antenna is built on a single or a multiple input ends on a dielectric substrate and is multi-folded wires and it is packaged by another dielectric material. The radiation wires of the antenna can be designed and manufactured in three dimension so as to reduce the area occupied by the antenna and reduce the coupling interference between the elements.


(21) Appl. No.: **11/036,015**

(22) Filed: **Jan. 18, 2005**

(65) **Prior Publication Data**  
US 2006/0158377 A1 Jul. 20, 2006

(51) **Int. Cl.**  
**H01Q 1/24** (2006.01)  
(52) **U.S. Cl.** ..... **343/702**  
(58) **Field of Classification Search** ..... 343/702,  
343/700 MS, 895, 873  
See application file for complete search history.

**9 Claims, 5 Drawing Sheets**





US007382326B1

(12) **United States Patent**  
**Lin et al.**

(10) **Patent No.:** **US 7,382,326 B1**  
(45) **Date of Patent:** **Jun. 3, 2008**

(54) **MULTI-BAND ANTENNA**

(75) Inventors: **Ching-Chi Lin**, Taipei Hsien (TW);  
**Kai Shih**, Taipei Hsien (TW); **Yu-Yuan Wu**, Taipei Hsien (TW)

(73) Assignee: **Cheng Uei Precision Industry**, Taipei Hsien (TW)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 19 days.

(21) Appl. No.: **11/613,260**

(22) Filed: **Dec. 20, 2006**

(51) **Int. Cl.**  
**H01Q 1/24** (2006.01)  
**H01Q 1/38** (2006.01)

(52) **U.S. Cl.** ..... **343/702; 343/700 MS**

(58) **Field of Classification Search** ..... **343/702, 343/700 MS**

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2006/0176233 A1\* 8/2006 Tang et al. .... 343/850

2007/0109199 A1\* 5/2007 Hung et al. .... 343/700 MS  
2007/0120753 A1\* 5/2007 Hung et al. .... 343/702  
2007/0194993 A1\* 8/2007 Deavours et al. .... 343/700 MS

\* cited by examiner


*Primary Examiner*—Hoang V Nguyen

(74) *Attorney, Agent, or Firm*—WPAT, P.C.; Anthony King

(57) **ABSTRACT**

A multi-band antenna configured in a portable electrical device capable of operating in a low frequency bandwidth and a high frequency bandwidth has an elongated radiating body and a feeding conductor connecting the elongated radiating body. The feeding conductor has opposite side arms respectively connecting the elongated radiating body and a connecting portion connecting the side arms. A feeding point is arranged at a corner where one of the side arms connects to the connecting portion. The elongated radiating body and the feeding conductor are located on different planes of the portable electronic device. According to the position where the feeding conductor connects to the elongated radiating body and the position where the feeding point is arranged at, the multi-band antenna has a preferred low frequency bandwidth and a preferred high frequency bandwidth. Therefore, the portable electrical device can operate at different wireless bandwidths.

**12 Claims, 2 Drawing Sheets**





US007382331B2

(12) **United States Patent**  
**Kurashima et al.**

(10) **Patent No.:** **US 7,382,331 B2**  
(45) **Date of Patent:** **Jun. 3, 2008**

(54) **ANTENNA DEVICE**  
(75) Inventors: **Shigemi Kurashima**, Shinagawa (JP); **Masahiro Yanagi**, Shinagawa (JP); **Hideki Iwata**, Shinagawa (JP); **Takashi Yuba**, Shinagawa (JP); **Masahiro Kaneko**, Shinagawa (JP); **Yuriko Segawa**, Shinagawa (JP); **Takashi Arita**, Shinagawa (JP)

(73) Assignee: **Fujitsu Component Limited**, Tokyo (JP)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **11/585,902**

(22) Filed: **Oct. 25, 2006**

(65) **Prior Publication Data**

US 2007/0229363 A1 Oct. 4, 2007

(30) **Foreign Application Priority Data**

Mar. 29, 2006 (JP) ..... 2006-091605

(51) **Int. Cl.**  
**H01Q 15/08** (2006.01)  
**H01Q 1/38** (2006.01)  
**H01Q 1/48** (2006.01)

(52) **U.S. Cl.** ..... **343/911 L; 343/700 MS; 343/846**

(58) **Field of Classification Search** ..... **343/700 MS, 343/753, 840, 911 L, 846, 911 R**  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

4,755,820 A \* 7/1988 Backhouse et al. ... 343/700 MS  
6,246,369 B1 \* 6/2001 Brown et al. .... 343/700 MS  
6,713,162 B2 \* 3/2004 Takaya et al. .... 428/209  
6,946,995 B2 \* 9/2005 Choi et al. .... 343/700 MS

**OTHER PUBLICATIONS**

Technical Report: An Omnidirectional and Low VSWR Antenna for the FCC-Approved UWB Frequency Band, written and proposed by Takuya Taniguchi and Takehiko Kobayashi, in The General Conference of The Institute of Electronics, Information and Communication Engineers, in 2003.

\* cited by examiner


*Primary Examiner*—Shih-Chao Chen

(74) *Attorney, Agent, or Firm*—Staas & Halsey LLP

(57) **ABSTRACT**

An antenna device includes an antenna part and a dielectric formed on the antenna part. The dielectric is formed to be thicker in a direction of directivity that the antenna part is to be made to have, than in another direction.

**10 Claims, 9 Drawing Sheets**





US007383060B2

(12) **United States Patent**  
**Su et al.**

(10) **Patent No.:** **US 7,383,060 B2**  
(45) **Date of Patent:** **Jun. 3, 2008**

(54) **MOBILE PHONE WITH FM ANTENNA**

(75) Inventors: **Jia-Hung Su**, Chung Ho (TW);  
**Hong-Ren Chen**, Chung Ho (TW);  
**Huang-Tse Peng**, Chung Ho (TW);  
**Yu-Yuan Wu**, Chung Ho (TW)

5,801,660 A \* 9/1998 Ohtsuka et al. .... 343/700 MS  
6,667,718 B2 \* 12/2003 Back et al. .... 343/700 MS  
6,762,724 B2 \* 7/2004 Peng ..... 343/702  
7,030,815 B2 \* 4/2006 Dunn et al. .... 343/700 MS  
7,039,437 B2 \* 5/2006 Kojola et al. .... 455/550.1  
2003/0214442 A1 \* 11/2003 Back et al. .... 343/700 MS

(73) Assignee: **Darts Technologies Corp.**, Taipei  
County (TW)

**FOREIGN PATENT DOCUMENTS**

(\* ) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 374 days.

WO WO 2005024997 A1 \* 3/2005

\* cited by examiner

(21) Appl. No.: **11/220,775**

*Primary Examiner*—Matthew Anderson  
*Assistant Examiner*—Minh D Dao

(22) Filed: **Sep. 6, 2005**

(57) **ABSTRACT**

(65) **Prior Publication Data**

US 2007/0054693 A1 Mar. 8, 2007

(51) **Int. Cl.**  
**H04M 1/00** (2006.01)

(52) **U.S. Cl.** ..... **455/550.1**; 455/556.1;  
455/553.1; 455/557.7; 343/700 MS; 343/702

(58) **Field of Classification Search** ..... 455/550.1,  
455/556.1, 553.1, 557.7, 129; 343/700 MS,  
343/702

See application file for complete search history.


A mobile phone with FM antenna includes a mobile phone body, an FM antenna, an FM microchip and a phone case. The FM antenna is fixed to an outer side of the mobile phone body. One end of the FM antenna has a feed point, and the other end of the FM antenna is an opening end. The FM antenna resonates at FM radio frequencies so as to receive FM radio signals. The FM microchip is disposed on the mobile phone body and coupled with the feed point of the FM antenna for processing the FM radio signals. The phone case encloses the mobile phone body, the FM antenna and the FM microchip. Thus the FM antenna is embedded in the mobile phone to enable the mobile phone to receive FM radio without extra external earphones.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

5,444,452 A \* 8/1995 Itoh et al. .... 343/700 MS

**3 Claims, 5 Drawing Sheets**





US007385556B2

(12) **United States Patent**  
**Chung et al.**

(10) **Patent No.:** **US 7,385,556 B2**  
(45) **Date of Patent:** **Jun. 10, 2008**

- (54) **PLANAR ANTENNA**
- (75) Inventors: **Cho-Ju Chung**, Taipei Hsien (TW);  
**Teng-Huei Chu**, Taipei Hsien (TW)
- (73) Assignee: **Hon Hai Precision Industry Co., Ltd.**,  
Tu-Cheng, Taipei Hsien (TW)
- (\* ) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 0 days.

|                |        |                   |            |
|----------------|--------|-------------------|------------|
| 6,933,902 B2 * | 8/2005 | Yeh .....         | 343/762    |
| 7,106,259 B2 * | 9/2006 | Tseng et al. .... | 343/702    |
| 7,183,981 B1 * | 2/2007 | Chao .....        | 343/700 MS |
| 7,259,720 B2 * | 8/2007 | Ryu .....         | 343/700 MS |

**FOREIGN PATENT DOCUMENTS**

CN 1819337 A 8/2006

\* cited by examiner

*Primary Examiner*—Trinh V Dinh  
(74) *Attorney, Agent, or Firm*—Wei Te Chung

- (21) Appl. No.: **11/615,019**
- (22) Filed: **Dec. 22, 2006**
- (65) **Prior Publication Data**  
US 2008/0106473 A1 May 8, 2008
- (51) **Int. Cl.**  
**H01Q 1/38** (2006.01)
- (52) **U.S. Cl.** ..... **343/700 MS; 343/895;**  
343/846; 343/829
- (58) **Field of Classification Search** ..... None  
See application file for complete search history.
- (56) **References Cited**


**U.S. PATENT DOCUMENTS**

|                |        |                   |            |
|----------------|--------|-------------------|------------|
| 5,926,139 A *  | 7/1999 | Korisch .....     | 343/702    |
| 6,094,170 A *  | 7/2000 | Peng .....        | 343/700 MS |
| 6,930,640 B2 * | 8/2005 | Chung et al. .... | 343/700 MS |

(57) **ABSTRACT**

A planar antenna (20) includes a radiating body (21), a feeding portion (22), and a first metallic ground plane (24). The radiating body includes a first radiating portion (212) extending away from the feeding portion and a second radiating portion (214) extending away from the feeding portion next to the first radiating portion. The first radiating portion includes an open end (2122) disposed at an extending end of the first radiating portion to point toward the second radiating portion, and a connecting portion (2124). The second radiating portion includes a free end (2144) disposed at an extending end of the second radiating portion to point toward the first radiating portion, and an end (2146) connected to the connecting portion. A first gap (26) is formed between the open end and the free end. The open end, the first gap and the free end are aligned with one another.

**18 Claims, 11 Drawing Sheets**







US007385558B2

(12) **United States Patent**  
**Krupa**

(10) **Patent No.:** **US 7,385,558 B2**  
(45) **Date of Patent:** **Jun. 10, 2008**

- (54) **CAPACITIVE FEED ANTENNA**
- (75) Inventor: **Steve Krupa**, Cambridge (GB)
- (73) Assignee: **Galtronics Ltd.**, Tiberias (IL)
- (\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

|              |     |         |                          |            |
|--------------|-----|---------|--------------------------|------------|
| 5,617,102    | A   | 4/1997  | Prater                   |            |
| 5,764,190    | A   | 6/1998  | Murch et al.             |            |
| 6,639,558    | B2  | 10/2003 | Kellerman et al.         |            |
| 6,650,294    | B2  | 11/2003 | Ying et al.              |            |
| 6,680,705    | B2  | 1/2004  | Tan et al.               |            |
| 6,853,339    | B2  | 2/2005  | Sievenpiper et al.       |            |
| 7,053,844    | B2  | 5/2006  | Gaucher et al.           |            |
| 7,136,019    | B2* | 11/2006 | Mikkola et al. ....      | 343/702    |
| 7,202,818    | B2* | 4/2007  | Anguera Pros et al. .... | 343/700 MS |
| 2005/0190106 | A1  | 9/2005  | Anguera Pros et al.      |            |
| 2005/0195124 | A1* | 9/2005  | Puente Baliarda et al. . | 343/893    |

(21) Appl. No.: **11/357,371**

(22) Filed: **Feb. 16, 2006**

(65) **Prior Publication Data**

US 2006/0197708 A1 Sep. 7, 2006

**Related U.S. Application Data**

- (60) Provisional application No. 60/673,588, filed on Apr. 21, 2005, provisional application No. 60/654,013, filed on Feb. 17, 2005.

- (51) **Int. Cl.**  
*H01Q 1/24* (2006.01)  
*H01Q 1/38* (2006.01)

- (52) **U.S. Cl.** ..... 343/702; 343/700 MS; 343/833; 343/834

- (58) **Field of Classification Search** ..... 343/702, 343/700 MS, 833, 834, 846, 850  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

4,218,685 A 8/1980 Frosch et al.

**OTHER PUBLICATIONS**

International Search Report dated Jan. 3, 2007 for PCT Patent Application PCT/IL2007/00201.

U.S. Appl. No. 60/654,013, filed Feb. 17, 2005.

U.S. Appl. No. 60/673,588, filed Apr. 21, 2005.

\* cited by examiner


*Primary Examiner*—Hoang V Nguyen

(74) *Attorney, Agent, or Firm*—Darby & Darby PC

(57) **ABSTRACT**

An antenna including a first monopole radiating element having a galvanic connection to an antenna feed and second and third monopole radiating elements having a capacitive connection to the antenna feed.

**20 Claims, 4 Drawing Sheets**





US007385561B2

(12) **United States Patent**  
**Krupa**

(10) **Patent No.:** **US 7,385,561 B2**  
(45) **Date of Patent:** **Jun. 10, 2008**

(54) **MULTIPLE MONOPOLE ANTENNA**  
(75) Inventor: **Steve Krupa**, Cambridge (GB)  
(73) Assignee: **Galtronics Ltd.**, Tiberias (IL)  
(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

5,406,295 A 4/1995 Baranski et al.  
5,617,102 A 4/1997 Prater  
5,764,190 A 6/1998 Murch et al.  
5,838,283 A 11/1998 Nakano  
6,680,705 B2 1/2004 Tan et al.  
6,853,339 B2 2/2005 Sievenpiper et al.  
6,888,511 B2 5/2005 Cake  
2004/0222922 A1\* 11/2004 Kuo et al. .... 343/700 MS  
2006/0071871 A1 4/2006 Tang et al.

(21) Appl. No.: **11/346,791**  
(22) Filed: **Feb. 3, 2006**

(65) **Prior Publication Data**  
US 2006/0181466 A1 Aug. 17, 2006

**OTHER PUBLICATIONS**

International Application No. PCT/IL06-00197 Search Report dated Mar. 1, 2007.

U.S. Appl. No. 60/654,013, no date avail.  
U.S. Appl. No. 60/673,588, filed Apr. 12, 2005.

\* cited by examiner

*Primary Examiner*—Hoang V Nguyen  
(74) *Attorney, Agent, or Firm*—Darby & Darby PC

**Related U.S. Application Data**  
(60) Provisional application No. 60/654,013, filed on Feb. 17, 2005, provisional application No. 60/673,588, filed on Apr. 21, 2005.


(51) **Int. Cl.**  
**H01Q 21/00** (2006.01)  
(52) **U.S. Cl.** ..... **343/728**; 343/725; 343/741;  
343/743; 343/866  
(58) **Field of Classification Search** ..... 343/866,  
343/870, 741, 700 MS, 713, 702, 725, 728,  
343/743

(57) **ABSTRACT**

The present invention seeks to provide a multiple monopole antenna including a looped conductor having at least two conductive arms extending therefrom and a common feed point located on the looped conductor.

(56) **References Cited**  
U.S. PATENT DOCUMENTS  
4,218,685 A 8/1980 Frosch et al.

**13 Claims, 2 Drawing Sheets**





US00D570800S

(12) **United States Design Patent** (10) **Patent No.:** **US D570,800 S**  
**Chen et al.** (45) **Date of Patent:** **\*\* Jun. 10, 2008**

(54) **ISM-BAND PRINTED ANTENNA FOR A PORTION OF A CIRCUIT BOARD**  
(75) Inventors: **Hui-Mei Chen**, Tainan County (TW);  
**Wei-Hsiu Hsu**, Taipei County (TW);  
**Huan-Ping Su**, Hsinchu (TW);  
**Chien-Hsin Su**, Hsinchu (TW)  
(73) Assignee: **Uniband Electronic Corp.** (TW)  
(\*\*) Term: **14 Years**  
(21) Appl. No.: **29/250,640**  
(22) Filed: **Nov. 27, 2006**  
(51) **LOC (8) Cl.** ..... **13-03**  
(52) **U.S. Cl.** ..... **D13/182**  
(58) **Field of Classification Search** ..... D13/182;  
D14/230; 343/700 MS, 795, 895  
See application file for complete search history.

2005/0035909 A1\* 2/2005 Lin ..... 343/700 MS  
2006/0145929 A1\* 7/2006 Teng et al. .... 343/700 MS  
2006/0152417 A1\* 7/2006 Ying et al. .... 343/702  
2006/0181478 A1\* 8/2006 Benato ..... 343/895  
2006/0213609 A1\* 9/2006 Green et al. .... 156/265  
2007/0013599 A1\* 1/2007 Gaucher et al. .... 343/795  
2007/0080869 A1\* 4/2007 Chen et al. .... 343/700 MS  
2007/0164920 A1\* 7/2007 Chen ..... 343/795  
2007/0229366 A1\* 10/2007 Kim et al. .... 343/700 MS  
2007/0279292 A1\* 12/2007 Shih ..... 343/700 MS  
2007/0279312 A1\* 12/2007 Mei et al. .... 343/845

\* cited by examiner

*Primary Examiner*—Selina Sikder

(57) **CLAIM**


The ornamental design for an ISM-band printed antenna for a portion of a circuit board, as shown and described.

**DESCRIPTION**

The single FIGURE is a front view of an ISM-band printed antenna for a portion of a circuit board showing the new design. The broken line drawing of an undefined portion of a circuit board is for illustrative purposes only and forms no part of the claimed design.

**1 Claim, 1 Drawing Sheet**

(56) **References Cited**  
U.S. PATENT DOCUMENTS  
6,329,962 B2\* 12/2001 Ying ..... 343/895  
D535,264 S \* 1/2007 Lai ..... D13/182  
2004/0252070 A1\* 12/2004 Chuang ..... 343/795





US007388543B2

(12) **United States Patent**  
**Vance**

(10) **Patent No.:** **US 7,388,543 B2**  
(45) **Date of Patent:** **Jun. 17, 2008**

(54) **MULTI-FREQUENCY BAND ANTENNA  
DEVICE FOR RADIO COMMUNICATION  
TERMINAL HAVING WIDE HIGH-BAND  
BANDWIDTH**

2006/0152411 A1\* 7/2006 Iguchi et al. .... 343/700 MS

FOREIGN PATENT DOCUMENTS

JP 2005020621 1/2005  
WO WO 03/075395 A2 9/2003  
WO WO 2005/038981 A1 4/2005

(75) Inventor: **Scott Vance**, Staffanstorp (SE)

\* cited by examiner

(73) Assignee: **Sony Ericsson Mobile  
Communications AB** (SE)

*Primary Examiner*—Huedung Mancuso

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 228 days.

(74) *Attorney, Agent, or Firm*—Myers Bigel Sibley & Sajovec, P.A.

(21) Appl. No.: **11/274,557**

(57) **ABSTRACT**

(22) Filed: **Nov. 15, 2005**

A multi-band radio antenna device for a radio communication terminal is disclosed. The antenna has an integral feed and ground structure electrically connected to a first radiating antenna element and a second radiating element. The first radiating element comprises a first continuous trace of conductive material and has a continuous trace has a first branch tuned to radiate at first frequencies in a first frequency band, and a second branch, which is tuned to radiate in a second frequency band at second frequencies approximately equal to or less than two times the first frequencies. The second radiating antenna element comprises a second continuous trace of conductive material, wherein the second continuous trace has a third branch, which is tuned to resonate in a third frequency band at third frequencies that are higher than the second frequencies, and which is capacitively coupled to the feed and ground structure and arranged substantially adjacent to the second branch. The first branch comprises a first section, composing approximately 1/3 to 2/3 of the total length of the first branch, wherein the first section is essentially straight and connected to said feed and ground structure at a first end thereof, and a second section in direct connection to a second end of said first section that is tightly meandered.

(65) **Prior Publication Data**

US 2007/0109202 A1 May 17, 2007

(51) **Int. Cl.**  
**H01Q 1/24** (2006.01)

(52) **U.S. Cl.** ..... **343/700 MS**

(58) **Field of Classification Search** ..... 343/700 MS,  
343/702, 895


See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

7,196,674 B2\* 3/2007 Timofeev et al. .... 343/810  
7,230,574 B2\* 6/2007 Johnson ..... 343/702  
2004/0137950 A1 7/2004 Bolin et al.  
2005/0093750 A1 5/2005 Vance  
2005/0110692 A1\* 5/2005 Andersson ..... 343/702  
2005/0237251 A1\* 10/2005 Boyle et al. .... 343/770  
2005/0248489 A1\* 11/2005 Kim et al. .... 343/702  
2006/0022889 A1\* 2/2006 Chiang et al. .... 343/833

**19 Claims, 8 Drawing Sheets**





US007388553B2

(12) **United States Patent**  
**Yuanzhu**

(10) **Patent No.:** **US 7,388,553 B2**  
(45) **Date of Patent:** **Jun. 17, 2008**

- (54) **ANTENNA DEVICE FOR VEHICLE**
- (75) Inventor: **Dou Yuanzhu**, Fukushima-ken (JP)
- (73) Assignee: **Alps Electric Co., Ltd**, Tokyo (JP)
- (\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

|                   |         |                      |            |
|-------------------|---------|----------------------|------------|
| 6,741,214 B1 *    | 5/2004  | Kadambi et al. ....  | 343/700 MS |
| 2003/0174092 A1 * | 9/2003  | Sullivan et al. .... | 343/702    |
| 2003/0189522 A1 * | 10/2003 | Zeilinger .....      | 343/702    |
| 2005/0122268 A1 * | 6/2005  | Suzuki .....         | 343/702    |
| 2006/0012524 A1 * | 1/2006  | Mierke et al. ....   | 343/700 MS |

**FOREIGN PATENT DOCUMENTS**

JP 2003-218629 7/2003

\* cited by examiner

*Primary Examiner*—Huedung Mancuso  
(74) *Attorney, Agent, or Firm*—Brinks Hofer Gilson & Lione

- (21) Appl. No.: **11/247,094**
- (22) Filed: **Oct. 6, 2005**

- (65) **Prior Publication Data**  
US 2006/0077113 A1 Apr. 13, 2006

- (30) **Foreign Application Priority Data**  
Oct. 12, 2004 (JP) ..... 2004-297736

- (51) **Int. Cl.**  
**H01Q 13/10** (2006.01)
- (52) **U.S. Cl.** ..... **343/770**
- (58) **Field of Classification Search** ..... **343/770,**  
**343/767, 700 MS, 702, 846-848**  
See application file for complete search history.


- (56) **References Cited**  
U.S. PATENT DOCUMENTS

|                |        |                   |            |
|----------------|--------|-------------------|------------|
| 5,912,647 A *  | 6/1999 | Tsuru et al. .... | 343/700 MS |
| 6,512,494 B1 * | 1/2003 | Diaz et al. ....  | 343/909    |

(57) **ABSTRACT**

An antenna device includes a circuit board, an upper shield case, a lower shield case, and a power feeding member. The circuit board has high frequency circuits arranged thereon. The upper shield case and the lower shield case cover the circuit board. The power feeding member extends from an upper plate of the upper shield case. Radiation slots and are formed in the upper plate. The power feeding member includes a horizontal portion, a bent portion, and a drooping portion, and a front end of the drooping portion is mounted on a land of the circuit board and soldered thereto. The horizontal portion protrudes from a base end which is continuous to the upper plate in a horizontal direction. The bent portion is formed by bending a front end of the horizontal portion at a right angle. The drooping portion extends downward from the bent portion.

**1 Claim, 2 Drawing Sheets**





US007391375B1

(12) **United States Patent**  
**Lin et al.**

(10) **Patent No.:** **US 7,391,375 B1**  
(45) **Date of Patent:** **Jun. 24, 2008**

(54) **MULTI-BAND ANTENNA**

(75) Inventors: **Ching-Chi Lin**, Taipei Hsien (TW);  
**Jia-Hung Su**, Taipei Hsien (TW); **Kai Shih**, Taipei Hsien (TW); **Yu-Yuan Wu**, Taipei Hsien (TW)

(73) Assignee: **Cheng Uei Precision Industry Co., Ltd.**, Taipei Hsien (TW)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **11/675,803**

(22) Filed: **Feb. 16, 2007**

(51) **Int. Cl.**  
**H01Q 1/38** (2006.01)  
**H01Q 1/24** (2006.01)  
**H01Q 1/48** (2006.01)

(52) **U.S. Cl.** ..... **343/700 MS; 343/702; 343/846**

(58) **Field of Classification Search** ..... **343/700 MS, 343/702, 767, 846, 893**  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

6,897,810 B2\* 5/2005 Dai et al. .... 343/700 MS

7,136,025 B2\* 11/2006 Lin et al. .... 343/770  
2005/0259024 A1\* 11/2005 Hung et al. .... 343/770  
2007/0188384 A1\* 8/2007 Liu ..... 343/700 MS

\* cited by examiner


*Primary Examiner*—Shih-Chao Chen

(74) *Attorney, Agent, or Firm*—WPAT, P.C.; Anthony King

(57) **ABSTRACT**

A multi-band antenna operates at a low frequency and a wider high frequency bands, which is formed as an elongated shape defining opposite ends. The multi-band antenna has a slot opened at a long edge and being extending to one end thereon. The wide range of the opening of the slot is larger than the extension length of the slot. A feeding conductor with a feeding point is arranged to adjoin the opening of the slot. The multi-band antenna resonates the low frequency band and a first high frequency. The slot obtains a second high frequency band higher than and partially overlapped the first high frequency. So the multi-band antenna has the low frequency bands and the better high frequency which includes several high frequency bands.

**20 Claims, 4 Drawing Sheets**





US007391376B2

(12) **United States Patent**  
**Yeh et al.**

(10) **Patent No.:** **US 7,391,376 B2**

(45) **Date of Patent:** **Jun. 24, 2008**

(54) **WIRELESS APPARATUS CAPABLE OF CONTROLLING RADIATION PATTERNS OF ANTENNA**

(58) **Field of Classification Search** ..... 343/700 MS, 343/702, 767, 829, 846  
See application file for complete search history.

(75) Inventors: **Shih-Huang Yeh**, Tou-Liu (TW);  
**Zih-Hao Lu**, Taichung Hsien (TW);  
**Chia-Lun Tang**, Miao-Li Hsien (TW)

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

|                   |         |                             |            |
|-------------------|---------|-----------------------------|------------|
| 5,402,132 A *     | 3/1995  | Hall et al. ....            | 342/432    |
| 7,002,527 B2 *    | 2/2006  | Sugawara .....              | 343/750    |
| 2004/0217916 A1 * | 11/2004 | Quintero Illera et al. .... | 343/895    |
| 2005/0259013 A1 * | 11/2005 | Gala Gala et al. ....       | 343/702    |
| 2005/0275591 A1 * | 12/2005 | King et al. ....            | 343/700 MS |

(73) Assignee: **Industrial Technology Research Institute**, Hsinchu (TW)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

\* cited by examiner

*Primary Examiner*—Tho G Phan

(21) Appl. No.: **11/762,763**

(57) **ABSTRACT**

(22) Filed: **Jun. 13, 2007**

A wireless apparatus capable of controlling radiation patterns and directions of antenna is provided. It comprises an antenna element, a ground plane, an antenna feed-point, and at least one slot or slit formed on the ground plane. The inclusion of such slots or slits in the wireless apparatus improves the radiation directivity of antenna, and greatly enhances the antenna gain on the horizontal plane. It also resolves the problems caused by shift of radiation patterns of antenna and the poor antenna gains for a conventional antenna apparatus. The wireless apparatus of the present invention has the advantages of simple structure and easy fabrication. The invention can be applied to various kinds of antennas, such as monopole antenna, shorted-monopole antenna, dipole antenna, loop antenna, and planar inverted-F antenna, etc.

(65) **Prior Publication Data**

US 2007/0236401 A1 Oct. 11, 2007

**Related U.S. Application Data**

(62) Division of application No. 11/221,148, filed on Sep. 7, 2005, now Pat. No. 7,352,327.


(30) **Foreign Application Priority Data**

May 5, 2005 (TW) ..... 94114506 A

(51) **Int. Cl.**  
**H01Q 1/24** (2006.01)

(52) **U.S. Cl.** ..... 343/700 MS; 343/846

**3 Claims, 9 Drawing Sheets**





US007391378B2

(12) **United States Patent**  
**Mikkola et al.**

(10) **Patent No.:** **US 7,391,378 B2**  
(45) **Date of Patent:** **Jun. 24, 2008**

(54) **ANTENNA ELEMENT FOR A RADIO DEVICE**

FOREIGN PATENT DOCUMENTS

(75) Inventors: **Jyrki Mikkola**, Kaustinen (FI); **Petteri Annamaa**, Oulunsalo (FI); **Esa Kalistaja**, Oulu (FI)

EP 0 851 530 A2 7/1998  
EP 0 923 158 A2 6/1999  
EP 1 067 627 A1 1/2001

(73) Assignees: **Filtronic LK Oy**, Kempele (FI); **LK Products Oy**, Kempele (FI); **Pulse Finland Oy**, Kempele (FI)

(Continued)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 464 days.

OTHER PUBLICATIONS

A Finnish Search Report, dated Sep. 26, 2003, which issued during the prosecution of Finnish Application No. 20030193 which corresponds to the present application.

(21) Appl. No.: **10/753,887**

(Continued)

(22) Filed: **Jan. 7, 2004**

*Primary Examiner*—Tan Ho

(65) **Prior Publication Data**

(74) *Attorney, Agent, or Firm*—Darby & Darby P.C.

US 2004/0147297 A1 Jul. 29, 2004

(30) **Foreign Application Priority Data**

(57) **ABSTRACT**

Jan. 15, 2003 (FI) ..... 20030059  
Feb. 7, 2003 (FI) ..... 20030193

A radiating antenna element intended to be used in small-sized radio devices, and a radio device having an antenna element according to the invention. The antenna element is part of the covers of a radio device. The antenna element may be conductive throughout, or it may comprise a dielectric portion and a conductive portion, which constitute a single integral component. The radiating portion of the antenna element is relatively large, e.g. in a foldable phone (20) the antenna element (200) may comprise the whole cover of a foldable part (21) except for the front side. The radiating element is advantageously fed electromagnetically through a feed element. As the radiating element is relatively large and is located on the outer surface of the device, the radiation characteristics of the antenna are good, and the space required by the antenna inside the device is relatively small.

(51) **Int. Cl.**

**H01Q 1/24** (2006.01)  
**H01Q 1/40** (2006.01)

(52) **U.S. Cl.** ..... 343/702; 343/872; 343/873

(58) **Field of Classification Search** ..... 343/702, 343/872, 873

See application file for complete search history.


(56) **References Cited**

U.S. PATENT DOCUMENTS

5,017,932 A 5/1991 Ushiyama et al.  
6,603,430 B1 \* 8/2003 Hill et al. .... 343/702

(Continued)

17 Claims, 5 Drawing Sheets







US007391379B1

(12) **United States Patent**  
**Bit-Babik et al.**

(10) **Patent No.:** **US 7,391,379 B1**  
(45) **Date of Patent:** **Jun. 24, 2008**

(54) **COMMUNICATION DEVICE WITH A WIDEBAND ANTENNA**

(75) Inventors: **Giorgi G. Bit-Babik**, Sunrise, FL (US);  
**Carlo Dinallo**, Plantation, FL (US);  
**Antonio Faraone**, Plantation, FL (US)

(73) Assignee: **Motorola, Inc.**, Schaumburg, IL (US)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **11/567,430**

(22) Filed: **Dec. 6, 2006**

(51) **Int. Cl.**  
**H01Q 1/24** (2006.01)

(52) **U.S. Cl.** ..... **343/702; 343/700 MS; 343/846**

(58) **Field of Classification Search** ..... **343/700 MS, 343/702, 846**  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

6,867,736 B2 3/2005 Faraone et al.  
6,982,675 B2\* 1/2006 Kwak et al. .... 343/702

2007/0069958 A1\* 3/2007 Ozkar ..... 343/700 MS  
2007/0268190 A1\* 11/2007 Huynh ..... 343/702

\* cited by examiner


*Primary Examiner*—Tan Ho

(74) *Attorney, Agent, or Firm*—James Lamb; Anthony P. Curtis

(57) **ABSTRACT**

An apparatus is disclosed for a communication device (100) with a wideband antenna (102) supporting at least two common and one differential resonant modes. An apparatus that incorporates teachings of the present invention may include, for example, the communication device having an antenna (102) that includes a ground structure (202), a first elongated conductor (204) spaced from the ground structure, a second elongated conductor (206) separated from the first elongated conductor, third and fourth conductors (212) each coupled to the first and second elongated conductors forming a gap (205), a ground conductor (208) coupling the ground structure to one among the first and second elongated conductors, and a signal feed conductor (210) coupling to one among the first and second elongated conductors spaced from the ground conductor. Additional embodiments are disclosed. A -10 dB bandwidth of at least 0.5 can be realized using electrical non-congruence.

**20 Claims, 4 Drawing Sheets**





US007391380B2

(12) **United States Patent**  
**Nevermann**

(10) **Patent No.:** **US 7,391,380 B2**  
(45) **Date of Patent:** **Jun. 24, 2008**

(54) **TELECOMMUNICATION ANTENNA**

|                |         |              |         |
|----------------|---------|--------------|---------|
| 6,680,703 B1   | 1/2004  | McConnell    |         |
| 6,703,974 B2 * | 3/2004  | White et al. | 342/361 |
| 7,120,399 B2 * | 10/2006 | Khorram      | 455/121 |
| 7,132,989 B1 * | 11/2006 | Poilasne     | 343/745 |
| 7,265,724 B1 * | 9/2007  | Tan et al.   | 343/702 |

(75) Inventor: **Peter Nevermann**, Langenfeld (DE)

(73) Assignee: **Lumberg Connect GmbH & Co. KG**,  
Schalksmuhle (DE)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

**FOREIGN PATENT DOCUMENTS**

DE 101 10 982 9/2002

(21) Appl. No.: **11/655,045**

(22) Filed: **Jan. 18, 2007**

\* cited by examiner

(65) **Prior Publication Data**

US 2007/0164915 A1 Jul. 19, 2007

*Primary Examiner*—Tho G Phan

(74) *Attorney, Agent, or Firm*—Andrew Wilford

(30) **Foreign Application Priority Data**

Jan. 19, 2006 (DE) ..... 10 2006 002 817

(57) **ABSTRACT**

(51) **Int. Cl.**  
**H01Q 1/24** (2006.01)

(52) **U.S. Cl.** ..... **343/702**; 343/700 MS;  
343/745; 342/361

(58) **Field of Classification Search** ..... 342/361,  
342/368; 455/295; 343/745, 700 MS, 702,  
343/829, 846

See application file for complete search history.


A telecommunication device has a permanently mounted antenna tuned to a predetermined resonant frequency and a housing formed of a plurality of parts one of which is removable. The one removable part, which may be an original element or an aftermarket add-on, changes the resonant frequency of the antenna when fitted to the housing. An electrically conductive passive correction element fixed in the one removable housing part is positioned therein and dimensioned such that when the one removable housing part is fitted to the housing the passive correction element cancels out the effect on the resonant frequency of the antenna by the one removable housing part.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,182,568 A \* 1/1993 Stamps et al. .... 343/702

**17 Claims, 3 Drawing Sheets**





US007391383B2

(12) **United States Patent**  
**Schantz**

(10) **Patent No.:** **US 7,391,383 B2**  
(45) **Date of Patent:** **Jun. 24, 2008**

(54) **CHIRAL POLARIZATION ULTRAWIDEBAND SLOT ANTENNA**

(75) Inventor: **Hans Gregory Schantz**, Huntsville, AL (US)

(73) Assignee: **Next-RE, Inc.**, Huntsville, AL (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 128 days.

(21) Appl. No.: **11/235,259**

(22) Filed: **Sep. 26, 2005**

(65) **Prior Publication Data**

US 2006/0028388 A1 Feb. 9, 2006

**Related U.S. Application Data**

(63) Continuation-in-part of application No. 10/714,046, filed on Nov. 14, 2003, now Pat. No. 6,950,064.

(60) Provisional application No. 60/438,724, filed on Jan. 8, 2003, provisional application No. 60/433,637, filed on Dec. 16, 2002.

(51) **Int. Cl.**  
**H01Q 1/10** (2006.01)

(52) **U.S. Cl.** ..... **343/767; 343/770**

(58) **Field of Classification Search** ..... **343/767, 343/770, 895**

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,568,159 A \* 10/1996 Pelton et al. .... 343/767

|                |        |                      |            |
|----------------|--------|----------------------|------------|
| 5,748,153 A *  | 5/1998 | McKinzie et al. .... | 343/767    |
| 5,764,696 A    | 6/1998 | Barnes et al.        |            |
| 6,091,374 A    | 7/2000 | Barnes               |            |
| 6,400,329 B1   | 6/2002 | Barnes               |            |
| 6,590,545 B2 * | 7/2003 | McCorkle .....       | 343/830    |
| 6,621,462 B2   | 9/2003 | Barnes               |            |
| 6,759,985 B2 * | 7/2004 | Acher et al. ....    | 343/700 MS |
| 6,950,064 B2 * | 9/2005 | Schantz .....        | 342/427    |


\* cited by examiner

Primary Examiner—Tan Ho

(57) **ABSTRACT**

A chiral polarization UWB slot antenna comprises a feed region and opposing tapered slot lines along an arcuate path of angle measure  $360^\circ$  or less. Opposing tapered slot lines may terminate in bulbous ends and may be characterized by an impedance profile such as an exponential or a Klopfenstein impedance profile. In alternate embodiments, an arcuate path has an arc length substantially equal to a half wavelength at a frequency of interest and an angle measure substantially equal to  $180^\circ$ . In still further alternate embodiments an arcuate path is substantially described by a radial variation with respect to angle of  $r(\phi) = R \sin \phi$  where R is a constant that in some embodiments is substantially equal to  $\frac{1}{2}\pi$  times wavelength ( $R = \lambda / (2\pi)$ ) at a particular frequency of interest. In some embodiments, a frequency of interest lies substantially within the range defined by 3.1 GHz to 10.6 GHz.

**16 Claims, 12 Drawing Sheets**





US007391384B2

(12) **United States Patent**  
**Wong et al.**

(10) **Patent No.:** **US 7,391,384 B2**  
(45) **Date of Patent:** **Jun. 24, 2008**

- (54) **DIGITAL-TELEVISION RECEIVING ANTENNA**
- (75) Inventors: **Kin-Lu Wong**, Kao-Hsiung (TW); **Yun-Wen Chi**, Taipei (TW); **Saou-Wen Su**, Taipei (TW)
- (73) Assignees: **Lite-On Technology Corp.**, Neihu, Taipei (TW); **National Sun Yat-Sen University**, Kaoshiung (TW)
- (\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.
- (21) Appl. No.: **11/464,498**
- (22) Filed: **Aug. 15, 2006**
- (65) **Prior Publication Data**  
US 2007/0195002 A1 Aug. 23, 2007
- (30) **Foreign Application Priority Data**  
Feb. 22, 2006 (TW) ..... 95105844 A
- (51) **Int. Cl.**  
**H01Q 9/28** (2006.01)  
**H01Q 9/16** (2006.01)  
**H01Q 13/10** (2006.01)  
**H01Q 1/38** (2006.01)
- (52) **U.S. Cl.** ..... **343/795**; 343/793; 343/767; 343/700 MS
- (58) **Field of Classification Search** ..... 343/795, 343/700 MS, 793, 767  
See application file for complete search history.


- (56) **References Cited**
- U.S. PATENT DOCUMENTS
- 5,182,570 A \* 1/1993 Nysen et al. .... 343/795
- 6,624,793 B1 \* 9/2003 Su et al. .... 343/795
- 7,151,500 B2 \* 12/2006 Su et al. .... 343/795
- 2004/0222936 A1 \* 11/2004 Hung et al. .... 343/795
- 2006/0284780 A1 \* 12/2006 Chen et al. .... 343/795

- FOREIGN PATENT DOCUMENTS
- TW 521455 2/2003
- \* cited by examiner
- Primary Examiner*—Hoang V Nguyen
- Assistant Examiner*—Robert Karacsony
- (74) *Attorney, Agent, or Firm*—Winston Hsu

(57) **ABSTRACT**

A receiving antenna for digital television signal reception includes a dielectric substrate, a radiating plate formed on the dielectric substrate with a bar shape, having a first long edge and a second long edge corresponding to the first long edge, a slit formed on the radiating plate with a length at least two times the width of the radiating plate, having a terminal at about the center of the first long edge and a terminal at the second long edge, and separating the radiating plate into a first sub-plate and a second sub-plate, a first feeding point formed on the first sub-plate, a second feeding point formed on the second sub-plate, and a feeding coaxial cable having a core conductor connected to the first feeding point and a grounding conductor connected to the second feeding point.

**9 Claims, 10 Drawing Sheets**





US007391385B1

(12) **United States Patent**  
**Thomas**

(10) **Patent No.:** **US 7,391,385 B1**  
(45) **Date of Patent:** **Jun. 24, 2008**

(54) **DIRECTIONAL ANTENNA**

(76) Inventor: **Harold J. Thomas**, 341 Redwood La.,  
La Habra, CA (US) 90631

|                 |         |                 |         |
|-----------------|---------|-----------------|---------|
| 3,618,103 A     | 11/1971 | Ringland        |         |
| 4,355,315 A     | 10/1982 | Zoulek          |         |
| 4,398,201 A *   | 8/1983  | Winegard et al. | 343/815 |
| 5,841,406 A *   | 11/1998 | Smith           | 343/815 |
| 2006/0139231 A1 | 6/2006  | Kimura          |         |

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

\* cited by examiner

*Primary Examiner*—Hoang V Nguyen

(74) *Attorney, Agent, or Firm*—Kenneth L. Green; Edgar W. Averill, Jr.; Calvin J. Eustaquio

(21) Appl. No.: **11/776,455**

(22) Filed: **Jul. 11, 2007**

(57) **ABSTRACT**

(51) **Int. Cl.**  
**H01Q 21/12** (2006.01)

(52) **U.S. Cl.** ..... **343/815**; 343/812; 343/817;  
343/818; 343/890

(58) **Field of Classification Search** ..... 343/812,  
343/815, 817, 818, 819, 874, 890, 891  
See application file for complete search history.


An antenna array includes an upper antenna and a lower antenna. Each antenna includes a driver dipole element and a director element horizontally spaced apart approximately one eighth wavelength from the driver dipole element. The driver dipole element is preferably approximately one half wavelength in overall length and the director element is preferably one half wavelength in length. The upper antenna is vertically spaced above the ground by approximately one wavelength and the upper and lower antennas are vertically spaced approximately one half wavelength apart. A preferred use of the antenna array is as an amateur radio antenna and a preferred frequency band is 14.0 to 14.350 MHz corresponding to an approximately 20 meter wavelength.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

|               |         |          |         |
|---------------|---------|----------|---------|
| 2,183,784 A   | 12/1939 | Carter   |         |
| 2,586,276 A   | 2/1952  | Umstead  |         |
| 2,598,005 A   | 5/1952  | Lippitt  |         |
| 2,655,600 A * | 10/1953 | Hillison | 343/815 |
| 3,371,348 A   | 2/1968  | Simons   |         |

**13 Claims, 3 Drawing Sheets**





US00D571793S

(12) **United States Design Patent**  
**Wu et al.**

(10) **Patent No.:** **US D571,793 S**  
(45) **Date of Patent:** **\*\* Jun. 24, 2008**

(54) **ANTENNA**

(75) Inventors: **Xiao-Gang Wu**, Kunshan (CN);  
**Ping-Sheng Su**, Tu-Cheng (TW)

(73) Assignee: **Hon Hai Precision Ind. Co., Ltd.**,  
Taipei Hsien (TW)

(\*\*) Term: **14 Years**

(21) Appl. No.: **29/293,616**

(22) Filed: **Dec. 4, 2007**

(30) **Foreign Application Priority Data**  
Sep. 29, 2007 (CN) ..... 2007 3 0189262

(51) **LOC (8) Cl.** ..... **14-03**

(52) **U.S. Cl.** ..... **D14/230; D14/238**

(58) **Field of Classification Search** ..... D14/138,  
D14/230-238, 299, 358; D12/42, 43; 343/700 R-705,  
343/871, 908, 795, 840, 711-713, 819, 846;  
455/90.2, 90.3, 91, 128, 269, 344, 347, 562.1;  
D8/395, 72; D28/40; 24/97.3  
See application file for complete search history.

(56) **References Cited**  
**U.S. PATENT DOCUMENTS**  
D254,060 S \* 1/1980 Spellins et al. .... D12/96  
D379,356 S \* 5/1997 Liu et al. .... D14/230

D398,611 S \* 9/1998 Read ..... D14/230  
D405,090 S \* 2/1999 Guttadauro ..... D14/230  
D533,544 S \* 12/2006 Lai ..... D14/230  
D559,838 S \* 1/2008 Yuba et al. .... D14/230

\* cited by examiner

*Primary Examiner*—Robert M. Spear  
*Assistant Examiner*—John Windmuller  
(74) *Attorney, Agent, or Firm*—Wei Te Chung

(57) **CLAIM**

The ornamental design for an antenna, as shown.

**DESCRIPTION**

FIG. 1 is a perspective view of an antenna showing our new design;  
FIG. 2 is a front elevational view thereof;  
FIG. 3 is a rear elevational view thereof;  
FIG. 4 is a left side elevational view thereof;  
FIG. 5 is a right side elevational view thereof;  
FIG. 6 is a top plan view thereof; and,  
FIG. 7 is a bottom plan view thereof.

The broken line showing of rectangular shapes in FIGS. 3 and 6 illustrates environment only and forms no part of the claimed design.

**1 Claim, 7 Drawing Sheets**

