



US007408510B2

(12) **United States Patent**
Yamamoto et al.

(10) **Patent No.:** **US 7,408,510 B2**
(45) **Date of Patent:** **Aug. 5, 2008**

- (54) **PATCH ANTENNA**
- (75) Inventors: **Sadahiko Yamamoto**, Osaka (JP);
Kazuhiro Kitatani, Osaka (JP);
Hidehisa Shiomi, Osaka (JP)
- (73) Assignee: **SANYO Electric Co., Ltd.**, Osaka (JP)
- (*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 52 days.
- (21) Appl. No.: **10/566,817**
- (22) PCT Filed: **Jul. 30, 2004**
- (86) PCT No.: **PCT/JP2004/011330**

§ 371 (c)(1),
(2), (4) Date: **Jan. 26, 2006**
- (87) PCT Pub. No.: **WO2005/013418**

PCT Pub. Date: **Feb. 10, 2005**
- (65) **Prior Publication Data**
US 2006/0227051 A1 Oct. 12, 2006
- (30) **Foreign Application Priority Data**
Aug. 1, 2003 (JP) 2003-284755
- (51) **Int. Cl.**
H01Q 1/38 (2006.01)
- (52) **U.S. Cl.** **343/700 MS; 343/700 MS;**
343/702; 343/828; 343/829; 343/846

(58) **Field of Classification Search** 343/700 MS,
343/702
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2002/0068602 A1* 6/2002 Kuriyama et al. 455/550
2004/0145528 A1* 7/2004 Mukai et al. 343/702

FOREIGN PATENT DOCUMENTS

JP 01-204342 3/1991 13/8
JP 03-307021 5/1993 13/8
JP 03-234110 3/1994 13/8
JP 2000-366700 6/2002 1/38
JP 2001-014689 8/2002 13/8
JP 2005 269366 A * 9/2005


* cited by examiner

Primary Examiner—Trinh V Dinh
(74) *Attorney, Agent, or Firm*—Gerald T. Bodner

(57) **ABSTRACT**

A patch antenna (10) includes a dielectric substrate (12), a patch conductor (14) and a ground conductor (18) formed on both surfaces thereof. A step (16) is formed on the lower surface of the dielectric substrate, which makes a spacing between the patch conductor and the ground conductor non-uniform in a direction of length of the patch conductor. By making nonuniform the spacing between the patch conductor and the ground conductor in the direction of length of the patch conductor, radiation efficiency and antenna gain are changed in that direction, resulting in asymmetrical directivity.

6 Claims, 7 Drawing Sheets





US007408511B2

(12) **United States Patent**
Liu

(10) **Patent No.:** **US 7,408,511 B2**
(45) **Date of Patent:** **Aug. 5, 2008**

(54) **MIMO ANTENNA CONFIGURATION**

(75) Inventor: **I-Ru Liu**, Taipei (TW)

(73) Assignee: **Accton Technology Corporation**,
Hsinchu (TW)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 247 days.

(21) Appl. No.: **11/342,708**

(22) Filed: **Jan. 31, 2006**

(65) **Prior Publication Data**

US 2007/0176829 A1 Aug. 2, 2007

(51) **Int. Cl.**
H01Q 1/38 (2006.01)
H01Q 1/42 (2006.01)
H01Q 9/16 (2006.01)

(52) **U.S. Cl.** **343/700 MS**; 343/872;
343/793

(58) **Field of Classification Search** 343/700 MS,
343/793, 872, 893

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,426,723 B1* 7/2002 Smith et al. 343/700 MS
7,119,744 B2* 10/2006 Theobald et al. 343/700 MS
2003/0134596 A1* 7/2003 Zhu 455/41


* cited by examiner

Primary Examiner—Shih-Chao Chen
(74) *Attorney, Agent, or Firm*—Birch, Stewart, Kolasch & Birch, LLP

(57) **ABSTRACT**

The present invention provides a MIMO antenna structure and design. A single dipole antenna stands at the center of a triangle which is formed by three PIFAs antennas, and the three PIFA antennas has equal squint angle relative to the neighbors, that is there is 120° sector angle between any two PIFA axes of three such that the dipole and the other PIFAs forms a tetrahedron. The MIMO antenna structure of the present invention is simpler in mechanics but high efficiency in performance.

22 Claims, 7 Drawing Sheets



Convex Cubical antenna Structure
($0^\circ \leq \phi \leq 360^\circ$, $0^\circ \leq \theta \leq 90^\circ$ symmetrically)



US007408512B1

(12) **United States Patent**
Rodenbeck et al.

(10) **Patent No.:** **US 7,408,512 B1**
(45) **Date of Patent:** **Aug. 5, 2008**

(54) **ANTENNA WITH DISTRIBUTED STRIP AND INTEGRATED ELECTRONIC COMPONENTS**

(75) Inventors: **Christopher T. Rodenbeck**, Albuquerque, NM (US); **Jason A. Payne**, Albuquerque, NM (US); **Cory W. Ottesen**, Albuquerque, NM (US)

(73) Assignee: **Sandie Corporation**, Albuquerque, MN (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 359 days.

(21) Appl. No.: **11/415,931**

(22) Filed: **May 2, 2006**

Related U.S. Application Data

(63) Continuation-in-part of application No. 11/243,860, filed on Oct. 5, 2005, now Pat. No. 7,345,647.

(51) **Int. Cl.**
H01Q 1/38 (2006.01)

(52) **U.S. Cl.** **343/700 MS**

(58) **Field of Classification Search** 343/895, 343/700 MS, 702, 767, 749, 830, 846
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,903,326	A	2/1990	Zakman et al.	
5,532,708	A	7/1996	Krenz et al.	
5,703,932	A	12/1997	Oda	
5,838,285	A *	11/1998	Tay et al.	343/895
5,936,587	A *	8/1999	Gudilev et al.	343/752
5,995,006	A *	11/1999	Walsh	340/572.7
6,028,555	A	2/2000	Harano	
6,045,652	A	4/2000	Tuttle et al.	
6,166,694	A *	12/2000	Ying	343/702

6,181,283	B1	1/2001	Johnson et al.	
6,252,550	B1 *	6/2001	Vernon	343/700 MS
6,285,342	B1	9/2001	Brady et al.	
6,327,154	B1	12/2001	Gauld et al.	
6,388,626	B1 *	5/2002	Gamalielsson et al.	343/702
6,424,301	B1	7/2002	Johnson et al.	
6,504,508	B2 *	1/2003	Apostolos	343/700 MS
6,535,166	B1	3/2003	Ali	
6,661,381	B2	12/2003	Chen	

(Continued)

OTHER PUBLICATIONS

"Using Text as a Meander Line for RFID Transponder Antennas", Mikko Keskilammi, et al., IEEE Antennas and Wireless Propagation Letters, pp. 372-374, vol. 3, 2004.


(Continued)

Primary Examiner—Huedung Cao Mancuso
(74) *Attorney, Agent, or Firm*—William R. Conley

(57) **ABSTRACT**

An antenna comprises electrical conductors arranged to form a radiating element including a folded line configuration and a distributed strip configuration, where the radiating element can be in proximity to a ground conductor and/or arranged as a dipole. Embodiments of the antenna include conductor patterns formed on a printed wiring board, having a ground plane, spacedly adjacent to and coplanar with the radiating element. An antenna can comprise a distributed strip patterned on a printed wiring board, integrated with electronic components mounted on top of or below the distributed strip, and substantially within the extents of the distributed strip. Mounting of electronic components on top of or below the distributed strip has little effect on the performance of the antenna, and allows for realizing the combination of the antenna and integrated components in a compact form. An embodiment of the invention comprises an antenna including a distributed strip, integrated with a battery mounted on the distributed strip.

24 Claims, 13 Drawing Sheets





US007408513B1

(12) **United States Patent**
Yanagi et al.

(10) **Patent No.:** **US 7,408,513 B1**
(45) **Date of Patent:** **Aug. 5, 2008**

(54) **ANTENNA APPARATUS**

(75) Inventors: **Masahiro Yanagi**, Shinagawa (JP);
Shigemi Kurashima, Shinagawa (JP);
Hideki Iwata, Shinagawa (JP); **Takashi**
Yuba, Shinagawa (JP); **Masahiro**
Kaneko, Shinagawa (JP); **Yuriko**
Segawa, Shinagawa (JP); **Takashi Arita**,
Shinagawa (JP)

(73) Assignee: **Fujitsu Component Limited**, Tokyo
(JP)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **11/580,910**

(22) Filed: **Oct. 16, 2006**

(30) **Foreign Application Priority Data**

Mar. 30, 2006 (JP) 2006-094459

(51) **Int. Cl.**
H01Q 1/38 (2006.01)
H01Q 1/50 (2006.01)

(52) **U.S. Cl.** **343/700 MS; 343/702;**
343/906; 343/846

(58) **Field of Classification Search** 343/700 MS,
343/846, 702, 906

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,509,877 B2 * 1/2003 Masaki 343/702
6,642,892 B2 * 11/2003 Masaki et al. 343/702

FOREIGN PATENT DOCUMENTS

JP 2000-196327 7/2000

OTHER PUBLICATIONS

2003 IEICE (The Institute of Electronics, Information and Commu-
nication Engineers) General Conference, Mar. 22, 2003, Room B201,
B-1-133: An Omnidirectional and Low-VSWR Antenna for the FCC-
Approved UWB Frequency Band, Takuya Taniguchi and Takehiko
Kobayashi (Tokyo Denki University).

* cited by examiner


Primary Examiner—Hoang V Nguyen

(74) *Attorney, Agent, or Firm*—Staas & Halsey LLP

(57) **ABSTRACT**

A disclosed antenna apparatus includes a base made of a
dielectric material; an antenna element pattern formed on a
surface of the base; a ground pattern formed in a position
adjacent to and opposite to the antenna element pattern on the
same surface of the base; and a surface-mounted coaxial
connector mounted on the ground pattern in a position close to
a feeding point of the antenna element pattern.

7 Claims, 7 Drawing Sheets





US007408515B2

(12) **United States Patent**
Leisten

(10) **Patent No.:** **US 7,408,515 B2**
(45) **Date of Patent:** **Aug. 5, 2008**

(54) **MOBILE COMMUNICATION DEVICE AND AN ANTENNA ASSEMBLY FOR THE DEVICE**

(75) Inventor: **Oliver Paul Leisten**, Northampton (GB)

(73) Assignee: **Sarantel Limited**, Wellingborough (GB)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 108 days.

(21) Appl. No.: **11/263,643**

(22) Filed: **Oct. 31, 2005**

(65) **Prior Publication Data**

US 2007/0063902 A1 Mar. 22, 2007

(30) **Foreign Application Priority Data**

Sep. 22, 2005 (GB) 0519371.9

(51) **Int. Cl.**
H01Q 1/24 (2006.01)

(52) **U.S. Cl.** **343/702; 343/895**

(58) **Field of Classification Search** **343/700 MS, 343/702, 846, 895**

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

- 4,008,479 A * 2/1977 Smith 343/895
- 5,650,792 A 7/1997 Moore et al.
- 5,784,034 A * 7/1998 Konishi et al. 343/895
- 5,910,790 A * 6/1999 Ohmuro et al. 343/895
- 5,945,963 A * 8/1999 Leisten 343/895
- 6,222,505 B1 * 4/2001 Endo et al. 343/895
- 6,600,450 B1 7/2003 Efanov et al.
- 2002/0123312 A1 9/2002 Hayes et al.
- 2002/0180649 A1 12/2002 Iguchi et al.

FOREIGN PATENT DOCUMENTS

EP	0957533	11/1999
EP	11182727	8/2003
EP	1505689	2/2005
GB	2292638	2/1996
GB	2410837	8/2005
JP	2224506	9/1990

OTHER PUBLICATIONS

A. Wingfield, O.P. Leisten, "12th Int. Conf. on Antennas and Propagation", published 2003, Vol. 1, pp. 39-42, "Performance Evaluation of Small Antennas for Global Positioning System (GPS)".
International search report from PCT/GB2006/003318, Nov. 15, 2006.

* cited by examiner


Primary Examiner—Tho G Phan

(74) *Attorney, Agent, or Firm*—John Bruckner PC

(57) **ABSTRACT**

A mobile communication device has an antenna assembly comprising the combination of an inverted-F antenna and a dielectrically-loaded quadrifilar helical antenna, the latter mounted on the distal end of an elongate radiator element of the inverted-F antenna. The dielectrically-loaded antenna has an integral balun on a ceramic antenna core, the balun providing a balanced feed for the radiating elements of the antenna. The elongate radiator structure of the inverted-F antenna acts as a feed path for the dielectrically-loaded antenna, the feed path extending along the elongate radiator structure from the balun to a ground connection element of the inverted-F antenna and, thence, to a signal port associated with a grounding connection of the inverted-F antenna. Placing the dielectrically-loaded quadrifilar antenna at the end of the radiator structure of the inverted-F antenna rather than alongside the latter substantially reduces breakthrough from a transmitter coupled to the inverted-F antenna to receiving circuitry coupled to the dielectrically-loaded antenna.

28 Claims, 6 Drawing Sheets





US007408517B1

(12) **United States Patent**
Poilasne et al.

(10) **Patent No.:** **US 7,408,517 B1**
(45) **Date of Patent:** **Aug. 5, 2008**

(54) **TUNABLE CAPACITIVELY-LOADED
MAGNETIC DIPOLE ANTENNA**

(75) Inventors: **Gregory Poilasne**, San Diego, CA (US);
Vanceet Pathak, San Diego, CA (US);
Jordi Fabrega, San Diego, CA (US);
Huan-Sheng Hwang, San Diego, CA
(US)

(73) Assignee: **Kyocera Wireless Corp.**, San Diego,
CA (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 121 days.

(21) Appl. No.: **11/339,926**

(22) Filed: **Jan. 25, 2006**

Related U.S. Application Data

(63) Continuation-in-part of application No. 10/940,935,
filed on Sep. 14, 2004, now Pat. No. 7,239,290.

(51) **Int. Cl.**
H01Q 11/12 (2006.01)

(52) **U.S. Cl.** **343/742; 343/867; 343/793;**
343/702

(58) **Field of Classification Search** 343/742,
343/866, 867, 702, 793
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,882,506 A 5/1975 Mori et al.
H1571 H 8/1996 Hansen et al.
6,144,346 A 11/2000 Boy
6,204,817 B1 3/2001 Edvardsson
6,456,243 B1 9/2002 Poilasne et al.
6,486,848 B1 11/2002 Poilasne et al.
6,573,867 B1 6/2003 Desclos et al.

6,593,886 B2* 7/2003 Schantz 343/700 MS
6,600,450 B1 7/2003 Efanov et al.
6,624,795 B2* 9/2003 Boyle 343/895
6,675,461 B1 1/2004 Rowson et al.
6,693,599 B1 2/2004 Chia et al.
6,697,025 B2 2/2004 Koyanagi et al.
6,765,846 B2 7/2004 Saitou et al.
6,958,735 B2* 10/2005 Handelsman 343/742
7,187,332 B2* 3/2007 Kezys et al. 343/702
2006/0038730 A1 2/2006 Parsche
2006/0079177 A1* 4/2006 Okubora 455/25

FOREIGN PATENT DOCUMENTS

DE 88 14 993 4/1989
EP 1 134 840 9/2001
EP 1 217 685 6/2002
WO WO 02/071536 9/2002


* cited by examiner

Primary Examiner—Trinh Vo Dinh
Assistant Examiner—Dieu Hien T Duong

(57) **ABSTRACT**

A frequency-tunable capacitively-loaded magnetic dipole antenna includes a transformer loop having a balanced feed interface, and a capacitively-loaded magnetic dipole radiator with a tunable effective electrical length. In one embodiment, the capacitively-loaded magnetic dipole radiator includes a tunable electric field bridge. For example, the capacitively-loaded magnetic dipole radiator may comprise a quasi loop with a tunable electric field bridge interposed between the quasi loop first and second ends. The electric field bridge may be an element such as a ferroelectric (FE) tunable capacitor or a microelectromechanical system (MEMS) capacitor, to name a couple of examples. In certain embodiments, the capacitively-loaded magnetic dipole radiator includes a quasi loop with a loop perimeter. The effective electrical length of the radiator is changed by adjusting the perimeter using an element such as a MEMS switch, or a semiconductor switch.

20 Claims, 5 Drawing Sheets





US007408522B2

(12) **United States Patent**
Ahn et al.

(10) **Patent No.:** **US 7,408,522 B2**
(45) **Date of Patent:** **Aug. 5, 2008**

(54) **ANTENNA-FEEDER DEVICE AND ANTENNA**

(75) Inventors: **Jiho Ahn**, 105-601, Samhwan Apt.,
897-2, Shingil 7-Dong,
Yongdeungpo-Gu, Seoul (KR); **Sergey**
Bankov, Moscow (RU); **Alexander**
Davydov, Kanischevo (RU)

1,804,673 A 5/1931 Chace
3,710,341 A * 1/1973 Sciambi, Jr. 343/779
5,243,357 A 9/1993 Koike et al.
6,603,437 B2 8/2003 Chang
6,697,028 B1 * 2/2004 Gothard et al. 343/781 CA
6,985,120 B2 * 1/2006 Lewry et al. 343/781 CA
7,187,340 B2 * 3/2007 Kralovec et al. 343/781 CA

(73) Assignee: **Jiho Ahn**, Shingil 7-Dong,
Yongdeungpo-Gu, Seoul (KR)

FOREIGN PATENT DOCUMENTS

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 164 days.

GB 973583 4/1963
JP 61-245605 10/1986

(21) Appl. No.: **11/287,979**

* cited by examiner

(22) Filed: **Nov. 28, 2005**

Primary Examiner—Tho G Phan

(74) *Attorney, Agent, or Firm*—Park Law Firm; John K. Park

(65) **Prior Publication Data**

US 2006/0267852 A1 Nov. 30, 2006

(57) **ABSTRACT**

(30) **Foreign Application Priority Data**

May 31, 2005 (RU) 2005116584

An antenna comprises: a main reflector being a body of revolution of parabolic shape; a sub-reflector being a body of the revolution of elliptic shape having a circle and a vertex oriented to the main reflector and being placed between the circle and the main reflector, one focal point of the sub-reflector being placed on the axis of revolution and the other focal point of the sub-reflector being placed out of the axis, the sub-reflector circle being placed in the plane of the main reflector edge circle; a radiator being placed along the axis of revolution of the main reflector and being placed between the main reflector and the sub-reflector; and wherein the sub-reflector has eccentricity ranging from 0.55 to 0.75.

(51) **Int. Cl.**

H01Q 13/00 (2006.01)

(52) **U.S. Cl.** **343/781 CA; 343/781 P**

(58) **Field of Classification Search** **343/781 CA,**
343/781 P, 836, 837, 840


See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

588,863 A 8/1897 Harry

14 Claims, 8 Drawing Sheets





US007408524B2

(12) **United States Patent**
Ogino

(10) **Patent No.:** **US 7,408,524 B2**
(45) **Date of Patent:** **Aug. 5, 2008**

(54) **LOOP ANTENNA**

7,253,773 B2* 8/2007 Chiba et al. 343/702

(75) Inventor: **Kazushige Ogino**, Kobe (JP)

FOREIGN PATENT DOCUMENTS

(73) Assignee: **Fujitsu Ten Limited**, Kobe-shi (JP)

JP	9-148838	6/1997
JP	2000-269724	9/2000
JP	2002-135045	5/2002
JP	2003-198410	7/2003
JP	2004-88218	3/2004

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 55 days.

OTHER PUBLICATIONS

(21) Appl. No.: **11/391,756**

Patent Abstract of Japan, Publication No. 09-148838, published Jun. 6, 1997, in the name of Ito, Sadao.

(22) Filed: **Mar. 28, 2006**

Patent Abstract of Japan, Publication No. 2000-269724, published Sep. 29, 2000, in the name of Sato, Sakiko.

(65) **Prior Publication Data**

US 2006/0220977 A1 Oct. 5, 2006

Patent Abstract of Japan, Publication No. 2002-135045, published May 10, 2002, in the name of Ogino, Kazushige.

(30) **Foreign Application Priority Data**

Mar. 29, 2005 (JP) 2005-095516
Feb. 7, 2006 (JP) 2006-029953

Computer generated English translation of Japan Publication 2002-135045, published May 10, 2002.

Patent Abstract of Japan, Publication No. 2003-198410, published Jul. 11, 2003, in the name of Ito, Hideo.

Patent Abstract of Japan, Publication No. 2004-088218, published Mar. 18, 2004, in the name of Wakabayashi, Toshio.

* cited by examiner

(51) **Int. Cl.**

H01Q 7/00 (2006.01)
H01Q 1/32 (2006.01)

Primary Examiner—Huedung Mancuso

(74) *Attorney, Agent, or Firm*—Christie, Parker & Hale, LLP

(52) **U.S. Cl.** **343/866; 343/713**

(58) **Field of Classification Search** 343/866,
343/702, 741, 700 MS, 855

See application file for complete search history.

(57) **ABSTRACT**


A loop antenna providing a reception performance equivalent to a patch antenna receiving a circularly polarized wave, simple in configuration, and kept low in cost, which forms a loop element and a parasitic element provided independently of this loop element on the same dielectric board to form an antenna element and sends or receives a circularly polarized wave by this antenna element, provides a metal plate parallel with or having a slight inclination with respect to the dielectric board, and sets this metal plate separated from the dielectric board by exactly a predetermined distance.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,371,507 A *	12/1994	Kuroda et al.	343/700 MS
5,557,293 A *	9/1996	McCoy et al.	343/867
5,926,139 A *	7/1999	Korisch	343/702
6,016,128 A *	1/2000	Imamura et al.	343/741
6,236,368 B1 *	5/2001	Johson	343/702
6,924,769 B2	8/2005	Ito et al.	
7,215,293 B2 *	5/2007	Chen et al.	343/741

16 Claims, 16 Drawing Sheets





US007411552B2

(12) **United States Patent**
King et al.

(10) **Patent No.:** **US 7,411,552 B2**
(45) **Date of Patent:** **Aug. 12, 2008**

(54) **GROUNDING ANTENNA FOR A WIRELESS COMMUNICATION DEVICE AND METHOD**

4,410,890 A 10/1983 Davis
4,530,483 A 7/1985 Nordstrom
4,545,761 A 10/1985 Cartwright

(75) Inventors: **Patrick F King**, Glen Ellyn, IL (US);
Ian J Forster, Essex (GB)

(73) Assignee: **Mineral Lassen LLC**, Las Vegas, NV (US)

(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 42 days.

FOREIGN PATENT DOCUMENTS

DE 3247 425 A1 12/1982

(21) Appl. No.: **11/506,407**

(Continued)

(22) Filed: **Aug. 17, 2006**

OTHER PUBLICATIONS

(65) **Prior Publication Data**

US 2007/0171139 A1 Jul. 26, 2007

Cho, Y.K., et al., "Improved Analysis Method for Broadband Rectangular Microstrip Antenna Geometry Using E-Plane Gap Coupling," *Electronics Letters* 29(22):1907-1909, Oct. 28, 1993.

Related U.S. Application Data

(Continued)

(63) Continuation of application No. 10/131,575, filed on Apr. 24, 2002, now Pat. No. 7,098,850, which is a continuation-in-part of application No. 09/678,271, filed on Oct. 3, 2000, now Pat. No. 6,501,435, which is a continuation-in-part of application No. 09/618,505, filed on Jul. 18, 2000, now Pat. No. 6,483,473.

Primary Examiner—Shih-Chao Chen

(74) *Attorney, Agent, or Firm*—Christensen O'Connor Johnson Kindness PLLC

(51) **Int. Cl.**

H01Q 1/38 (2006.01)

G08B 13/14 (2006.01)

(52) **U.S. Cl.** **343/700 MS; 340/572.1**

(58) **Field of Classification Search** **343/700 MS, 343/793, 795, 893, 846; 340/572.1**

See application file for complete search history.

(57) **ABSTRACT**



A wireless communication device includes an antenna for wireless communication with a remote interrogator. Several embodiments are disclosed to increase the options available to designers of wireless communication devices. In some embodiments, the antenna is a quarter wavelength long with one end of the antenna being grounded to provide desired impedance matching characteristics. The position of the ground plane relative to the antenna is also varied between embodiments. The connection from a wireless communication chip to the antenna is also varied between embodiments to provide alternate structures.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,507,528 A 5/1950 Kandoian
3,972,049 A 7/1976 Kaloi
4,054,886 A 10/1977 Bergander
4,117,489 A 9/1978 Kaloi
4,278,186 A 7/1981 Williamson

36 Claims, 30 Drawing Sheets





US007411554B2

(12) **United States Patent**
Jung et al.

(10) **Patent No.:** **US 7,411,554 B2**
(45) **Date of Patent:** **Aug. 12, 2008**

(54) **MIMO ANTENNA OPERABLE IN MULTIBAND**

(75) Inventors: **Chang-won Jung**, Yongin-si (KR);
Byung-tae Yoon, Yongin-si (KR);
Young-eil Kim, Yongin-si (KR);
Se-hyun Park, Yongin-si (KR)

(73) Assignee: **Samsung Electronics Co., Ltd.**, Suwon (KR)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **11/637,663**

(22) Filed: **Dec. 13, 2006**

(65) **Prior Publication Data**

US 2008/0018539 A1 Jan. 24, 2008

(30) **Foreign Application Priority Data**

Jul. 20, 2006 (KR) 10-2006-0068208

(51) **Int. Cl.**
H01Q 1/38 (2006.01)
H01Q 3/24 (2006.01)

(52) **U.S. Cl.** **343/700 MS; 343/876**

(58) **Field of Classification Search** **343/700 MS, 343/702, 754, 876, 850, 853, 895**
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,511,238 A * 4/1996 Bayraktaroglu 455/81
6,061,024 A * 5/2000 McGirr et al. 343/700 MS
6,806,843 B2 * 10/2004 Killen et al. 343/795

* cited by examiner


Primary Examiner—Hoang V Nguyen

(74) *Attorney, Agent, or Firm*—Sughrue Mion, PLLC

(57) **ABSTRACT**

A multiple-input multiple-output (MIMO) antenna operable in a multiband includes a plurality of antenna elements each including a radiator radiating electromagnetic waves, a ground connected to the radiator, at least one switching element mounted in an area of lengthwise direction of the radiator and short-circuiting or opening the area of the radiator.

16 Claims, 6 Drawing Sheets





US007411555B2

(12) **United States Patent**
McInnis

(10) **Patent No.:** **US 7,411,555 B2**

(45) **Date of Patent:** **Aug. 12, 2008**

(54) **FOLDED MONOPOLE ANTENNA, BENT, TAPPED, OR BOTH, AND SYSTEMS INCORPORATING SAME**

(75) Inventor: **A. J. McInnis**, Santa Rosa, CA (US)

(73) Assignee: **Texas Instruments Incorporated**,
Dallas, TX (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 615 days.

(21) Appl. No.: **10/716,798**

(22) Filed: **Nov. 19, 2003**

(65) **Prior Publication Data**

US 2004/0166908 A1 Aug. 26, 2004

Related U.S. Application Data

(60) Provisional application No. 60/448,755, filed on Feb. 20, 2003.

(51) **Int. Cl.**
H01Q 1/24 (2006.01)

(52) **U.S. Cl.** 343/702; 343/795; 343/828

(58) **Field of Classification Search** 343/702,
343/700 MS, 826, 803, 804, 713, 795, 828,
343/829

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,045,987	A *	6/1936	Green	343/730
4,438,437	A *	3/1984	Burgmyer	343/770
5,151,707	A *	9/1992	Kumpfbeck et al.	343/705
5,289,198	A *	2/1994	Altschuler	343/729
6,008,766	A *	12/1999	Maeda et al.	343/713
6,016,128	A *	1/2000	Imamura et al.	343/741
6,054,955	A *	4/2000	Schlegel et al.	343/702

OTHER PUBLICATIONS

Walsin Technology Corporation, "Multilayer Ceramic Antenna RFANT Series 2.4 GHz ISM Band Working Frequency;" Aug. 2002, 9 pgs.

* cited by examiner


Primary Examiner—Michael C. Wimer

(74) *Attorney, Agent, or Firm*—Steven A. Shaw; W. James Brady; Frederick J. Telecky, Jr.

(57) **ABSTRACT**

Various antenna designs that are small and cost effective are disclosed. In one design, the antenna is a bent and folded monopole antenna. In another design, the antenna is a folded and tapped monopole antenna. In yet another design, the antenna is a folded, bent, and tapped monopole antenna. The antennas may be part of a system using two back-to-back symmetric antennas. The antennas may be part of a modem, such as a wireless computer modem or a wireless handset.

16 Claims, 4 Drawing Sheets





US007411560B2

(12) **United States Patent**
Jordan

(10) **Patent No.:** **US 7,411,560 B2**
(45) **Date of Patent:** **Aug. 12, 2008**

(54) **LOW PROFILE ANTENNAS AND DEVICES**

(75) Inventor: **David Frederick Jordan**, Danville, NH (US)

(73) Assignee: **M/A-Com, Inc.**, Lowell, MA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

3,665,478	A *	5/1972	Dempsey	343/725
4,396,920	A *	8/1983	Grimberg et al.	343/846
6,229,489	B1	5/2001	Holshouser et al.		
6,683,570	B2	1/2004	Skladany et al.		
6,683,580	B2	1/2004	Kuramoto et al.		
6,693,600	B1 *	2/2004	Elliot	343/773
6,812,902	B2	11/2004	Rossmann et al.		
6,930,640	B2 *	8/2005	Chung et al.	343/700 MS
6,956,533	B2	10/2005	Lindenmeier		
2007/0013593	A1 *	1/2007	Zafar et al.	343/713

* cited by examiner

Primary Examiner—Trinh V Dinh

(21) Appl. No.: **11/537,616**

(22) Filed: **Sep. 30, 2006**

(65) **Prior Publication Data**

US 2008/0079643 A1 Apr. 3, 2008

(51) **Int. Cl.**
H01Q 21/00 (2006.01)

(52) **U.S. Cl.** **343/725; 343/702; 343/895; 343/846**

(58) **Field of Classification Search** **343/725**
See application file for complete search history.

(56) **References Cited**


U.S. PATENT DOCUMENTS

2,732,551 A * 1/1956 Kraus 343/843

(57) **ABSTRACT**

An apparatus includes a monopole extending substantially along an axis that may be vertical. However, the monopole may have a loop portion that deviates from the axis. Further, the apparatus includes multiple conductive elements, each having a substantially linear first segment that is coupled to the monopole. The first segments may be coplanar and/or perpendicular to the axis. Each of the conductive elements may further include a second segment that is substantially parallel to the axis. One or more of these segments may be connected to a ground potential. Also, the conductive elements may each include a third segment having a loop pattern.

18 Claims, 5 Drawing Sheets



400



US007411563B2

(12) **United States Patent**
Liu et al.

(10) **Patent No.:** **US 7,411,563 B2**
(45) **Date of Patent:** ***Aug. 12, 2008**

(54) **ANTENNA DEVICE**

(75) Inventors: **Kuo-Cheng Liu**, Xindian (TW);
Chin-Hon Fan, Xindian (TW);
Kun-Ting Lin, Xindian (TW);
Ren-Peng Chen, Xindian (TW)

(73) Assignee: **High Tech Computer, Corp.**, Taoyuan (TW)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **11/826,763**

(22) Filed: **Jul. 18, 2007**

(65) **Prior Publication Data**

US 2007/0262915 A1 Nov. 15, 2007

Related U.S. Application Data

(63) Continuation of application No. 11/099,616, filed on Apr. 6, 2005, now Pat. No. 7,253,787.

(30) **Foreign Application Priority Data**

Nov. 25, 2004 (TW) 93136269 A
Dec. 17, 2004 (CN) 2004 1 0102062 A

(51) **Int. Cl.**
H01Q 1/36 (2006.01)

(52) **U.S. Cl.** **343/895**

(58) **Field of Classification Search** 343/700 MS, 343/725, 829, 846, 853, 895
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,828,348	A	10/1998	Tassoudji et al.
5,986,616	A *	11/1999	Edvardsson 343/853
6,184,844	B1	2/2001	Filipovic et al.
6,184,845	B1	2/2001	Leisten et al.
6,886,237	B2 *	5/2005	Leisten et al. 29/600
7,253,787	B2 *	8/2007	Liu et al. 343/895
2002/0140622	A1	10/2002	Park et al.

FOREIGN PATENT DOCUMENTS

EP	0 791 978	A	8/1997
JP	1-132107	U	9/1989
JP	5-14043	A	1/1993
JP	06 077722	A	3/1994
JP	08 078945	A	3/1996
JP	2001-168631	A	6/2001
WO	WO-98/44590	A	10/1998

* cited by examiner



Primary Examiner—Shih-Chao Chen

(74) *Attorney, Agent, or Firm*—Birch, Stewart, Kolasch & Birch, LLP

(57) **ABSTRACT**

An antenna device has a dielectric body with a convex surface and a concave surface. The antenna device further has a flexible printed circuit board disposed on the convex surface.

16 Claims, 4 Drawing Sheets





US007414583B2

(12) **United States Patent**
Choi et al.

(10) **Patent No.:** **US 7,414,583 B2**
(45) **Date of Patent:** **Aug. 19, 2008**

(54) **PIFA, RFID TAG USING THE SAME AND ANTENNA IMPEDANCE ADJUSTING METHOD THEREOF**

(75) Inventors: **Won-Kyu Choi**, Gyeonggi-do (KR); **Nak-Seon Seong**, Daejeon (KR); **Cheol-Sig Pyo**, Daegu (KR); **Jong-Suk Chae**, Daejeon (KR)

(73) Assignee: **Electronics and Telecommunications Research Institute**, Daejeon (KR)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **11/297,517**

(22) Filed: **Dec. 7, 2005**

(65) **Prior Publication Data**

US 2007/0046543 A1 Mar. 1, 2007

(30) **Foreign Application Priority Data**

Dec. 8, 2004 (KR) 10-2004-0103087
Jun. 9, 2005 (KR) 10-2005-0049266

(51) **Int. Cl.**
H01Q 1/38 (2006.01)
H01Q 1/24 (2006.01)

(52) **U.S. Cl.** **343/700 MS; 343/895; 343/846; 343/702**

(58) **Field of Classification Search** **343/770, 343/767, 846, 848**

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,369,761 B1 * 4/2002 Thiam et al. 343/700 MS
6,388,626 B1 * 5/2002 Gamalielsson et al. 343/702

6,573,869 B2 6/2003 Moore
6,683,576 B2 * 1/2004 Achim 343/702
6,714,162 B1 * 3/2004 Kadambi et al. 343/700 MS
6,741,214 B1 * 5/2004 Kadambi et al. 343/700 MS
6,795,026 B2 * 9/2004 Chiu et al. 343/702
6,819,287 B2 * 11/2004 Sullivan et al. 343/700 MS

(Continued)

FOREIGN PATENT DOCUMENTS

KR 1020020081 490 A 10/2002

OTHER PUBLICATIONS

"Analysis of Radiation Characteristics of Planar Inverted-F Type Antenna On Conductive Body of Hand-Held Transceiver By Spatial Network Method", Electronics Letters, Aug. 3, 1989, vol. 25, No. 16, pp. 1044-1045.


Primary Examiner—Trinh Vo Dinh

(74) Attorney, Agent, or Firm—Blakely, Sokoloff, Taylor & Zafman LLP

(57) **ABSTRACT**

Provided are a Planar Inverted-F Antenna (PIFA), a Radio Frequency Identification (RFID) tag using the PIFA. The present invention miniaturizes the antenna by using a meander line extended from a radiating edge of a radiation antenna and adjusting a resonant frequency of the antenna, and it performs impedance matching by adjusting capacitive reactance of the antenna. Also, it can perform impedance matching by using a stub having a slot formed therein and adjusting inductive reactance and capacitive reactance of the antenna. The present invention miniaturizes the antenna by using a plurality of shorting plates for shorting the radiation patch from a grounding surface and adjusting the resonant frequency of the antenna. The present invention also provides an inexpensive PIFA antenna with an excellent radiation efficiency by forming the radiation patch in the form of metal sheet in the antenna and floating the radiation patch in the air.

27 Claims, 5 Drawing Sheets





US007414585B2

(12) **United States Patent**
Lu et al.

(10) **Patent No.:** **US 7,414,585 B2**
(45) **Date of Patent:** **Aug. 19, 2008**

(54) **ANTENNA ASSEMBLY FOR USE IN A TELECOMMUNICATION DEVICE**

(75) Inventors: **Shih-Wen Lu**, Taipei Hsien (TW);
Hao-Chun Tung, Chinmen Hsien (TW)

(73) Assignee: **Qisda Corporation**, Taoyuan (TW)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 316 days.

(21) Appl. No.: **11/342,047**

(22) Filed: **Jan. 27, 2006**

(65) **Prior Publication Data**

US 2006/0176219 A1 Aug. 10, 2006

(30) **Foreign Application Priority Data**

Feb. 5, 2005 (TW) 94103848 A

(51) **Int. Cl.**
H01Q 1/24 (2006.01)

(52) **U.S. Cl.** **343/702; 343/700 MS**

(58) **Field of Classification Search** **343/702, 343/700 MS, 846**

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,366,243 B1 *	4/2002	Isohata et al.	343/700 MS
6,970,140 B2 *	11/2005	Hibino et al.	343/860
7,098,856 B2 *	8/2006	Okado	343/702
2007/0139281 A1 *	6/2007	Park et al.	343/702

* cited by examiner


Primary Examiner—HoangAnh T Le

(74) *Attorney, Agent, or Firm*—Ladas and Parry LLP

(57) **ABSTRACT**

An antenna assembly is use in a telecommunication device having a first printed circuit board and a second printed circuit board disposed right below and facing the first printed circuit board. The antenna assembly includes: radiating metal strip having a main strip section for disposing on an upper surface of the first printed circuit board, a feeding strip section extending from the main strip section through a first through hole in the first printed circuit board toward the second printed circuit board, and a grounding strip section extending from the main strip section through a second through hole in the first printed circuit board toward the second printed circuit board. After assembly, the feeding and grounding strip sections tend toward an upper surface of the second printed circuit board.

17 Claims, 4 Drawing Sheets





US007417588B2

(12) **United States Patent**
Castany et al.

(10) **Patent No.:** **US 7,417,588 B2**
(45) **Date of Patent:** **Aug. 26, 2008**

(54) **MULTI-BAND MONOPOLE ANTENNAS FOR MOBILE NETWORK COMMUNICATIONS DEVICES**

(75) Inventors: **Jordi Soler Castany**, Mataro (ES); **Carles Puente Baliarda**, Barcelona (ES); **Carmen Borja Borau**, Barcelona (ES)

(73) Assignee: **Fractus, S.A.**, Bracelona (ES)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **10/587,119**

(22) PCT Filed: **Jan. 28, 2005**

(86) PCT No.: **PCT/ES2005/000879**

§ 371 (c)(1),
(2), (4) Date: **Aug. 29, 2006**

(87) PCT Pub. No.: **WO2005/076409**

PCT Pub. Date: **Aug. 18, 2005**

(65) **Prior Publication Data**

US 2007/0152887 A1 Jul. 5, 2007

Related U.S. Application Data

(60) Provisional application No. 60/540,448, filed on Jan. 30, 2004.

(51) **Int. Cl.**
H01Q 1/38 (2006.01)

(52) **U.S. Cl.** **343/700 MS; 343/702; 343/846**

(58) **Field of Classification Search** **343/700 MS, 343/846, 702**

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,157,548 A 6/1979 Kaloi
4,356,492 A 10/1982 Kaloi
5,870,066 A 2/1999 Asakura et al.

(Continued)

FOREIGN PATENT DOCUMENTS

CA 2416437 A1 1/2002

(Continued)

OTHER PUBLICATIONS

Ning Hua Zhu et al, New algorithms of the TSM and Tom methods for calibrating microwave test fixtures, *Microwaves and optical technology letters.*, Jul. 2002, vol. 34, No. 1.


(Continued)

Primary Examiner—Hoang V Nguyen
(74) *Attorney, Agent, or Firm*—Winstead PC

(57) **ABSTRACT**

Multiband monopole antennas are disclosed. The antennas disclosed can include a substrate for mounting conductors, one or more conductors for receiving networking signals mainly in a first frequency band, and one or more conductors for receiving networking signals mainly in a second frequency band. The conductors can have a polygonal shape or the conductors can have a linear, space-filling, or grid dimension shape. The conductors can be connected at a feed point. One or more antenna can be incorporated into a single printed circuit board. When multiple antennas are used with the same printed circuit board, the conducting material of the printed circuit board located between the antenna attachment points can be interrupted to improve the isolation of each antenna.

27 Claims, 7 Drawing Sheets





US007417591B2

(12) **United States Patent**
Iguchi et al.

(10) **Patent No.:** **US 7,417,591 B2**
(45) **Date of Patent:** **Aug. 26, 2008**

(54) **ANTENNA APPARATUS AND PORTABLE WIRELESS DEVICE USING THE SAME**

(75) Inventors: **Akihiko Iguchi**, Osaka (JP); **Yuki Satoh**, Osaka (JP)

(73) Assignee: **Matsushita Electric Industrial Co., Ltd.**, Osaka (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 3 days.

(21) Appl. No.: **11/353,620**

(22) Filed: **Feb. 14, 2006**

(65) **Prior Publication Data**

US 2006/0181468 A1 Aug. 17, 2006

(30) **Foreign Application Priority Data**

Feb. 17, 2005 (JP) 2005-040146
Feb. 17, 2005 (JP) 2005-040147

(51) **Int. Cl.**
H01Q 1/24 (2006.01)
H01Q 1/48 (2006.01)

(52) **U.S. Cl.** **343/702**; 343/702; 343/700 MS;
343/846; 343/829

(58) **Field of Classification Search** 343/700 MS,
343/702, 846, 829
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,172,646 B1 * 1/2001 Kawahata et al. 343/702
6,426,723 B1 * 7/2002 Smith et al. 343/700 MS
6,549,169 B1 * 4/2003 Matsuyoshi et al. 343/702
6,686,886 B2 * 2/2004 Flint et al. 343/702

6,867,736 B2 * 3/2005 Faraone et al. 343/700 MS
6,970,135 B2 * 11/2005 Sato et al. 343/702
7,075,483 B2 * 7/2006 Okado 343/700 MS
7,161,543 B2 * 1/2007 Cheng et al. 343/702
7,199,762 B2 * 4/2007 Liu et al. 343/702
2004/0027298 A1 * 2/2004 Iguchi et al. 343/702
2005/0090284 A1 * 4/2005 Yuanzhu 455/558
2005/0162318 A1 * 7/2005 Higasa 343/700 MS

FOREIGN PATENT DOCUMENTS

JP 2002-237779 8/2002

OTHER PUBLICATIONS

"Antenna Frequency Scaling", The ARRL Antenna Book COpy right 1988, p. 2-24 to 2-25.*

* cited by examiner


Primary Examiner—Trinh V Dinh

(74) *Attorney, Agent, or Firm*—RatnerPrestia

(57) **ABSTRACT**

An antenna apparatus and a portable wireless device using the same are disclosed, in which a coupling between antenna elements is reduced and an isolation property is improved even when frequencies of antenna elements are close or overlapped. The antenna apparatus includes a ground board, a first antenna element corresponding to a first frequency band, a second antenna element corresponding to a second frequency band in the vicinity of, or overlapped with the first frequency band, a first power feeding part connecting the ground board to the first antenna element and a second power feeding part connecting the ground board to the second antenna element, in which the first antenna element is arranged in a direction at an angle of an integer multiple of 90 degrees with respect to a long edge of the ground board, and the second antenna element is arranged in parallel with the long edge of the ground board.

26 Claims, 6 Drawing Sheets





US007417593B1

(12) **United States Patent**
Hsiao et al.

(10) **Patent No.:** **US 7,417,593 B1**
(45) **Date of Patent:** **Aug. 26, 2008**

(54) **WIRELESS APPARATUS FOR INCREASING ANTENNA GAIN**

2006/0202895 A1* 9/2006 Nam et al. 343/702
2007/0176830 A1* 8/2007 Winter 343/702

(75) Inventors: **Lan-Yung Hsiao**, Taipei Hsien (TW);
Kai Shih, Taipei Hsien (TW); **Yu-Yuan Wu**, Taipei Hsien (TW)

* cited by examiner

(73) Assignee: **Cheng Uei Precision Industry Co., Ltd.**, Taipei Hsien (TW)

Primary Examiner—Shih-Chao Chen

(74) *Attorney, Agent, or Firm*—WPAT, P.C.; Anthony King

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(57) **ABSTRACT**

(21) Appl. No.: **11/696,604**

A wireless apparatus has a main housing, a movable housing relatively extended to the main housing. The main housing contains a first PCB with a first layer being fully laid metal material. The movable housing contains a second PCB with a second layer being fully laid metal material. An insulation route is laid on the second layer and led to the border of the second layer. A connection component electronically connects the first layer and the second layer. When the wireless apparatus is operated at wireless communication, the cooperation of the first layer, the second layer, the insulation route and the connection component adjusts the electrical characteristic of the first and second PCBs for eliminating a parasitic effect being caused of movement of the first and second PCBs and increasing gain of the antenna of the wireless apparatus.

(22) Filed: **Apr. 4, 2007**

(51) **Int. Cl.**
H01Q 1/24 (2006.01)
H01Q 13/10 (2006.01)
H01Q 1/48 (2006.01)

(52) **U.S. Cl.** **343/702; 343/767; 343/846**

(58) **Field of Classification Search** **343/700 MS, 343/702, 767, 846**

See application file for complete search history.


(56) **References Cited**

U.S. PATENT DOCUMENTS

6,822,611 B1* 11/2004 Kontogeorgakis et al. ... 343/702

14 Claims, 3 Drawing Sheets

100





US007417599B2

(12) **United States Patent**
Goff et al.

(10) **Patent No.:** **US 7,417,599 B2**
(45) **Date of Patent:** ***Aug. 26, 2008**

(54) **MULTI-LOOP ANTENNA FOR RADIO
FREQUENCY IDENTIFICATION (RFID)
COMMUNICATION**

(75) Inventors: **Edward D. Goff**, Mahtomedi, MN (US);
Seth A. Liefkort, Eagan, MN (US);
Leroy Stolberg, Eagan, MN (US)

(73) Assignee: **3M Innovative Properties Company**,
St. Paul, MN (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 505 days.

This patent is subject to a terminal dis-
claimer.

(21) Appl. No.: **10/784,124**

(22) Filed: **Feb. 20, 2004**

(65) **Prior Publication Data**

US 2004/0183742 A1 Sep. 23, 2004

(51) **Int. Cl.**
H01Q 21/00 (2006.01)

(52) **U.S. Cl.** **343/867; 343/742; 340/572.7**

(58) **Field of Classification Search** **343/741,**
343/742, 866, 867, 895; 340/825.36, 572.7,
340/572.5, 572.1; 235/451, 492

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,243,980 A * 1/1981 Lichtblau 340/572.7
4,260,990 A * 4/1981 Lichtblau 343/742
4,326,198 A * 4/1982 Novikoff 340/572.2
4,782,345 A 11/1988 Landt
5,103,234 A * 4/1992 Watkins et al. 343/742
5,126,749 A * 6/1992 Kaltner 343/742

5,142,292 A 8/1992 Chang
5,337,063 A * 8/1994 Takahira 343/741
5,608,417 A * 3/1997 de Vall 343/895
5,914,692 A * 6/1999 Bowers et al. 343/742
5,926,093 A 7/1999 Bowers et al.
5,940,043 A 8/1999 Canipe et al.
5,963,173 A * 10/1999 Lian et al. 343/742
5,977,875 A 11/1999 Lin et al.
6,037,879 A 3/2000 Tuttle
6,043,792 A 3/2000 Finlayson

(Continued)

FOREIGN PATENT DOCUMENTS

EP 0 766 200 4/1997

(Continued)

OTHER PUBLICATIONS

Carr, Joseph J., "Practical Antenna Handbook," 3rd Edition, pp. 291-
297 and 307-309, 1998.

(Continued)

Primary Examiner—Tan Ho

(74) *Attorney, Agent, or Firm*—John A. Burtis

(57) **ABSTRACT**

A multi-loop antenna is described having a plurality of con-
ductive loops to produce an electromagnetic field for radio
frequency identification (RFID) communication with RFID
tags. The conductive loops are spaced apart at least a distance
that is selected based on a dimension of the RFID tags with
which the antenna communicates. In this manner, the loops
are positioned and spaced in a manner that reduces the size of
the holes within the resulting magnetic field. In addition, the
configuration of the described dual-loop antenna increases
the coverage of the antenna, and decreases inter-winding
capacitance, thereby increasing overall read range achieved
by the antenna.

29 Claims, 8 Drawing Sheets

