



US007791541B2

(12) **United States Patent**
Chang et al.

(10) **Patent No.:** **US 7,791,541 B2**
(45) **Date of Patent:** **Sep. 7, 2010**

(54) **PRINTED CIRCUIT BOARD**
(75) Inventors: **Ki Won Chang**, Gyunggi-do (KR);
Jeong Sik Seo, Gyunggi-do (KR); **Hyun Do Park**, Gyunggi-do (KR); **Jae Suk Sung**, Gyunggi-do (KR)

(73) Assignee: **Samsung Electro-Mechanics Co., Ltd.**, Suwon, Gyunggi-do (KR)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 205 days.

(21) Appl. No.: **11/944,571**

(22) Filed: **Nov. 23, 2007**

(65) **Prior Publication Data**
US 2008/0122713 A1 May 29, 2008

(30) **Foreign Application Priority Data**
Nov. 22, 2006 (KR) 10-2006-0115951

(51) **Int. Cl.**
H01Q 1/38 (2006.01)

(52) **U.S. Cl.** **343/700 MS; 343/702**

(58) **Field of Classification Search** **343/700 MS, 343/702**
See application file for complete search history.

(56) **References Cited**
U.S. PATENT DOCUMENTS

5,861,854 A	1/1999	Kawahata et al.	
6,762,731 B1 *	7/2004	Chou	343/882
7,034,752 B2	4/2006	Sekiguchi et al.	
7,265,724 B1	9/2007	Tan et al.	
2003/0132885 A1 *	7/2003	Kuramoto et al.	343/702

2003/0222827 A1	12/2003	Sung	
2004/0246180 A1 *	12/2004	Okado	343/700 MS
2009/0040109 A1	2/2009	Iguchi et al.	

FOREIGN PATENT DOCUMENTS

EP	1 146 589 A1	10/2001
EP	1 267 441 A3	12/2002
EP	1 482 592 A1	1/2004
EP	1 564 837 A2	8/2005
EP	1860732 A1	11/2007
JP	2001-36317 A	2/2001
JP	2006295876 A	10/2006
WO	2005-078860 A1	8/2005
WO	2006-000631 A1	1/2006
WO	2006098089 A1	9/2006

OTHER PUBLICATIONS

UK Intellectual Property Office English Language Search Report, mailed Mar. 17, 2008.
UKIPO Search Report issued Sep. 9, 2008.
Korean Intellectual Property Office Search Report issued Sep. 9, 2008.
German Office Action for Application No. 10 2007 056.8-55, issued Jun. 10, 2010.



* cited by examiner

Primary Examiner—Douglas W Owens
Assistant Examiner—Dieu Hien T Duong
(74) *Attorney, Agent, or Firm*—Lowe Hauptman Ham & Berner LLP

(57) **ABSTRACT**

There is provided a printed circuit board comprising: a mounting area of a chip antenna provided on one surface thereof, and a tuning ground pattern formed on a surface opposing the one surface of the printed circuit board to have one end connected to a ground part so as to be used for tuning frequency characteristics of the chip antenna.

6 Claims, 5 Drawing Sheets





US007791543B2

(12) **United States Patent**
Choi et al.

(10) **Patent No.:** **US 7,791,543 B2**
(45) **Date of Patent:** ***Sep. 7, 2010**

(54) **ANTENNA FOR RADIO FREQUENCY IDENTIFICATION TAG**

(75) Inventors: **Won Kyu Choi**, Daejeon (KR); **Jeong Seok Kim**, Daejeon (KR); **Gil Young Choi**, Daejeon (KR); **Cheol Sig Pyo**, Daejeon (KR); **Jong-suk Chae**, Daejeon (KR)

(73) Assignee: **Electronics and Telecommunications Research Institute**, Daejeon (KR)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 187 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **12/126,020**

(22) Filed: **May 23, 2008**

(65) **Prior Publication Data**

US 2009/0096678 A1 Apr. 16, 2009

(30) **Foreign Application Priority Data**

Oct. 10, 2007 (KR) 10-2007-0102274

(51) **Int. Cl.**
H01Q 1/38 (2006.01)

(52) **U.S. Cl.** **343/700 MS**; 343/702; 343/895

(58) **Field of Classification Search** 343/700 MS, 343/850, 860; 340/572.7

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,028,564	A	2/2000	Duan et al.
6,215,402	B1	4/2001	Rao Kodukula et al.
6,285,342	B1	9/2001	Brady et al.
6,535,175	B2	3/2003	Brady et al.
7,486,192	B2	2/2009	Yamagajo et al.
7,557,757	B2 *	7/2009	Deavours et al. 343/700 MS
2006/0208955	A1	9/2006	Kai et al.
2009/0140947	A1 *	6/2009	Sasagawa et al. 343/845

FOREIGN PATENT DOCUMENTS

JP	2006-295879	10/2006
JP	2007-228437	9/2007
KR	10-2007-0088228	A 8/2007

OTHER PUBLICATIONS

Byunggil Yu et al., "RFID Antenna Using Two-Shorted Microstrip Patches Mountable on Metallic Objects", *Microwave and Optical Technology Letters*, vol. 49, No. 2, Feb. 2007, pp. 414-416.

* cited by examiner


Primary Examiner—Hoang V Nguyen

(74) *Attorney, Agent, or Firm*—Jae Y. Park; Kile Goekjian Reed & McManus

(57) **ABSTRACT**

An antenna for an RFID tag having an RFID tag chip includes a dielectric material, a radiating patch radiating a signal from the RFID tag chip, and a feed line supplying power to the RFID tag chip through magnetic-coupling with the radiating patch. Accordingly, a small antenna that can be attached to metal can be realized.

8 Claims, 7 Drawing Sheets





US007791545B2

(12) **United States Patent**
Lin et al.

(10) **Patent No.:** **US 7,791,545 B2**
(45) **Date of Patent:** **Sep. 7, 2010**

(54) **MULTIBAND ANTENNA**

(75) Inventors: **Sheng-Chih Lin**, Hsin-Tien (TW);
Tsung-Wen Chiu, Hsin-Tien (TW);
Fu-Ren Hsiao, Hsin-Tien (TW)

(73) Assignee: **Advanced Connectek, Inc.**, Taipei (TW)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **11/943,799**

(22) Filed: **Nov. 21, 2007**

(65) **Prior Publication Data**
US 2008/0122702 A1 May 29, 2008

(30) **Foreign Application Priority Data**
Nov. 24, 2006 (TW) 95143543 A

(51) **Int. Cl.**
H01Q 1/24 (2006.01)

(52) **U.S. Cl.** **343/702; 343/700 MS; 343/846**

(58) **Field of Classification Search** **343/700 MS, 343/702, 846, 906**
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS
5,764,190 A 6/1998 Murch et al.

6,992,627	B1 *	1/2006	Honda et al.	343/700	MS
7,050,010	B2 *	5/2006	Wang et al.	343/702	
7,212,161	B2 *	5/2007	Chen et al.	343/700	MS
7,236,132	B1	6/2007	Lin et al.			
7,535,422	B2 *	5/2009	Liu et al.	343/702	
2004/0113848	A1 *	6/2004	Gaucher et al.	343/702	


* cited by examiner

Primary Examiner—James H. Cho
Assistant Examiner—Christopher Lo
(74) *Attorney, Agent, or Firm*—Schmeiser, Olsen & Watts LLP

(57) **ABSTRACT**

A multiband antenna with the broadband function has a radiator, a feed cable, a first extension conductor, and a second extension conductor. The radiator has a microwave substrate, a coupling conductor, a first conductor, a second conductor, a third conductor, and a connecting conductor. The coupling conductor is connected with a positive signal wire of the feed cable. The third conductor is connected with a negative signal wire of the feed cable for transmitting electrical signals. The radiator generates the multiband mode of the antenna. By connecting the first extension conductor and the second extension conductor with the radiator, the surface current distribution and impedance variation of the antenna can be effectively adjusted to achieve the broadband effect.

3 Claims, 5 Drawing Sheets





US007791546B2

(12) **United States Patent**
Hotta et al.

(10) **Patent No.:** **US 7,791,546 B2**
(45) **Date of Patent:** **Sep. 7, 2010**

(54) **ANTENNA DEVICE AND ELECTRONIC APPARATUS**

7,423,598 B2 *	9/2008	Bit-Babik et al.	343/702
7,605,764 B2 *	10/2009	Ishimiya	343/702
2004/0137950 A1	7/2004	Bolin	
2007/0115118 A1	5/2007	Hsu et al.	
2007/0115188 A1	5/2007	Mizoguchi et al.	

(75) Inventors: **Hiroyuki Hotta**, Hamura (JP); **Koichi Sato**, Tachikawa (JP); **Hiroshi Shimasaki**, Kunitachi (JP)

FOREIGN PATENT DOCUMENTS

(73) Assignee: **Kabushiki Kaisha Toshiba**, Tokyo (JP)
(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 61 days.

EP	1 555 715	7/2005
EP	1 679 762	7/2006
JP	8-046419	2/1996
JP	2004-172912	6/2004
JP	2004-173143	6/2004
JP	2004-260586	9/2004

(21) Appl. No.: **12/188,923**

(Continued)

(22) Filed: **Aug. 8, 2008**

OTHER PUBLICATIONS

(65) **Prior Publication Data**

US 2009/0079639 A1 Mar. 26, 2009

European Search Report dated Feb. 10, 2009 for application No. 08161655.9 (U.S. Appl. No. 12/188,923), entitled Antenna Device and Electronic Apparatus.

(30) **Foreign Application Priority Data**

(Continued)

Sep. 21, 2007 (JP) 2007-245205

Primary Examiner—Tan Ho
(74) *Attorney, Agent, or Firm*—Blakely, Sokoloff, Taylor & Zafman LLP

(51) **Int. Cl.**
H01Q 1/24 (2006.01)

(52) **U.S. Cl.** **343/702**; 343/700 MS

(58) **Field of Classification Search** 343/700 MS, 343/702, 895
See application file for complete search history.

(57) **ABSTRACT**


According to one embodiment, an antenna device includes a folded element and an end-free element wound around a core member. A feed portion for a folded element and an end-free element is located close to one end of the core member, and a ground portion for a folded element is located closer to the one end than the feed portion. A coaxial cable connected to the feed portion is led away the antenna device, and an external conductor of the coaxial cable is connected near the ground portion.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,821,902 A	10/1998	Keen	
5,929,825 A *	7/1999	Niu et al.	343/895
6,307,520 B1	10/2001	Liu	
6,819,287 B2 *	11/2004	Sullivan et al.	343/700 MS
6,961,028 B2	11/2005	Joy et al.	
7,345,637 B2	3/2008	Mizoguchi et al.	

20 Claims, 17 Drawing Sheets





US007791547B2

(12) **United States Patent**
Qi et al.

(10) **Patent No.:** **US 7,791,547 B2**
(45) **Date of Patent:** ***Sep. 7, 2010**

(54) **MOBILE WIRELESS COMMUNICATIONS DEVICE INCLUDING A GROUND PATCH PROVIDING SPECIFIC ABSORPTION RATE (SAR) REDUCTION AND RELATED METHODS**

(75) Inventors: **Yihong Qi**, St. Agatha (CA); **Ying Tong Man**, Waterloo (CA); **Perry Jarmuszewski**, Waterloo (CA)

(73) Assignee: **Research In Motion Limited**, Waterloo, Ontario (CA)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **12/472,638**

(22) Filed: **May 27, 2009**

(65) **Prior Publication Data**

US 2009/0231216 A1 Sep. 17, 2009

Related U.S. Application Data

(63) Continuation of application No. 11/733,360, filed on Apr. 10, 2007, now Pat. No. 7,554,496.

(51) **Int. Cl.**
H01Q 1/24 (2006.01)

(52) **U.S. Cl.** **343/702**; 343/846

(58) **Field of Classification Search** 343/702,
343/846, 700 MS

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,765,536 B2	7/2004	Phillips et al.	343/702
6,819,287 B2	11/2004	Sullivan et al.	343/700 MS
6,864,842 B2	3/2005	Hung et al.	343/700 MS
7,397,432 B2	7/2008	Ku et al.	343/702

FOREIGN PATENT DOCUMENTS

CA	2571338	3/2007
EP	0603082	6/1994
EP	1331691	7/2003
GB	2351848	1/2001
GB	2390957	1/2004
WO	2005004277	1/2005


Primary Examiner—Hoang V Nguyen

(74) *Attorney, Agent, or Firm*—Allen, Dyer, Doppelt, Milbrath & Gilchrist, P.A.

(57) **ABSTRACT**

A mobile wireless communications device may include a portable housing, a dielectric substrate carried by the portable housing having a front side facing toward a user and a back side opposite the front side, and a ground plane carried by the dielectric substrate. The device may further include at least one circuit carried by the dielectric substrate, and an antenna carried by the dielectric substrate adjacent an end thereof and electrically connected to the at least one circuit. A ground patch may be adjacent the front side of the dielectric substrate that is electrically connected to the ground plane and spaced apart from and at least partially overlapping the antenna.

29 Claims, 3 Drawing Sheets





US007796085B2

(12) **United States Patent**
Fujii

(10) **Patent No.:** **US 7,796,085 B2**
(45) **Date of Patent:** **Sep. 14, 2010**

- (54) **ANTENNA AND WIRING BOARD**
- (75) Inventor: **Tomoharu Fujii**, Nagano (JP)
- (73) Assignee: **Shinko Electric Industries Co., Ltd.**,
Nagano-shi, Nagano (JP)
- (*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 525 days.

7,026,999	B2 *	4/2006	Umehara et al.	343/702
7,046,197	B2 *	5/2006	Okado	343/700 MS
7,053,837	B2 *	5/2006	Il et al.	343/700 MS
7,218,282	B2 *	5/2007	Humpfer et al.	343/700 MS
7,339,535	B2 *	3/2008	Liang et al.	343/702
2002/0000939	A1 *	1/2002	Kaiponen	343/700 MS
2005/0062651	A1 *	3/2005	Dai et al.	343/700 MS

- (21) Appl. No.: **11/586,624**
- (22) Filed: **Oct. 26, 2006**

FOREIGN PATENT DOCUMENTS

JP	05-211406	8/1993
JP	08-330830	12/1996
JP	2003-124742	4/2003
JP	2005-110109	4/2005
JP	2005-110110	4/2005
JP	2005-142739	6/2005

- (65) **Prior Publication Data**
US 2007/0096992 A1 May 3, 2007

* cited by examiner

Primary Examiner—Douglas W Owens
Assistant Examiner—Chuc D Tran

- (30) **Foreign Application Priority Data**
Oct. 28, 2005 (JP) P.2005-314506

(74) *Attorney, Agent, or Firm*—Drinker Biddle & Reath LLP


- (51) **Int. Cl.**
H01Q 1/38 (2006.01)
- (52) **U.S. Cl.** **343/700 MS**; 343/702;
343/725; 343/846; 343/893
- (58) **Field of Classification Search** 343/700 MS,
343/702, 725, 728, 846, 848, 830, 893
See application file for complete search history.

(57) **ABSTRACT**

An antenna **1** which is incorporated in a multilayer wiring board **2** has: radiating elements **11-1**, **11-2**, **11-3**, and **11-4** which are laid on faces of A-, B-, and C-layers of the wiring board **2**, respectively; power supplying portions **12-1**, **12-2**, **12-3**, and **12-4** which are laid on the faces of the layers, respectively to supply an electric power to the radiating elements **11-1**, **11-2**, **11-3**, and **11-4**; short-circuiting portions **13-1**, **13-2**, **13-3**, and **13-4** which are laid on the faces of the layers, respectively to ground the radiating elements **11-1**, **11-2**, **11-3**, and **11-4**; and a connecting portion **14** which penetrates the A-, B-, and C-layers of the wiring board **2**, and through which the power supplying portions **12-1**, **12-2**, **12-3**, and **12-4** are electrically connected to each other.

- (56) **References Cited**
U.S. PATENT DOCUMENTS
5,307,075 A * 4/1994 Huynh 343/700 MS
5,929,825 A * 7/1999 Niu et al. 343/895
6,674,405 B2 * 1/2004 Wang 343/700 MS
6,982,675 B2 * 1/2006 Kwak et al. 343/702

5 Claims, 7 Drawing Sheets





US007796086B2

(12) **United States Patent**
Coskun et al.

(10) **Patent No.:** **US 7,796,086 B2**
(45) **Date of Patent:** **Sep. 14, 2010**

(54) **ANTENNA AND METHOD OF
MANUFACTURING AN ANTENNA**

7,183,981	B1	2/2007	Chao	
7,450,072	B2*	11/2008	Kim et al. 343/700 MS
2002/0036897	A1	3/2002	Nakajima	
2003/0151555	A1	8/2003	Holshouser	
2007/0139270	A1	6/2007	Takei	

(75) Inventors: **Orhan Coskun**, Izmir (TR); **Ayşe Sevinc Aydinlik Bechteler**, Izmir (TR)

(73) Assignee: **Vestel Elektronik Sanayi ve Ticaret A.S.**, Manisa (TR)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 202 days.

FOREIGN PATENT DOCUMENTS

EP	1039576	9/2000
WO	WO2005/048404	5/2005

(21) Appl. No.: **12/118,427**

OTHER PUBLICATIONS

(22) Filed: **May 9, 2008**

European Search Report dated Jan. 24, 2008 for Application No. EP 07252019 (4 pages).

(65) **Prior Publication Data**

US 2009/0015484 A1 Jan. 15, 2009

* cited by examiner

Related U.S. Application Data

Primary Examiner—Hoang V Nguyen
(74) *Attorney, Agent, or Firm*—Conley Rose, P.C.

(60) Provisional application No. 60/938,607, filed on May 17, 2007.

(57) **ABSTRACT**

(51) **Int. Cl.**
H01Q 1/38 (2006.01)
H01Q 1/48 (2006.01)

(52) **U.S. Cl.** **343/700 MS**; 343/846

(58) **Field of Classification Search** 343/700 MS,
343/702, 846

See application file for complete search history.


An antenna (10) comprises a substrate (11) having a first and a second opposed side (12, 13); a single element for radiating electromagnetic waves (15), wherein the radiating element (15) is formed on the first substrate side (12); a first ground plane (18) formed on the first substrate side (12), the first ground plane (18) being electrically connected to the radiating element (15); and, a second ground plane (19) formed on the second substrate side (13), the second ground plane (19) being electrically connected to the first ground plane (18).

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,664,926 B1 12/2003 Zinanti

19 Claims, 11 Drawing Sheets





US007796087B2

(12) **United States Patent**
Yanagi et al.

(10) **Patent No.:** **US 7,796,087 B2**
(45) **Date of Patent:** **Sep. 14, 2010**

(54) **ANTENNA APPARATUS HAVING A GROUND PLATE AND FEEDING UNIT**

(75) Inventors: **Masahiro Yanagi**, Shinagawa (JP);
Shigemi Kurashima, Shinagawa (JP);
Hiroto Inoue, Shinagawa (JP); **Takuya Uchiyama**, Shinagawa (JP)

(73) Assignee: **Fujitsu Component Limited**, Tokyo (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **11/783,216**

(22) Filed: **Apr. 6, 2007**

(65) **Prior Publication Data**
US 2007/0182642 A1 Aug. 9, 2007

Related U.S. Application Data
(63) Continuation of application No. 11/119,732, filed on May 3, 2005, now Pat. No. 7,289,070.

(30) **Foreign Application Priority Data**
Sep. 17, 2004 (JP) 2004-271580

(51) **Int. Cl.**
H01Q 1/24 (2006.01)
(52) **U.S. Cl.** **343/702**; 343/700 MS
(58) **Field of Classification Search** 343/700 MS, 343/846, 848, 702
See application file for complete search history.

(56) **References Cited**
U.S. PATENT DOCUMENTS
5,872,546 A 2/1999 Ihara et al. 343/795

6,232,923	B1 *	5/2001	Guinn et al.	343/700	MS
6,259,418	B1	7/2001	Jones et al.	343/846	
6,419,506	B2	7/2002	Jones et al.	439/131	
6,642,892	B2 *	11/2003	Masaki et al.	343/702	
6,774,853	B2 *	8/2004	Wong et al.	343/700	MS
6,879,849	B2 *	4/2005	Begic	455/575.7	
6,906,677	B2 *	6/2005	Yamamoto et al.	343/789	
6,937,192	B2 *	8/2005	Mendolia et al.	343/700	MS
6,943,734	B2 *	9/2005	Zinanti et al.	343/700	MS
6,992,627	B1 *	1/2006	Honda et al.	343/700	MS
6,995,722	B2	2/2006	Komatsu et al.	343/711	
7,057,563	B2 *	6/2006	Cox et al.	343/700	MS

(Continued)

FOREIGN PATENT DOCUMENTS

JP 9-223921 8/1997

(Continued)

OTHER PUBLICATIONS

Takuya Taniguchi, et al., "An Omnidirectional and Low-VSWR Antenna for the FCC-Approved UWB Frequency Band", The Institute of Electronics, Information and Communication Engineers, B-1-133, p. 133, 2003.



(Continued)

Primary Examiner—Hoang Anh T Le
(74) *Attorney, Agent, or Firm*—Staas & Halsey LLP

(57) **ABSTRACT**

An antenna apparatus is disclosed. The antenna apparatus is structured by a ground plate that is shaped like a plate, and a feeding unit that is formed by a plate-like member, the feeding unit extending from the ground plate generally perpendicular to the ground plate at a predetermined angle to the ground plate for a predetermined length.

3 Claims, 13 Drawing Sheets





US007796088B1

(12) **United States Patent**
Chen et al.

(10) **Patent No.:** **US 7,796,088 B1**
(45) **Date of Patent:** **Sep. 14, 2010**

(54) **STRETCHABLE ANTENNA ASSEMBLY AND NOTEBOOK COMPUTER WITH THE ANTENNA ASSEMBLY THEREOF**

(75) Inventors: **Hen-An Chen**, Taipei Hsien (TW);
San-Yi Kuo, Taipei Hsien (TW);
Bing-Chun Chung, Taipei Hsien (TW)

(73) Assignee: **Wistron Neweb Corporation**, Hsichih, Taipei Hsien (TW)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **12/007,146**

(22) Filed: **Jan. 7, 2008**

(30) **Foreign Application Priority Data**

Aug. 20, 2007 (TW) 96130746 A

(51) **Int. Cl.**
H01Q 1/24 (2006.01)

(52) **U.S. Cl.** **343/702**

(58) **Field of Classification Search** 343/702,
343/872, 878, 880, 883; 455/575.1, 575.3,
455/575.4

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,943,018 A * 8/1999 Miller 343/702
6,259,409 B1 * 7/2001 Fulton et al. 343/702

FOREIGN PATENT DOCUMENTS

DE 102006015790 A1 7/2007


* cited by examiner

Primary Examiner—Hoang V Nguyen

(57) **ABSTRACT**

A stretchable antenna assembly and a notebook computer with the antenna assembly thereof, comprising an antenna module and a holder which respectively has a guiding unit corresponding to the antenna module and the holder, and further the antenna module couples to a signal transmission element for activating with a first conductive element disposed at one side of the holder, resulting in preventing the antenna signal transmission from being interrupted whenever the antenna module is open or closed, and in further ensuring the precise locating function, and strengthening the receipt of signal.

25 Claims, 5 Drawing Sheets





US007796090B2

(12) **United States Patent**
Minard et al.

(10) **Patent No.:** **US 7,796,090 B2**
(45) **Date of Patent:** **Sep. 14, 2010**

- (54) **COMPACT MULTIBAND ANTENNA**
- (75) Inventors: **Philippe Minard**, Saint Medard sur Ille (FR); **Jean-François Pintos**, Bourgbarre (FR); **Ali Louzir**, Rennes (FR); **Philippe Gilberton**, Geveze (FR)
- (73) Assignee: **Thomson Licensing**, Boulogne-Billancourt (FR)
- (*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 387 days.

- (21) Appl. No.: **11/991,521**
- (22) PCT Filed: **Aug. 31, 2006**
- (86) PCT No.: **PCT/FR2006/050828**
§ 371 (c)(1),
(2), (4) Date: **Mar. 5, 2008**
- (87) PCT Pub. No.: **WO2007/028918**
PCT Pub. Date: **Mar. 15, 2007**

- (65) **Prior Publication Data**
US 2009/0135075 A1 May 28, 2009

- (30) **Foreign Application Priority Data**
Sep. 7, 2005 (FR) 05 52697
Oct. 3, 2005 (FR) 05 52987

- (51) **Int. Cl.**
H01Q 21/00 (2006.01)
H01Q 1/24 (2006.01)

- (52) **U.S. Cl.** **343/727; 343/702; 343/725**
- (58) **Field of Classification Search** **343/727, 343/725, 702, 726, 846, 767, 795**
See application file for complete search history.



- (56) **References Cited**
U.S. PATENT DOCUMENTS
5,608,413 A 3/1997 Macdonald
6,466,176 B1 * 10/2002 Maoz et al. 343/767
6,870,513 B2 3/2005 Deng et al.
6,940,460 B2 * 9/2005 Maoz et al. 343/702
7,362,283 B2 * 4/2008 Quintero Illera et al. 343/846
2003/0112200 A1 * 6/2003 Marino 343/824

- FOREIGN PATENT DOCUMENTS
WO WO 02/05384 1/2002

- OTHER PUBLICATIONS
Search Report Dated Feb. 7, 2007.
* cited by examiner
Primary Examiner—HoangAnh T Le
(74) *Attorney, Agent, or Firm*—Robert D. Shedd; Jeffrey M. Navon

- (57) **ABSTRACT**
The present invention relates to a compact multiband antenna constituted by a first dipole type element comprising a first conductive arm connected to a second conductive arm having the shape of a box, mounted on a ground plane, the first and the second arms being supplied differentially and a second element of the slot type realized on said ground plane in the extension of said second arm.

8 Claims, 4 Drawing Sheets





US007796092B2

(12) **United States Patent**
Holly et al.

(10) **Patent No.:** **US 7,796,092 B2**
(45) **Date of Patent:** **Sep. 14, 2010**

(54) **BROADBAND COMPOSITE DIPOLE ANTENNA ARRAYS FOR OPTICAL WAVE MIXING**

2005/0088358 A1 4/2005 Larry et al.

(75) Inventors: **Sandor Holly**, Woodland Hills, CA (US); **William Daniel Mack**, Encino, CA (US)

(Continued)

FOREIGN PATENT DOCUMENTS

(73) Assignee: **The Boeing Company**, Chicago, IL (US)

EP 01101006 4/1989

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 313 days.

(Continued)

OTHER PUBLICATIONS

(21) Appl. No.: **11/753,490**

PCT search report of Jul. 21, 2008.

(22) Filed: **May 24, 2007**

(Continued)

(65) **Prior Publication Data**
US 2008/0291108 A1 Nov. 27, 2008

Primary Examiner—Huedung Mancuso
(74) *Attorney, Agent, or Firm*—Haynes and Boone, LLP

(51) **Int. Cl.**
H01Q 9/16 (2006.01)

(57) **ABSTRACT**

(52) **U.S. Cl.** **343/820**
(58) **Field of Classification Search** **343/820,**
343/852, 793

A broadband composite dipole array (CDA) includes an array of macro dipoles on a non-conducting substrate adapted to receive radiation at two frequencies. Each macro dipole is an array of micro dipoles adapted to receive radiation at substantially the mean of the two frequencies. The micro-dipoles are coupled to each other by a parallel resonant circuit including a nonlinear element, wherein the minimum impedance of the circuit is a substantially short circuit at the difference frequency $f_1 - f_2$, and the circuit has a substantially open circuit impedance in the range of frequencies from f_1 to f_2 . The micro dipoles resonate efficiently at both frequencies f_1 and f_2 with low-loss. The nonlinear element in the resonant circuit generates a signal at the difference frequency which is the resonant frequency of the macro dipole antenna. A composite of macro dipole antennas couple electromagnetically via a cluster of micro-dipole elements to broaden the bandwidth over a range of frequencies from f_1 to f_2 at which the macro dipole antenna resonates.


See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,852,755 A	12/1974	Works et al.	
3,919,638 A	11/1975	Belden, Jr.	
4,634,968 A	1/1987	Aslan	
4,638,813 A	1/1987	Turner	
5,030,962 A	7/1991	Rees	
5,420,595 A *	5/1995	Zhang et al.	342/368
6,492,957 B2	12/2002	Carillo, Jr. et al.	
6,762,726 B2 *	7/2004	Alden et al.	343/703
7,142,147 B2 *	11/2006	Holly	342/13
7,205,891 B1 *	4/2007	McGlothlin et al.	340/539.26
7,486,250 B2 *	2/2009	Vetrovec et al.	343/820
2002/0075189 A1	6/2002	Carillo, Jr. et al.	
2004/0008149 A1	1/2004	Killen et al.	

15 Claims, 7 Drawing Sheets





US00D623632S

(12) **United States Design Patent**
Montgomery et al.

(10) **Patent No.:** **US D623,632 S**

(45) **Date of Patent:** **** Sep. 14, 2010**

(54) **ANTENNA STRUCTURE**

(75) Inventors: **Mark T. Montgomery**, Melbourne
Beach, FL (US); **Paul A. Tornatta, Jr.**,
Melbourne, FL (US)

(73) Assignee: **SkyCross, Inc.**, Viera, FL (US)

(**) Term: **14 Years**

(21) Appl. No.: **29/350,010**

(22) Filed: **Nov. 10, 2009**

(51) **LOC (9) Cl.** **14-03**

(52) **U.S. Cl.** **D14/230**

(58) **Field of Classification Search** D14/138,
D14/230-238, 299, 358; D12/42, 43; 343/700 MS,
343/700 R-705, 711-713, 741, 748, 767,
343/795, 819, 840, 846, 866, 871-908; 455/90.2,
455/90.3, 91, 128, 269, 344, 347, 562.1;
333/193, 195
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,667,718	B2 *	12/2003	Back et al.	343/700 MS
D535,647	S *	1/2007	Hall et al.	D14/230
D555,154	S *	11/2007	Lin et al.	D14/230
D580,417	S *	11/2008	Miyoshi	D14/230
D583,364	S *	12/2008	Ito et al.	D14/230
D585,054	S *	1/2009	Hsiao et al.	D14/230
D587,693	S *	3/2009	Ohshima	D14/230

D591,734	S *	5/2009	Karakama	D14/230
D603,385	S *	11/2009	Kuramoto	D14/230
D604,278	S *	11/2009	Chen et al.	D14/230
2005/0190109	A1 *	9/2005	Washiro	343/702
2006/0001579	A1 *	1/2006	Noro et al.	343/702
2008/0001823	A1 *	1/2008	Jung et al.	343/700 MS
2008/0007478	A1 *	1/2008	Jung et al.	343/895
2008/0198089	A1 *	8/2008	Hsiao et al.	343/850

* cited by examiner

Primary Examiner—T. Chase Nelson

Assistant Examiner—John Windmuller

(74) *Attorney, Agent, or Firm*—Rajesh Vallabh; Foley Hoag LLP

(57) **CLAIM**

The ornamental design for an antenna structure, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of an antenna structure showing our new design;

FIG. 2 is a top plan view thereof;

FIG. 3 is a left side elevation view thereof;


FIG. 4 is a front elevation view thereof;

FIG. 5 is a right side elevation view thereof;

FIG. 6 is a rear elevation view thereof; and,

FIG. 7 is a bottom plan view thereof.

1 Claim, 2 Drawing Sheets





US007800546B2

(12) **United States Patent**
Rao et al.

(10) **Patent No.:** **US 7,800,546 B2**
(45) **Date of Patent:** **Sep. 21, 2010**

(54) **MOBILE WIRELESS COMMUNICATIONS DEVICE INCLUDING MULTI-LOOP FOLDED MONOPOLE ANTENNA AND RELATED METHODS**

(75) Inventors: **Qinjiang Rao**, Waterloo (CA); **Geyi Wen**, Waterloo (CA)

(73) Assignee: **Research In Motion Limited**, Ontario (CA)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 208 days.

(21) Appl. No.: **11/850,751**

(22) Filed: **Sep. 6, 2007**

(65) **Prior Publication Data**
US 2009/0066586 A1 Mar. 12, 2009

(51) **Int. Cl.**
H01Q 1/22 (2006.01)

(52) **U.S. Cl.** **343/702**; 343/700 MS; 343/797; 343/853; 343/860; 343/895

(58) **Field of Classification Search** 343/702, 343/742, 767, 770, 867, 870, 895, 700 MS, 343/797, 853, 860

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,412,392	A *	5/1995	Tsunekawa	343/702
5,600,341	A *	2/1997	Thill et al.	343/895
5,923,305	A *	7/1999	Sadler et al.	343/895
6,054,955	A	4/2000	Schlegel, Jr. et al.	343/702
6,373,448	B1 *	4/2002	Chun	343/895
6,448,934	B1 *	9/2002	Lee et al.	343/702
6,683,571	B2 *	1/2004	Ghosh et al.	343/700 MS
6,806,832	B2 *	10/2004	Sato et al.	343/700 MS

6,967,631	B1 *	11/2005	Park et al.	343/895
6,987,494	B2 *	1/2006	Keren	343/895
7,504,997	B2 *	3/2009	Baliarda et al.	343/700 MS
2003/0058173	A1	3/2003	Yoon	343/702
2003/0058176	A1	3/2003	Keilen et al.	343/702
2004/0130495	A1	7/2004	Hilgers	343/702
2007/0236394	A1 *	10/2007	Aoyama et al.	343/700 MS

(Continued)

FOREIGN PATENT DOCUMENTS

EP	1 152 482	A2	7/2001
EP	1 414 108	A2	4/2004

OTHER PUBLICATIONS

Liu et al., Dual-Frequency Planar Inverted-F Antenna, IEEE Transactions on Antennas and Propagation, vol. 45, No. 9, pp. 1451-1457, Oct. 1997.


(Continued)

Primary Examiner—Douglas W Owens
Assistant Examiner—Chuc D Tran

(57) **ABSTRACT**

A mobile wireless communications device may include a portable housing, a printed circuit board (PCB) carried within the portable housing, and wireless communications circuitry carried by the PCB within the portable housing. Furthermore, a folded monopole antenna may be coupled to the wireless communications circuitry. The folded monopole antenna may include a dielectric body having a generally rectangular shape defining a bottom portion adjacent the PCB and a top portion opposite the bottom portion. The antenna may also include a conductive trace having a bottom loop adjacent the bottom portion of the dielectric body, a top loop adjacent the top portion of the dielectric body, and an intermediate wrap-around section extending around the dielectric body and between the bottom and top loops.

21 Claims, 6 Drawing Sheets





US007800547B2

(12) **United States Patent**
Li et al.

(10) **Patent No.:** **US 7,800,547 B2**
(45) **Date of Patent:** ***Sep. 21, 2010**

- (54) **DUAL BAND WLAN ANTENNA**
- (75) Inventors: **James Li**, Santa Clara, CA (US); **Jing Jiang**, San Jose, CA (US)
- (73) Assignee: **Marvell World Trade Ltd.**, St. Michael (BB)
- (*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 193 days.

This patent is subject to a terminal disclaimer.

5,714,961	A	2/1998	Kot et al.	
6,184,828	B1	2/2001	Shoki	
6,597,316	B2	7/2003	Rao et al.	
7,006,043	B1	2/2006	Nalbandian	
7,394,433	B2*	7/2008	Li et al.	343/702
7,403,162	B2*	7/2008	Li et al.	343/702
7,423,597	B2*	9/2008	Li et al.	343/702
7,423,599	B2*	9/2008	Li et al.	343/702
7,495,621	B2*	2/2009	Li et al.	343/702
2002/0163473	A1	11/2002	Koyama et al.	
2003/0210187	A1	11/2003	Lu et al.	
2004/0004572	A1	1/2004	Ma	
2004/0239568	A1	12/2004	Masutani	

(Continued)

FOREIGN PATENT DOCUMENTS

EP 0 795 926 A2 9/1997

(Continued)

OTHER PUBLICATIONS

802.11n; IEEE P802.11-04/0889r6; Wireless LANs, TGn Sync Proposal Technical Specification; 131 pages.
Notification of Transmittal of The International Search Report and The Written Opinion of The International Searching Authority, or The Declaration; PCT/US2007/003594; Dated: Nov. 5, 2007; 24 pages.

(Continued)

Primary Examiner—HoangAnh T Le


(57) **ABSTRACT**

An antenna system includes first, second, and third antennas that are arranged on a substrate and that include an arc-shaped element having a concave side and a convex side, a conducting element that extends substantially radially from a center of the concave side, and a U-shaped element having a base portion with a center that communicates with the conducting element and two side portions that extend from ends of the base portion towards the concave side.

- (21) Appl. No.: **12/214,165**
- (22) Filed: **Jun. 17, 2008**
- (65) **Prior Publication Data**
US 2008/0291094 A1 Nov. 27, 2008
- Related U.S. Application Data**
- (63) Continuation of application No. 11/581,502, filed on Oct. 16, 2006, now Pat. No. 7,394,433, which is a continuation of application No. 11/519,979, filed on Sep. 12, 2006, now Pat. No. 7,423,597.
- (60) Provisional application No. 60/771,634, filed on Feb. 9, 2006.
- (51) **Int. Cl.**
H01Q 1/24 (2006.01)
- (52) **U.S. Cl.** **343/702; 343/700 MS**
- (58) **Field of Classification Search** **343/702, 343/700 MS, 846, 795**
See application file for complete search history.

- (56) **References Cited**
U.S. PATENT DOCUMENTS
4,343,976 A 8/1982 Nasretdin et al.

34 Claims, 38 Drawing Sheets





US007800549B2

(12) **United States Patent**
Rebeiz et al.

(10) **Patent No.:** **US 7,800,549 B2**
(45) **Date of Patent:** **Sep. 21, 2010**

(54) **MULTI-BEAM ANTENNA**

(75) Inventors: **Gabriel M. Rebeiz**, La Jolla, CA (US);
James P. Ebling, Ann Arbor, MI (US);
Bernhard Schoenlinner, Trostberg (DE)

(73) Assignee: **TK Holdings, Inc. Electronics**, Pontiac, MI (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 4 days.

(21) Appl. No.: **11/929,791**

(22) Filed: **Oct. 30, 2007**

(65) **Prior Publication Data**
US 2008/0055175 A1 Mar. 6, 2008

Related U.S. Application Data

(63) Continuation of application No. 11/627,369, filed on Jan. 25, 2007, which is a continuation-in-part of application No. 10/907,305, filed on Mar. 28, 2005, now abandoned, said application No. 11/627,369 is a continuation-in-part of application No. 11/161,681, filed on Aug. 11, 2005, now Pat. No. 7,358,913, which is a continuation-in-part of application No. 10/604,716, filed on Aug. 12, 2003, now Pat. No. 7,042,420, which is a continuation-in-part of application No. 10/202,242, filed on Jul. 23, 2002, now Pat. No. 6,606,077, which is a continuation-in-part of application No. 09/716,736, filed on Nov. 20, 2000, now Pat. No. 6,424,319.

(60) Provisional application No. 60/521,284, filed on Mar. 26, 2004, provisional application No. 60/522,077, filed on Aug. 11, 2004, provisional application No. 60/166,231, filed on Nov. 18, 1999.

(51) **Int. Cl.**
H01Q 3/24 (2006.01)

(52) **U.S. Cl.** **343/754; 343/911 R**

(58) **Field of Classification Search** 343/754, 343/753, 755, 911 R, 911 L
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,170,158 A 2/1965 Rotman et al.

(Continued)

FOREIGN PATENT DOCUMENTS

EP 0 483 686 B1 4/1996

(Continued)

OTHER PUBLICATIONS

Yngvesson et al., "The tapered slot antenna—a new integrated element for mm-wave applications," IEEE Trans. on Microwave Theory and Techniques, MTT-37, No. 2, Feb. 1989, pp. 365-374.

(Continued)


Primary Examiner—Tho G Phan

(74) *Attorney, Agent, or Firm*—Raggio & Dinnin, P.C.

(57) **ABSTRACT**

A plurality of antenna elements on a dielectric substrate are adapted to launch or receive electromagnetic waves in or from a direction substantially away from either a convex or concave edge of the dielectric substrate, wherein at least two of the antenna elements operate in different directions. Slotlines of tapered-slot endfire antennas in a first conductive layer of a first side of the dielectric substrate are coupled to microstrip lines of a second conductive layer on the second side of the dielectric substrate. A bi-conical reflector, conformal cylindrical dielectric lens, or discrete lens array improves the H-plane radiation pattern. Dipole or Yagi-Uda antenna elements on the conductive layer of the dielectric substrate can be used in cooperation with associated reflective elements, either alone or in combination with a corner-reflector of conductive plates attached to the conductive layers proximate to the endfire antenna elements.

2 Claims, 25 Drawing Sheets





US007804450B2

(12) **United States Patent**
Sullivan et al.

(10) **Patent No.:** **US 7,804,450 B2**
(45) **Date of Patent:** **Sep. 28, 2010**

(54) **HYBRID ANTENNA STRUCTURE**

(75) Inventors: **Jonathan L. Sullivan**, Lincoln, NE (US); **Stefan Lofgren**, Stockholm (SE); **Ulf Palin**, Stockholm (SE)

(73) Assignee: **Laird Technologies, Inc.**, Chesterfield, MO (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 647 days.

(21) Appl. No.: **11/780,964**

(22) Filed: **Jul. 20, 2007**

(65) **Prior Publication Data**

US 2009/0020328 A1 Jan. 22, 2009

(51) **Int. Cl.**
H01Q 1/38 (2006.01)
H01Q 21/00 (2006.01)

(52) **U.S. Cl.** **343/700 MS; 343/893**

(58) **Field of Classification Search** **343/700 MS, 343/893, 895**

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,018,326 A	1/2000	Rudisill
6,816,127 B2	11/2004	McKivergan et al.
6,819,287 B2	11/2004	Sullivan et al.
6,856,294 B2	2/2005	Kadambi et al.
7,081,855 B2	7/2006	Murray et al.
7,183,983 B2	2/2007	Ozden
7,510,985 B1	3/2009	Boenke et al.
7,651,932 B2	1/2010	Aoki et al.
2004/0026254 A1	2/2004	Hupe et al.

2004/0104040 A1*	6/2004	Schauz	174/250
2005/0205407 A1*	9/2005	Hein et al.	200/600
2006/0038737 A1	2/2006	Spiropoulos	
2007/0126651 A1	6/2007	Snyder et al.	
2008/0206553 A1	8/2008	Schneider et al.	
2008/0227235 A1*	9/2008	Theuss et al.	438/53
2009/0009403 A1*	1/2009	Sullivan	343/700 MS
2009/0020328 A1	1/2009	Sullivan et al.	
2009/0065590 A1	3/2009	Aoki et al.	
2009/0297802 A1	12/2009	Sastry et al.	
2010/0009094 A1	1/2010	Lochtman et al.	
2010/0021657 A1	1/2010	Lochtman et al.	

FOREIGN PATENT DOCUMENTS

EP	1 576 205 B1	1/2009
EP	1 141 776 B1	6/2009
EP	1 926 784 B1	1/2010
WO	WO 01/97583 A2	12/2001

OTHER PUBLICATIONS

Notification of Transmittal of the International Search Report and the Written Opinion of the International Searching Authority, or the Declaration re Application No. PCT/US08/66533 issued on Aug. 22, 2008.

* cited by examiner


Primary Examiner—Shih-Chao Chen

(74) *Attorney, Agent, or Firm*—Harness, Dickey & Pierce, P.L.C.

(57) **ABSTRACT**

An electrical component is provided that provides at least a two shot injection molding structure. One of the at least two shots of plastic comprises a laser direct structuring material. Another of the at least two shots of plastic comprises a non-platable plastic. The laser direct structuring material is selectively activated such that a conductive trace can be plated on the laser direct structuring material.

26 Claims, 6 Drawing Sheets





US007804451B2

(12) **United States Patent**
Glocker et al.

(10) **Patent No.:** **US 7,804,451 B2**
(45) **Date of Patent:** **Sep. 28, 2010**

(54) **WIRELESS COMMUNICATION DEVICE
HAVING A REDUCED SAR VALUE**

(75) Inventors: **Wolfgang Glocker**, Memmingen (DE);
Stefan Huber, München (DE);
Thorsten Kowalski, München (DE);
Martin Oelschläger, Berlin (DE);
Michael Schreiber, Aying-Göggenhofen
(DE); **Martin Weinberger**, München
(DE)

(73) Assignee: **Palm, Inc.**, Sunnyvale, CA (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **10/527,768**

(22) PCT Filed: **Sep. 11, 2003**

(86) PCT No.: **PCT/DE03/02983**

§ 371 (c)(1),
(2), (4) Date: **Sep. 23, 2005**

(87) PCT Pub. No.: **WO2004/027924**

PCT Pub. Date: **Apr. 1, 2004**

(65) **Prior Publication Data**

US 2006/0139216 A1 Jun. 29, 2006

(30) **Foreign Application Priority Data**

Sep. 12, 2002 (DE) 102 42 386
Oct. 18, 2002 (DE) 102 48 756

(51) **Int. Cl.**
H01Q 1/24 (2006.01)

(52) **U.S. Cl.** **343/702**

(58) **Field of Classification Search** 343/702,
343/841, 846; 455/575, 90, 575.1, 575.3-575.5,
455/575.7, 575.8, 90.3
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,246,374 B1 * 6/2001 Perrotta et al. 343/702
6,421,016 B1 * 7/2002 Phillips et al. 343/702
6,650,294 B2 * 11/2003 Ying et al. 343/700 MS
6,728,555 B1 * 4/2004 Pirila et al. 455/566
7,065,379 B1 * 6/2006 Kim et al. 455/550.1
2002/0061734 A1 * 5/2002 Ito 455/90

FOREIGN PATENT DOCUMENTS

DE 102 04 877 8/2003
WO WO 01/33665 5/2001
WO WO 02/15333 2/2002
WO WO 02/071534 9/2002

* cited by examiner

Primary Examiner—Hoang V Nguyen


Assistant Examiner—Robert Karacsony

(74) *Attorney, Agent, or Firm*—K&L Gates LLP

(57) **ABSTRACT**

In order to reduce the SAR value in a wireless communication device (MP), an additional, current-conducting corrective element (CE1) is coupled to and configured in relation to the printed circuit board (LP) and the antenna (AT1) such that the amplitude level (IM1, NIM1) and/or the phase angle of electrical currents (I3, I1, I2) on the antenna (AT1), the printed circuit board (LP), and the corrective element (CE1) are adjusted relative to each other in such a way that the SAR distribution resulting from such currents becomes minimal.

37 Claims, 3 Drawing Sheets





US007804453B2

(12) **United States Patent**
Chiang et al.

(10) **Patent No.:** **US 7,804,453 B2**
(45) **Date of Patent:** **Sep. 28, 2010**

(54) **ANTENNAS FOR WIRELESS ELECTRONIC DEVICES**

6,380,930	B1	4/2002	Van Ruymbeke
2002/0149523	A1	10/2002	Fang et al.
2004/0051670	A1	3/2004	Sato
2007/0057855	A1	3/2007	Mizoguchi et al.
2007/0115187	A1	5/2007	Zhang et al.
2008/0018551	A1	1/2008	Cheng et al.

(75) Inventors: **Bing Chiang**, Cupertino, CA (US);
Douglas Blake Kough, San Jose, CA (US);
Enrique Ayala Vazquez, Watsonville, CA (US);
Eduardo Lopez Camacho, Watsonville, CA (US);
Gregory Allen Springer, Sunnyvale, CA (US)

FOREIGN PATENT DOCUMENTS

EP	1 329 979	A1	7/2003
EP	1 329 985	A2	7/2003

(73) Assignee: **Apple Inc.**, Cupertino, CA (US)

Primary Examiner—Hoang V Nguyen
(74) *Attorney, Agent, or Firm*—Treyz Law Group; David C. Kellogg; G. Victor Treyz

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 212 days.

(57) **ABSTRACT**

(21) Appl. No.: **12/104,359**

Antenna window structures and antennas are provided for electronic devices. The electronic devices may be laptop computers or other devices that have conductive housings. Antenna windows can be formed from dielectric members. The dielectric members can have elastomeric properties. An antenna may be mounted inside a conductive housing beneath a dielectric member. The antenna can be formed from a parallel plate waveguide structure. The parallel plate waveguide structure may have a ground plate and a radiator plate and may have dielectric material between the ground and radiator plates. The ground plate can have a primary ground plate portion and a ground strip. The ground strip may reflect radio-frequency signals so that they travel through the dielectric member. The antenna may handle radio-frequency antenna signals in one or more communications bands. The radio-frequency antenna signals pass through the dielectric member.


(22) Filed: **Apr. 16, 2008**

(65) **Prior Publication Data**
US 2009/0262029 A1 Oct. 22, 2009

(51) **Int. Cl.**
H01Q 1/24 (2006.01)
(52) **U.S. Cl.** **343/702**
(58) **Field of Classification Search** **343/702,**
343/872; 455/575.1, 575.3, 575.8
See application file for complete search history.

(56) **References Cited**
U.S. PATENT DOCUMENTS
6,081,729 A 6/2000 Bauerschmidt et al.
6,339,400 B1 1/2002 Flint et al.

14 Claims, 10 Drawing Sheets





US007804456B2

(12) **United States Patent**
Yekeh Yazdandoost et al.

(10) **Patent No.:** **US 7,804,456 B2**
(45) **Date of Patent:** **Sep. 28, 2010**

- (54) **ULTRA WIDEBAND LOOP ANTENNA**
- (75) Inventors: **Kamya Yekeh Yazdandoost**, Koganei (JP); **Ryuji Kohno**, Koganei (JP)
- (73) Assignee: **National Institute of Information and Communications Technology**, Tokyo (JP)
- (*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 379 days.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,761,933	A *	9/1973	Smalser	343/740
4,298,878	A	11/1981	Dupressoir et al.	
4,940,992	A *	7/1990	Nguyen et al.	343/803
6,259,416	B1	7/2001	Qi et al.	
6,693,599	B1 *	2/2004	Chia et al.	343/741

FOREIGN PATENT DOCUMENTS

JP	2004-048233	2/2004
JP	2004-112044 A	4/2004

OTHER PUBLICATIONS

Kin-Lu Wong et al., A Low-Profile Planar Monopole Antenna for Multiband Operation of Mobile Handsets, IEEE Transactions on Antennas and Propagation, vol. 51, No. 1, Jan. 2003, pp. 121-125.
 Julien Perruisseau-Carrier et al., Dual-Polarized Broadband Dipole, IEEE Antennas and Wireless Propagation Letters, vol. 2, 2003, pp. 310-312.

(Continued)

Primary Examiner—Hoang V Nguyen
(74) Attorney, Agent, or Firm—McGlew and Tuttle, P.C.

- (21) Appl. No.: **11/568,338**
- (22) PCT Filed: **Dec. 28, 2004**
- (86) PCT No.: **PCT/JP2004/019594**
 § 371 (c)(1), (2), (4) Date: **Jun. 14, 2008**
- (87) PCT Pub. No.: **WO2005/107011**
 PCT Pub. Date: **Nov. 10, 2005**

(65) **Prior Publication Data**
 US 2008/0297424 A1 Dec. 4, 2008


(30) **Foreign Application Priority Data**
 Apr. 28, 2004 (JP) 2004-133759

- (51) **Int. Cl.**
H01Q 11/12 (2006.01)
- (52) **U.S. Cl.** **343/741; 343/866**
- (58) **Field of Classification Search** **343/741, 343/866, 700 MS, 850**
 See application file for complete search history.

(57) **ABSTRACT**

The wideband L-loop antenna is presented in this invention. It has excellent performance for lower band of UWB system and has the attractive features of small size, inexpensive, and easy to design. The antenna composed of a single metallic layer is printed on the top of a substrate and a coupled tapered transmission line is printed on the top of the same substrate. A L shape portion is formed by widening partially or wholly the width of a part of antenna elements in comparison with the other part.

13 Claims, 11 Drawing Sheets





US007804457B2

(12) **United States Patent**
Oshiyama et al.

(10) **Patent No.:** **US 7,804,457 B2**
(45) **Date of Patent:** **Sep. 28, 2010**

(54) **MULTI-BAND ANTENNA WITH INDUCTOR AND/OR CAPACITOR**

(75) Inventors: **Tadashi Oshiyama**, Gunma (JP);
Hirotohi Mizuno, Gunma (JP); **Yusuke Suzuki**, Gunma (JP)

(73) Assignee: **Yokowo Co., Ltd.**, Tokyo (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 380 days.

(21) Appl. No.: **11/645,012**

(22) Filed: **Dec. 26, 2006**

(65) **Prior Publication Data**
US 2007/0146221 A1 Jun. 28, 2007

(30) **Foreign Application Priority Data**
Dec. 27, 2005 (JP) P2005-375101

(51) **Int. Cl.**
H01Q 9/00 (2006.01)
H01Q 9/04 (2006.01)

(52) **U.S. Cl.** **343/749**; 343/825

(58) **Field of Classification Search** 343/895,
343/700 MS, 702, 752, 741, 744, 745, 747-750,
343/803, 825, 828, 829
See application file for complete search history.

(56) **References Cited**
U.S. PATENT DOCUMENTS
6,515,625 B1* 2/2003 Johnson 343/700 MS
6,903,688 B2* 6/2005 Edvardsson 343/700 MS

7,336,239 B2	2/2008	Takei	
7,420,511 B2*	9/2008	Oshiyama et al.	343/700 MS
2003/0020661 A1*	1/2003	Sato	343/702
2006/0017635 A1*	1/2006	Zheng	343/748

FOREIGN PATENT DOCUMENTS

KR	10-2005-0050098	5/2005
WO	WO 2004/047223 A1	6/2004


* cited by examiner

Primary Examiner—Hoang V Nguyen
Assistant Examiner—Robert Karacsony
(74) *Attorney, Agent, or Firm*—Morgan, Lewis & Bockius LLP

(57) **ABSTRACT**

A multi-band antenna is adapted to operate in a first frequency band and a second frequency band which is lower than the first frequency band. In the multi-band antenna, an antenna element has an electrical length of 3/4 wavelength of the first frequency band. The antenna element has a first end adapted to be electrically connected to a power feeding point, and a second end. An inductor is electrically connected between the second end of the antenna element and a ground in a serial manner. The inductor has such an inductance that an electrical length of the antenna element and the inductor corresponds to 1/2 wavelength of the second frequency band.

8 Claims, 10 Drawing Sheets





US007804458B2

(12) **United States Patent**
Montgomery et al.

(10) **Patent No.:** **US 7,804,458 B2**
(45) **Date of Patent:** **Sep. 28, 2010**

- (54) **SLOT ANTENNA** 5,489,913 A * 2/1996 Raguene et al. 343/767
- (75) Inventors: **Mark Montgomery**, Melbourne Beach, FL (US); **Frank M. Caimi**, Vero Beach, FL (US) 5,955,997 A 9/1999 Ho 6,636,181 B2 * 10/2003 Asano et al. 343/702 7,079,081 B2 7/2006 Parsche 2007/0194994 A1 * 8/2007 Waltho 343/702
- (73) Assignee: **SkyCross, Inc.**, Melbourne, FL (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 147 days.

* cited by examiner

(21) Appl. No.: **12/055,259**

Primary Examiner—Hoang V Nguyen

(22) Filed: **Mar. 25, 2008**

(74) *Attorney, Agent, or Firm*—John L. DeAngelis; Beusse Wolter Sanks Mora & Maire, P.A.

(65) **Prior Publication Data**
US 2008/0231522 A1 Sep. 25, 2008

(57) **ABSTRACT**

Related U.S. Application Data

A communications device for sending and receiving an information signal. The communications device comprising an element having an opening defined therein for receiving an antenna, the element comprising first conductive material disposed proximate the opening and comprising transmitting and receiving circuits. The antenna comprises: a dielectric tubular member, second conductive material forming an exterior surface of the tubular member with the second conductive material defining a slot therein, a slot length approximately equal to one-half of a guided wavelength and a feed connected to the transmitting and receiving circuits and disposed proximate the slot for establishing currents in the second conductive material.

(60) Provisional application No. 60/896,930, filed on Mar. 25, 2007.

(51) **Int. Cl.**
H01Q 13/10 (2006.01)
H01Q 1/24 (2006.01)

(52) **U.S. Cl.** **343/767; 343/702**

(58) **Field of Classification Search** 343/767, 343/770, 702, 700 MS


See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

- 3,852,994 A * 12/1974 Pereda 73/35.15
- 4,328,502 A * 5/1982 Scharp 343/771

17 Claims, 2 Drawing Sheets





US007804459B2

(12) **United States Patent**
Chung et al.

(10) **Patent No.:** **US 7,804,459 B2**
(45) **Date of Patent:** **Sep. 28, 2010**

(54) **TRANSMISSION LINE LOADED DUAL-BAND MONOPOLE ANTENNA**

WO WO96/02075 1/1996
WO WO98/15031 4/1998

(75) Inventors: **Shyh-Jong Chung**, Hsinchu (TW);
Yu-Hsin Wang, Taichung (TW);
Yu-Chiang Cheng, Taipei (TW)

OTHER PUBLICATIONS

(73) Assignee: **Getac Technology Corporation**,
Hsinchu (TW)

Communication from the European Patent Office regarding a corresponding foreign application dated Aug. 26, 2008.

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 222 days.

Kennedy, et al.; "Investigation of impedance and radiation properties of dual-frequency choke-loaded monopole antennas"; Electronics Letters; Mar. 20, 2003; V. 39, No. 6; (2 pages).

Rogers, et al.; "Wide-band Sleeve-Cage and Sleeve-Helical Antennas"; IEEE Transactions on Antennas and Propagation; vol. 50, No. 10; Oct. 2002; pp. 1409-1414.

(21) Appl. No.: **12/213,611**

* cited by examiner

(22) Filed: **Jun. 23, 2008**

Primary Examiner—HoangAnh T Le

(65) **Prior Publication Data**

(57) **ABSTRACT**

US 2009/0115678 A1 May 7, 2009

(30) **Foreign Application Priority Data**

Disclosed is a transmission line loaded dual-band monopole antenna, which realizes operation in dual bands with a single antenna. The dual-band monopole antenna includes a monopole antenna and a transmission line load. The monopole antenna has a signal feeding terminal and a load connection terminal. The load connection terminal is connected to the transmission line load. The transmission line load includes a core transmission line, an outer circumferential conductor, and a short-circuit section. The core transmission line has an antenna connection terminal and a short-circuit terminal. The antenna connection terminal is connected to the load connection terminal of the monopole antenna. The outer circumferential conductor circumferentially surrounds and is spaced from the core transmission line and the outer circumferential conductor has an open terminal and a short-circuit terminal. The opening of the open terminal of the outer circumferential conductor faces the antenna connection terminal of the core transmission line so that the outer circumferential conductor forms an open structure facing the monopole antenna.

Nov. 5, 2007 (TW) 96141724 A
Mar. 4, 2008 (TW) 97107522 A

(51) **Int. Cl.**
H01Q 9/04 (2006.01)

(52) **U.S. Cl.** **343/791; 343/790**

(58) **Field of Classification Search** **343/790, 343/791, 792, 900**

See application file for complete search history.

(56) **References Cited**


U.S. PATENT DOCUMENTS

3,508,271 A * 4/1970 Kuecken 343/745
5,995,065 A * 11/1999 Kitchener et al. 343/895
6,266,026 B1 7/2001 Stengel, Jr.
2007/0080878 A1* 4/2007 McLean 343/725

FOREIGN PATENT DOCUMENTS

DE 3732994 4/1989

15 Claims, 17 Drawing Sheets





US007804463B2

(12) **United States Patent**
Degner et al.

(10) **Patent No.:** **US 7,804,463 B2**
(45) **Date of Patent:** **Sep. 28, 2010**

(54) **ANTENNA-CARRYING ASSEMBLY**

(75) Inventors: **Brett William Degner**, Menlo Park, CA (US); **Chris Ligtenberg**, San Carlos, CA (US); **Bartley K. Andre**, Menlo Park, CA (US); **Douglas B. Kough**, San Jose, CA (US)

(73) Assignee: **Apple Inc.**, Cupertino, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 615 days.

(21) Appl. No.: **11/835,944**

(22) Filed: **Aug. 8, 2007**

(65) **Prior Publication Data**

US 2009/0040129 A1 Feb. 12, 2009

(51) **Int. Cl.**
H01Q 1/12 (2006.01)

(52) **U.S. Cl.** **343/878**; 343/700 MS; 343/702; 343/895

(58) **Field of Classification Search** 343/700 MS, 343/702, 878, 895; 235/441, 449, 451, 492, 235/472.01, 472.03

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,410,325 A 4/1995 Friedrich et al.

5,779,496 A *	7/1998	Bolinger et al.	439/377
5,834,756 A *	11/1998	Gutman et al.	235/493
5,841,122 A *	11/1998	Kirchhoff	235/492
6,344,825 B1 *	2/2002	Wong	343/702
6,618,013 B1 *	9/2003	Aldous	343/702
7,068,238 B2	6/2006	Yoneya et al.	
7,114,652 B2 *	10/2006	Moulette et al.	235/449
7,129,906 B2	10/2006	Yoneya et al.	
7,486,165 B2 *	2/2009	Ligtenberg et al.	335/205
7,701,400 B2 *	4/2010	Su et al.	343/702
2007/0218837 A1 *	9/2007	Lessing et al.	455/41.2

* cited by examiner

Primary Examiner—Douglas W Owens

Assistant Examiner—Chuc D Tran

(57) **ABSTRACT**

An antenna-carrying assembly for facilitating wireless communication using an electronic device is disclosed. The antenna-carrying assembly may include a body and one or more antenna elements carried by the body. The antenna-carrying assembly may also include a first attraction element carried by the body. The first attraction element is configured to magnetically couple the antenna-carrying assembly with a track and to slide along the track. At least one of the first attraction element and the track includes one or more magnetic elements.

30 Claims, 7 Drawing Sheets

