



US008593348B2

(12) **United States Patent**  
**Krupa et al.**

(10) **Patent No.:** **US 8,593,348 B2**  
(45) **Date of Patent:** **Nov. 26, 2013**

- (54) **DISTRIBUTED COUPLING ANTENNA**
- (75) Inventors: **Steve Krupa**, Tiberias (IL); **Snir Azulay**, Tiberias (IL)
- (73) Assignee: **Galtronics Corporation Ltd.**, Tiberias (IL)
- (\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 82 days.
- (21) Appl. No.: **13/203,109**
- (22) PCT Filed: **Apr. 7, 2010**
- (86) PCT No.: **PCT/IL2010/000291**  
§ 371 (c)(1),  
(2), (4) Date: **Nov. 4, 2011**
- (87) PCT Pub. No.: **WO2010/116373**  
PCT Pub. Date: **Oct. 14, 2010**
- (65) **Prior Publication Data**  
US 2012/0044121 A1 Feb. 23, 2012

**Related U.S. Application Data**

- (60) Provisional application No. 61/167,247, filed on Apr. 7, 2009.
- (51) **Int. Cl.**  
**H01Q 1/38** (2006.01)
- (52) **U.S. Cl.**  
USPC ..... **343/700 MS; 343/745; 343/846; 343/860**
- (58) **Field of Classification Search**  
USPC ..... **343/700 MS, 745, 846, 850, 860**  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,343,089	A *	9/1967	Murphy et al.	455/123
3,909,830	A *	9/1975	Campbell	343/703
4,876,522	A	10/1989	Mitlmeier et al.	
5,867,127	A *	2/1999	Black et al.	343/702
6,518,937	B2 *	2/2003	Fang	343/895
6,906,667	B1	6/2005	Poilasne et al.	
6,958,729	B1	10/2005	Metz	
7,091,907	B2	8/2006	Brachat	
7,190,322	B2 *	3/2007	Apostolos et al.	343/841
7,408,512	B1	8/2008	Rodenbeck et al.	

(Continued)

FOREIGN PATENT DOCUMENTS

WO	WO 2008/054108	A1	5/2008
WO	WO 2010/044086	A1	4/2010
WO	WO 2010/116373	A1	10/2010

OTHER PUBLICATIONS

Bank, M. et al., "Cell Phone Antennas, Problems and Solutions", Proceedings of the 3rd International Conference on Communications and Information Technology, p. 1-3, Dec. 2009.

(Continued)


*Primary Examiner* — David G Phan

(74) *Attorney, Agent, or Firm* — Sughrue Mion, PLLC

(57) **ABSTRACT**

An antenna including a ground plane region, a feed element having associated with it a first reactance and a coupling element having associated with it a second reactance, the second reactance being of opposite sign to the first reactance, the coupling element being coupled to the feed element and to the ground plane region and being located in close proximity to the ground plane region, wherein an impedance and hence a resonant frequency of the antenna depend on the first and second reactances.

**29 Claims, 3 Drawing Sheets**





US008593351B2

(12) **United States Patent**  
**Hsieh et al.**

(10) **Patent No.:** **US 8,593,351 B2**  
(45) **Date of Patent:** **Nov. 26, 2013**

- (54) **PORTABLE ELECTRONIC DEVICE**
- (75) Inventors: **Shih-Wei Hsieh**, Taipei (TW);  
**Shyh-Tirng Fang**, Tai-Nan (TW)
- (73) Assignee: **Mediatek Inc.**, Hsin-Chu (TW)
- (\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 355 days.
- (21) Appl. No.: **12/855,608**
- (22) Filed: **Aug. 12, 2010**
- (65) **Prior Publication Data**  
US 2012/0038516 A1 Feb. 16, 2012
- (51) **Int. Cl.**  
**H01Q 1/24** (2006.01)
- (52) **U.S. Cl.**  
USPC ..... **343/702**; 343/895; 343/818
- (58) **Field of Classification Search**  
USPC ..... 343/702, 895, 783, 817-819, 872, 878,  
343/700 MS  
See application file for complete search history.

2004/0021608 A1 2/2004 Kojima et al.  
2006/0170601 A1 8/2006 Fang  
2008/0158065 A1 7/2008 Wee

FOREIGN PATENT DOCUMENTS

CN 1633735 6/2005  
CN 1812277 8/2006

OTHER PUBLICATIONS

Lindberg, P., et al; "Improvement of Hearing Aid Compatibility (HAC) of Terminal Antennas using Wavetraps;" IEEE; 2009; pp. 1-4.

\* cited by examiner

*Primary Examiner* — Daniel D Chang


(74) *Attorney, Agent, or Firm* — McClure, Qualey & Rodack, LLP

(57) **ABSTRACT**

A portable electronic device is provided. The portable electronic device includes a housing, a circuit board, an amplifier, an antenna and a short element. The circuit board is disposed in the housing, wherein the circuit board includes a first edge and a second edge, and the first edge is opposite to the second edge. The amplifier is disposed on the circuit board and adjacent to the first edge. The antenna is disposed on the second edge of the circuit board, wherein the antenna transmits a wireless signal. The short element is disposed on the second edge of the circuit board, wherein the short element is separated from the antenna, and the short element couples with the antenna to reduce Specific Absorption Rate (SAR) value around the amplifier.

**15 Claims, 4 Drawing Sheets**

- (56) **References Cited**  
U.S. PATENT DOCUMENTS  
7,126,545 B2 \* 10/2006 Nagano et al. .... 343/702  
2002/0058483 A1 \* 5/2002 Shinichi et al. .... 455/90





US008593352B2

(12) **United States Patent**  
**Tseng et al.**

(10) **Patent No.:** **US 8,593,352 B2**  
(45) **Date of Patent:** **Nov. 26, 2013**

(54) **TRIPLE-BAND ANTENNA WITH LOW PROFILE**

(75) Inventors: **Hsien-Sheng Tseng**, Tu-Cheng (TW);  
**Shang-Jen Chen**, Tu-Cheng (TW)

(73) Assignee: **Hon Hai Precision Industry Co., Ltd.**,  
New Taipei (TW)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 617 days.

(21) Appl. No.: **12/857,764**

(22) Filed: **Aug. 17, 2010**

(65) **Prior Publication Data**

US 2011/0037672 A1 Feb. 17, 2011

(30) **Foreign Application Priority Data**

Aug. 17, 2009 (TW) ..... 98127534

(51) **Int. Cl.**  
**H01Q 1/24** (2006.01)  
**H01Q 13/10** (2006.01)  
**H01Q 1/48** (2006.01)

(52) **U.S. Cl.**  
USPC ..... **343/702**; 343/767; 343/846

(58) **Field of Classification Search**  
USPC ..... 343/700 MS, 702, 767, 846, 848  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

7,501,987 B2	3/2009	Wang et al.	
7,777,684 B2 *	8/2010	Rao et al.	343/770
7,782,261 B2 *	8/2010	An et al.	343/702
2006/0262016 A1	11/2006	Hung et al.	
2007/0103367 A1 *	5/2007	Wang	343/700 MS
2009/0073052 A1	3/2009	Hung et al.	
2010/0238072 A1 *	9/2010	Ayatollahi et al.	343/700 MS

FOREIGN PATENT DOCUMENTS

CN	2706884 Y	6/2005
CN	101102008	1/2008
CN	101308954	11/2008

\* cited by examiner

*Primary Examiner* — Michael C Wimer


*Assistant Examiner* — Hasan Islam

(74) *Attorney, Agent, or Firm* — Wei Te Chung; Ming Chieh Chang

(57) **ABSTRACT**

A multi-band antenna includes a grounding element having an edge and a grounding point, a first radiating arm being substantially of L shape and located above the grounding element, a second radiating arm working at a first frequency band and being substantially of L shape above the first radiating arm, a third radiating arm working at a second frequency band and being substantially of rectangular metal patch parallel to the edge of the grounding element, and a feeding line including an inner conductor connected to the first radiating arm and an outer conductor connected to the grounding point of the grounding element. The feeding line, the first radiating arm, the grounding element commonly compose a slot operating at a third frequency band.

**20 Claims, 3 Drawing Sheets**





US008593353B2

(12) **United States Patent**  
**Byun et al.**

(10) **Patent No.:** **US 8,593,353 B2**  
(45) **Date of Patent:** **Nov. 26, 2013**

- (54) **ANTENNA DEVICE FOR A PORTABLE TERMINAL**
- (75) Inventors: **Joon-Ho Byun**, Suwon-si (KR); **Soon-Ho Hwang**, Seoul (KR); **Mun-Il Kim**, Seoul (KR); **Do-Won Kim**, Seoul (KR); **Hyun-Seok Park**, Seoul (KR)
- (73) Assignees: **Samsung Electronics Co., Ltd.** (KR); **Korea University Industrial & Academic Collaboration Foundation** (KR)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 368 days.

- (21) Appl. No.: **12/999,802**
- (22) PCT Filed: **Jun. 12, 2009**
- (86) PCT No.: **PCT/KR2009/003171**  
§ 371 (c)(1),  
(2), (4) Date: **May 20, 2011**
- (87) PCT Pub. No.: **WO2009/154376**  
PCT Pub. Date: **Dec. 23, 2009**

(65) **Prior Publication Data**  
US 2011/0210897 A1 Sep. 1, 2011

(30) **Foreign Application Priority Data**  
Jun. 19, 2008 (KR) ..... 10-2008-0057814

- (51) **Int. Cl.**  
**H01Q 1/24** (2006.01)
- (52) **U.S. Cl.**  
USPC ..... **343/702**; 343/700 MS; 343/749
- (58) **Field of Classification Search**  
USPC ..... 343/700 MS, 702, 749, 829, 846  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,483,249	A *	1/1996	Kennedy	343/846
6,819,287	B2 *	11/2004	Sullivan et al.	343/700 MS
6,842,149	B2 *	1/2005	Taubman	343/702
7,760,146	B2 *	7/2010	Ollikainen	343/702
7,990,320	B2 *	8/2011	Pros et al.	343/700 MS
8,339,321	B2 *	12/2012	Nagano et al.	343/702
2005/0237251	A1	10/2005	Boyle et al.	
2005/0270240	A1	12/2005	Qi et al.	
2006/0055606	A1	3/2006	Boyle	

FOREIGN PATENT DOCUMENTS

KR	1020040108759	12/2004
KR	1020050007557	1/2005
KR	1020070001175	1/2007
KR	1020070098020	10/2007

OTHER PUBLICATIONS

PCT/ISA/237 Written Opinion issued on PCT/KR2009/003171 (10 pp.).


\* cited by examiner

*Primary Examiner* — Tho G Phan  
(74) *Attorney, Agent, or Firm* — The Farrell Law Firm, P.C.

(57) **ABSTRACT**

An antenna device for a portable terminal includes: a ground pattern provided on one surface of a circuit board; a first antenna pattern configured to resonate at a first frequency band and provided on an opposite surface of the circuit board; and a second antenna pattern configured to resonate at a second frequency band different from the first frequency band and arranged along a periphery of the ground pattern. The second antenna pattern is a zeroth order mode resonator including a plurality of capacitors and a plurality of inductors. The antenna device easily secures the operation characteristics of different operation frequency bands and contributes to miniaturization of the portable terminal. Thus, a user can conveniently carry and use the portable terminal.

**12 Claims, 7 Drawing Sheets**





US008593354B2

(12) **United States Patent**  
**Tai et al.**

(10) **Patent No.:** **US 8,593,354 B2**  
(45) **Date of Patent:** **Nov. 26, 2013**

(54) **MULTI-BAND ANTENNA**

(75) Inventors: **Lung-Sheng Tai**, New Taipei (TW);  
**Chun-Ming Chiu**, New Taipei (TW);  
**Po-Kang Ku**, New Taipei (TW)

(73) Assignee: **Hon Hai Precision Industry Co., Ltd.**,  
New Taipei (TW)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 393 days.

(21) Appl. No.: **13/007,784**

(22) Filed: **Jan. 17, 2011**

(65) **Prior Publication Data**

US 2011/0175794 A1 Jul. 21, 2011

(30) **Foreign Application Priority Data**

Jan. 15, 2010 (TW) ..... 99200813

(51) **Int. Cl.**  
**H01Q 1/24** (2006.01)  
**H01Q 1/38** (2006.01)

(52) **U.S. Cl.**  
USPC ..... **343/702**; 343/700 MS; 343/846;  
343/908

(58) **Field of Classification Search**  
None  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

7,466,272 B1 \* 12/2008 Su et al. .... 343/700 MS  
7,642,967 B2 \* 1/2010 Wang et al. .... 343/702  
7,839,342 B2 \* 11/2010 Su et al. .... 343/702  
2006/0262016 A1 \* 11/2006 Hung et al. .... 343/702

2007/0171130 A1 \* 7/2007 Chung et al. .... 343/700 MS  
2008/0030407 A1 \* 2/2008 Hung et al. .... 343/700 MS  
2008/0266185 A1 \* 10/2008 Hung et al. .... 343/700 MS  
2008/0278382 A1 \* 11/2008 Hung et al. .... 343/700 MS  
2008/0309563 A1 \* 12/2008 Wang et al. .... 343/702  
2009/0027277 A1 \* 1/2009 Su et al. .... 343/700 MS  
2009/0109098 A1 \* 4/2009 Hung et al. .... 343/700 MS  
2009/0135070 A1 \* 5/2009 Hung et al. .... 343/700 MS  
2011/0037680 A1 \* 2/2011 Chiu et al. .... 343/893

\* cited by examiner


*Primary Examiner* — Trinh Dinh

(74) *Attorney, Agent, or Firm* — Wei Te Chung; Ming Chieh Chang

(57) **ABSTRACT**

A multi-band antenna (1), comprising a grounding element (10) extending horizontally along a longitudinal direction, comprising a side edge (101) with a connecting point (102) and a grounding point (103) distanced from the connecting point by a length; a radiating element (11) disposed at an upper level parallel to the grounding element and defining a first end and a second end, and operating in a first frequency band; a connecting element (12) located between the radiating element and the grounding element, comprising a first portion (121) connecting to the first end of the radiating element and a second portion (122) linking to said connecting point of the grounding element; a parasitic element (13) extending from the second portion of the connecting element towards the second end of the radiating element along the longitudinal direction, and operating in a second frequency band; a feeding point (141) disposed on the second portion of the connecting element and under the parasitic element; and a feeding line (15) comprising an inner conductor connected to the feeding point and an outer conductor connected to the grounding point; wherein said connecting element, the grounding element, the feeding point and the grounding point together forming a slot (16) operating in a third frequency band.

**20 Claims, 3 Drawing Sheets**





US008593355B1

(12) **United States Patent  
Tonn**


(10) **Patent No.:** US 8,593,355 B1  
(45) **Date of Patent:** Nov. 26, 2013

- (54) **RECONFIGURABLE BUOYANT CABLE ANTENNA WITH IMPROVED GAIN**
- (75) Inventor: **David A. Tonn**, Charlestown, RI (US)
- (73) Assignee: **The United States of America as represented by the Secretary of the Navy**, Washington, DC (US)
- (\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 685 days.
- (21) Appl. No.: **12/822,523**
- (22) Filed: **Jun. 24, 2010**
- (51) **Int. Cl.**  
**H01Q 1/34** (2006.01)
- (52) **U.S. Cl.**  
USPC ..... **343/709**
- (58) **Field of Classification Search**  
USPC ..... 343/709  
See application file for complete search history.

- (56) **References Cited**  
U.S. PATENT DOCUMENTS  
6,426,464 B1 \* 7/2002 Spellman et al. .... 174/101.5  
\* cited by examiner  
*Primary Examiner* — Hoang V Nguyen  
*Assistant Examiner* — Kyana R Robinson  
(74) *Attorney, Agent, or Firm* — James M. Kasischke; Jean-Paul A. Nasser; Michael P. Stanley

(57) **ABSTRACT**  
An antenna element with a single-conductor antenna is provided within a removable core. The removable core is mounted within a hollow liner by sliding the core into the hollow liner. A pull cable may be attached to an end of the removable core to pull the core through the outboard end of the hollow liner. Due to reduced strain on the core as compared to the liner, the single-conductor antenna may be formed in segments interconnected with capacitors for adjusting the antenna gain to a maximum in the vicinity of a desired operating frequency or frequencies.

**14 Claims, 4 Drawing Sheets**





US008593358B2

(12) **United States Patent**  
**Rappaport**

(10) **Patent No.:** **US 8,593,358 B2**  
(45) **Date of Patent:** **Nov. 26, 2013**

(54) **ACTIVE ANTENNAS FOR MULTIPLE BANDS  
IN WIRELESS PORTABLE DEVICES**

- (71) Applicant: **Theodore S. Rappaport**, Riner, VA (US)
- (72) Inventor: **Theodore S. Rappaport**, Riner, VA (US)
- (\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.
- (21) Appl. No.: **13/713,804**
- (22) Filed: **Dec. 13, 2012**
- (65) **Prior Publication Data**  
US 2013/0141294 A1 Jun. 6, 2013

**Related U.S. Application Data**

- (63) Continuation of application No. 12/541,764, filed on Aug. 14, 2009, now Pat. No. 8,350,763.
- (60) Provisional application No. 61/088,829, filed on Aug. 14, 2008.
- (51) **Int. Cl.**  
**H01Q 1/50** (2006.01)
- (52) **U.S. Cl.**  
USPC ..... **343/745; 343/702**
- (58) **Field of Classification Search**  
USPC ..... **343/702, 722, 745**  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,381,222	A *	4/1968	Gray	455/77
3,689,928	A *	9/1972	Felsenheld	343/703
4,499,606	A	2/1985	Rambo	
6,140,966	A *	10/2000	Pankinaho	343/700 MS
6,693,600	B1	2/2004	Elliot	
6,762,723	B2 *	7/2004	Nallo et al.	343/700 MS
7,088,299	B2	8/2006	Siegler et al.	
7,132,989	B1 *	11/2006	Poilasne	343/745
8,421,695	B2 *	4/2013	Friman et al.	343/745
8,456,366	B2 *	6/2013	Vance	343/700 MS
2003/0151556	A1	8/2003	Cohen	
2008/0158081	A1	7/2008	Rofougaran	


\* cited by examiner

*Primary Examiner* — Tho G Phan  
(74) *Attorney, Agent, or Firm* — Whitham Curtis Christofferson & Cook, PC

(57) **ABSTRACT**

Wireless devices, and particularly mobile devices such as cellphones, PDAs, computers, navigation devices, etc., as well as other devices which transmit or receive data or other signals at multiple frequency bands utilize at least one antenna to transmit and receive and a plurality of different bands (e.g., GSM cellular communication band; Bluetooth short range communication band; ultrawideband (UWB) communications, etc.). These wireless devices can simultaneously transmit or receive at a plurality of different bands, or simultaneously transmit and receive at different bands. The wireless devices have the ability to use a single physical structure (e.g., an antenna) for transmission and reception of many different bands. The antenna can be either actively tuned or passively tuned using one or more elements.

**31 Claims, 3 Drawing Sheets**





US008593360B2

(12) **United States Patent**  
**Baliarda et al.**

(10) **Patent No.:** **US 8,593,360 B2**  
(45) **Date of Patent:** **\*Nov. 26, 2013**

(54) **SLOTTED GROUND-PLANE USED AS A SLOT ANTENNA OR USED FOR A PIFA ANTENNA**

(75) Inventors: **Carles Puente Baliarda**, Barcelona (ES); **Jaime Anguera Pros**, Castellon (ES)

(73) Assignee: **Fractus, S.A.**, Sant Cugat del Valles (ES)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **13/336,127**

(22) Filed: **Dec. 23, 2011**

(65) **Prior Publication Data**

US 2012/0092226 A1 Apr. 19, 2012

**Related U.S. Application Data**

(63) Continuation of application No. 12/958,522, filed on Dec. 2, 2010, now Pat. No. 8,111,199, which is a continuation of application No. 11/884,991, filed as application No. PCT/EP2006/060766 on Mar. 15, 2006, now Pat. No. 7,872,605.

(30) **Foreign Application Priority Data**

Mar. 15, 2005 (EP) ..... 05005540

(51) **Int. Cl.**  
**H01Q 13/10** (2006.01)  
**H01Q 1/38** (2006.01)

(52) **U.S. Cl.**  
USPC ..... **343/767; 343/700 MS; 343/702**

(58) **Field of Classification Search**  
USPC ..... 343/700 MS, 702, 767, 846, 848  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,141,014 A	2/1979	Sletten
5,268,696 A	12/1993	Buck
5,608,413 A	3/1997	Macdonald
5,777,581 A	7/1998	Lilly

(Continued)

FOREIGN PATENT DOCUMENTS

CA	2416437	1/2002
EP	0548975	6/1993

(Continued)

OTHER PUBLICATIONS

Abedin, M. F. Modifying the ground plane and its effect on planar inverted-F antennas (PIFAs) for mobile phone handsets. Antennas and Wireless Propagation Letters, IEEE. vol. 2. Jan. 1, 2003.

(Continued)


*Primary Examiner* — Tan Ho

(74) *Attorney, Agent, or Firm* — Winstead PC

(57) **ABSTRACT**

A wireless device includes a ground plane with at least two portions. On each of the at least two portions at least one connecting means is provided. The two connecting means are connected with an electric component for connecting the at least two portions of the ground plane. The ground plane is partially covered with an insulating material and the connecting means are given by a part of the ground plane which is not covered by any insulating material.

**20 Claims, 6 Drawing Sheets**







US008593363B2

(12) **United States Patent**  
**McLean et al.**

(10) **Patent No.:** **US 8,593,363 B2**  
(45) **Date of Patent:** **Nov. 26, 2013**

(54) **END-FED SLEEVE DIPOLE ANTENNA  
COMPRISING A 3/4-WAVE TRANSFORMER**

(75) Inventors: **James McLean**, Austin, TX (US);  
**Kunio Yata**, Tokyo (JP); **Robert Sutton**,  
Austin, TX (US); **Hidetsugu Sakou**,  
Tokyo (JP); **Nobutaka Misawa**, Tokyo  
(JP)

(73) Assignee: **TDK Corporation**, Chiba (JP)

(\* ) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 440 days.

(21) Appl. No.: **13/015,280**

(22) Filed: **Jan. 27, 2011**

(65) **Prior Publication Data**

US 2012/0194401 A1 Aug. 2, 2012

(51) **Int. Cl.**  
**H01Q 9/16** (2006.01)

(52) **U.S. Cl.**  
USPC ..... **343/792; 343/822**

(58) **Field of Classification Search**  
USPC ..... 343/791, 790, 792, 820, 821, 822  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,821,709 A	1/1958	Fucci	
3,139,620 A	6/1964	Leidy et al.	
3,750,181 A	7/1973	Kuecken	
4,097,870 A	6/1978	Fulmer, Sr. et al.	
4,282,528 A	8/1981	Aspinwall	
4,290,071 A *	9/1981	Fenwick	343/819
4,352,109 A	9/1982	Reynolds et al.	
4,410,893 A	10/1983	Griffiee	

4,509,056 A	4/1985	Ploussios	
4,730,195 A	3/1988	Phillips et al.	
4,940,989 A	7/1990	Austin	
4,963,879 A	10/1990	Lin	
5,079,562 A	1/1992	Yarusnas et al.	
5,248,988 A	9/1993	Makino	
5,440,317 A	8/1995	Jalloul et al.	
5,719,587 A	2/1998	Rodal	
5,812,097 A	9/1998	Maldonado	
5,963,180 A	10/1999	Leisten	
5,999,140 A	12/1999	Johnson	
6,037,907 A	3/2000	Ha et al.	
6,054,962 A	4/2000	Ha et al.	
6,057,804 A	5/2000	Kaegegein	
6,337,666 B1	1/2002	Bishop	
6,421,024 B1	7/2002	Stolle	
6,552,692 B1	4/2003	Zeilinger et al.	
6,657,601 B2	12/2003	McLean	
6,828,944 B2	12/2004	Martiskainen et al.	
7,164,389 B1	1/2007	Platt	
7,248,227 B2	7/2007	Chen	
2003/0030591 A1 *	2/2003	Gipson et al.	343/792
2006/0139228 A1 *	6/2006	Lin et al.	343/792
2007/0052609 A1 *	3/2007	Lee	343/792
2007/0139289 A1 *	6/2007	Lee et al.	343/792

\* cited by examiner


Primary Examiner — Hoanganh Le

(74) Attorney, Agent, or Firm — Kevin L. Daffer; Daffer  
McDaniel LLP

(57) **ABSTRACT**

An end-fed sleeve dipole is provided herein with improved impedance match and increased bandwidth by incorporating a 3/4-wavelength transformer in the antenna design. The 3/4-wavelength transformer is compatible with a number of different choking schemes, including but not limited to, a single 1/4-wave choke sleeve, a single 1/4-wave choke sleeve with additional ferrite beads, and two or more 1/4-wave choke sleeves with or without ferrite beads. In some embodiments, one or more shunt resonators may be used to provide additional impedance compensation.

**20 Claims, 8 Drawing Sheets**





US008593366B2

(12) **United States Patent**  
**Wakabayashi**

(10) **Patent No.:** **US 8,593,366 B2**  
(45) **Date of Patent:** **Nov. 26, 2013**

(54) **MULTI-ANTENNA APPARATUS AND MOBILE DEVICE**

7,688,273 B2 3/2010 Montgomery et al.  
7,688,275 B2 3/2010 Montgomery et al.  
2006/0038736 A1 2/2006 Hui et al.  
2010/0265146 A1 10/2010 Montgomery et al.

(75) Inventor: **Naoyuki Wakabayashi**, Daito (JP)

(73) Assignee: **Funai Electric Co., Ltd.**, Daito-shi (JP)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 426 days.

(21) Appl. No.: **12/949,994**

(22) Filed: **Nov. 19, 2010**

(65) **Prior Publication Data**

US 2011/0122040 A1 May 26, 2011

(30) **Foreign Application Priority Data**

Nov. 20, 2009 (JP) ..... 2009-264448

(51) **Int. Cl.**  
**H01Q 21/00** (2006.01)  
**H01Q 19/00** (2006.01)

(52) **U.S. Cl.**  
USPC ..... **343/835**; 343/833; 343/834

(58) **Field of Classification Search**  
USPC ..... 343/700 MS, 810, 815, 833, 834, 835  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

6,069,586 A \* 5/2000 Karlsson et al. .... 343/700 MS  
7,352,328 B2 4/2008 Moon et al.  
7,525,502 B2 \* 4/2009 Hui et al. .... 343/835  
7,557,761 B2 7/2009 Iwai et al.

**FOREIGN PATENT DOCUMENTS**

EP 0 958 636 B1 4/2006  
GB 2 458 492 A 9/2009  
JP 2004-274445 A 9/2004  
JP 2006-108830 A 4/2006  
JP 2007-97167 A 4/2007  
JP 2008-17047 A 1/2008  
JP 2008-199588 A 8/2008  
JP 2008-245132 A 10/2008  
JP 2009-521898 A 6/2009  
JP 2009-246560 A 10/2009

**OTHER PUBLICATIONS**

European Search Report dated Mar. 3, 2011(seven (7) pages).  
European Examination Report dated Mar. 27, 2013 (five (5) pages).


\* cited by examiner

*Primary Examiner* — Hoang V Nguyen  
(74) *Attorney, Agent, or Firm* — Crowell & Moring LLP

(57) **ABSTRACT**

This multi-antenna apparatus includes a first antenna element and a second antenna element, and an ungrounded passive antenna element arranged between the first antenna element and the second antenna element, wherein the passive antenna element has a first opposing portion opposed to the first antenna element, a second opposing portion opposed to the second antenna element and a coupling portion coupling the first opposing portion and the second opposing portion with each other.

**18 Claims, 6 Drawing Sheets**





US008593368B2

(12) **United States Patent**  
**Lee et al.**

(10) **Patent No.:** **US 8,593,368 B2**  
(45) **Date of Patent:** **Nov. 26, 2013**

(54) **MULTI-BAND ANTENNA AND ELECTRONIC APPARATUS HAVING THE SAME**

(75) Inventors: **Cheng-Tse Lee**, Yilan County (TW);  
**Saou-Wen Su**, Keelung (TW)

(73) Assignees: **Lite-On Electronics (Guangzhou) Limited**, Guangzhou (CN); **Lite-On Technology Corporation**, Taipei (TW)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 286 days.

(21) Appl. No.: **13/207,387**

(22) Filed: **Aug. 10, 2011**

(65) **Prior Publication Data**  
US 2012/0326940 A1 Dec. 27, 2012

(30) **Foreign Application Priority Data**  
Jun. 27, 2011 (CN) ..... 2011 1 0174026

(51) **Int. Cl.**  
**H01Q 1/50** (2006.01)

(52) **U.S. Cl.**  
USPC ..... **343/860**

(58) **Field of Classification Search**  
USPC ..... 343/860, 700 MS, 702, 846  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

7,352,326 B2 *	4/2008	Korva et al.	343/700 MS
8,022,881 B2 *	9/2011	Wong et al.	343/700 MS
2004/0085245 A1 *	5/2004	Miyata et al.	343/700 MS
2008/0122714 A1 *	5/2008	Ishihara et al.	343/750
2011/0084883 A1 *	4/2011	Wong et al.	343/702
2012/0146874 A1 *	6/2012	Lee et al.	343/841

\* cited by examiner

*Primary Examiner* — Huedung Mancuso


(74) *Attorney, Agent, or Firm* — Li & Cai Intellectual Property (USA) Office

(57) **ABSTRACT**

A multi-band antenna includes an antenna substrate, an antenna ground, an antenna unit, and a matching conductor. The antenna ground has a signal ground terminal and at least one bend. The antenna unit is adjacent to the antenna ground. The matching conductor is electrically coupled to the antenna ground, and an angle exists between the matching conductor and the antenna ground. A length of the first matching conductor is about a quarter of the wavelength corresponding to a frequency of the first operating band. The antenna unit includes a coupling conductor, a feeding conductor, a radiating conductor, and a shorting conductor. The feeding conductor has a signal feeding terminal. One end of the radiating conductor is facing to the antenna ground, and a distance exists between the feeding conductor the antenna ground. Two ends of the shorting conductor are respectively electrically coupled to the antenna ground and the coupling conductor.

**20 Claims, 9 Drawing Sheets**

10





US008599074B2

(12) **United States Patent**  
**Wong et al.**

(10) **Patent No.:** **US 8,599,074 B2**  
(45) **Date of Patent:** **Dec. 3, 2013**

(54) **MOBILE COMMUNICATION DEVICE AND ANTENNA THEREOF**

(75) Inventors: **Kin-Lu Wong**, Taipei Hsien (TW);  
**Cheng-Tse Lee**, Taipei Hsien (TW)

(73) Assignee: **Acer Inc.**, Taipei Hsien (TW)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 271 days.

(21) Appl. No.: **12/648,365**

(22) Filed: **Dec. 29, 2009**

(65) **Prior Publication Data**

US 2011/0084883 A1 Apr. 14, 2011

(30) **Foreign Application Priority Data**

Oct. 8, 2009 (TW) ..... 98134200 A

(51) **Int. Cl.**  
**H01Q 1/24** (2006.01)

(52) **U.S. Cl.**  
USPC ..... **343/702**

(58) **Field of Classification Search**  
USPC ..... 343/700 MS, 702, 846  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2008/0180333 A1 \* 7/2008 Martiskainen et al. .... 343/722  
2009/0189815 A1 \* 7/2009 Hotta et al. .... 343/700 MS

FOREIGN PATENT DOCUMENTS

TW 227576 2/2005

OTHER PUBLICATIONS

Chih-Hua Chang and Kin-Lu Wong, "Penta-Band One-Eight Wavelength PIFA for Internal Mobile Phone Antenna"—Antennas and Propagation Society International Symposium, Jun. 1-5, 2009, 4 pgs. IEEE.

\* cited by examiner

*Primary Examiner* — Robert Karacsony


(74) *Attorney, Agent, or Firm* — Alan Kamrath; Kamrath IP Lawfirm, P.A.

(57) **ABSTRACT**

A mobile communication device has a ground plane and an antenna. The antenna is disposed on a dielectric substrate and includes a radiating metal portion, a coupling metal portion, and a shorting metal portion. One edge of the radiating metal portion faces the ground plane and has a distance between the edge and the ground plane. The coupling metal portion is electrically connected to a source via a connecting metal strip. One end of the shorting metal portion is electrically connected to the radiating metal portion, and the other end of the shorting metal portion is electrically connected to the ground plane.

**7 Claims, 5 Drawing Sheets**

1





US008599084B2

(12) **United States Patent**  
**Wong et al.**

(10) **Patent No.:** **US 8,599,084 B2**  
(45) **Date of Patent:** **Dec. 3, 2013**

(54) **MOBILE COMMUNICATION DEVICE AND ANTENNA**

(75) Inventors: **Kin-Lu Wong**, Taipei Hsien (TW);  
**Po-Wei Lin**, Taipei Hsien (TW);  
**Chih-Hua Chang**, Taipei Hsien (TW)

(73) Assignee: **Acer Incorporated**, Hsichih, Taipei Hsien (TW)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 340 days.

(21) Appl. No.: **13/088,561**

(22) Filed: **Apr. 18, 2011**

(65) **Prior Publication Data**  
US 2012/0098721 A1 Apr. 26, 2012

(30) **Foreign Application Priority Data**  
Oct. 22, 2010 (TW) ..... 99136065 A

(51) **Int. Cl.**  
**H01Q 9/00** (2006.01)

(52) **U.S. Cl.**  
USPC ..... **343/749**

(58) **Field of Classification Search**  
USPC ..... 343/700 MS, 749, 767  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

- 2,942,263 A \* 6/1960 Baldwin ..... 343/767
- 6,664,931 B1 \* 12/2003 Nguyen et al. .... 343/767
- 7,612,676 B2 \* 11/2009 Yuen et al. .... 340/572.7
- 8,085,202 B2 \* 12/2011 Ayatollahi et al. .... 343/700 MS

- 8,115,686 B2 \* 2/2012 Mumbru et al. .... 343/702
- 2007/0257842 A1 11/2007 Tseng
- 2009/0153407 A1 6/2009 Zhang et al.
- 2010/0245176 A1 9/2010 Wong et al.

FOREIGN PATENT DOCUMENTS

- EP 2 157 659 2/2010
- TW 200908445 2/2009
- WO WO 2006/114477 11/2006
- WO WO 2010/010529 1/2010

OTHER PUBLICATIONS

European Search Report dated Oct. 19, 2011.  
TW Office Action dated Jun. 19, 2013.  
English Abstract translation of TW200908445 (Published Feb. 16, 2009, included with the foreign reference).

\* cited by examiner


Primary Examiner — Seung Lee

(74) Attorney, Agent, or Firm — McClure, Qualey & Rodack, LLP

(57) **ABSTRACT**

A mobile communication device is provided. The mobile communication device includes a system circuit board with a surface, a ground plane having a monopole slot on the surface, a microstrip feedline, and a metal element, wherein the ground plane has a longer edge and a shorter edge. The monopole slot has a first operating band and a second operating band. The microstrip feedline is located on the system circuit board, wherein one end of the microstrip feedline passes over the monopole slot, and the other end of the microstrip feedline is connected to a signal source. The metal element is electrically connected to the shorter edge of the ground plane, and is substantially perpendicular to the ground plane. A distance between the open end of the monopole slot and the shorter edge of the ground plane where the metal element is connected is shorter than 0.05 wavelength of the lowest operating frequency of the first operating band.

20 Claims, 7 Drawing Sheets





US008599086B2

(12) **United States Patent**  
**Wong et al.**

(10) **Patent No.:** **US 8,599,086 B2**  
(45) **Date of Patent:** **Dec. 3, 2013**

- (54) **MONOPOLE SLOT ANTENNA**
- (75) Inventors: **Kin-Lu Wong**, Taipei Hsien (TW);  
**Fang-Hsien Chu**, Taipei Hsien (TW)
- (73) Assignee: **Acer Incorporated**, New Taipei (TW)
- (\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 398 days.

7,184,808	B2 *	2/2007	Shoji	.....	455/575.7
7,209,087	B2	4/2007	Tang et al.		
7,417,593	B1 *	8/2008	Hsiao et al.	.....	343/702
7,471,249	B2	12/2008	Tang et al.		
7,630,743	B2 *	12/2009	Uejima et al.	.....	455/575.3
2008/0272971	A1 *	11/2008	Kanno	.....	343/767

- (21) Appl. No.: **12/536,584**
- (22) Filed: **Aug. 6, 2009**
- (65) **Prior Publication Data**  
US 2010/0245176 A1 Sep. 30, 2010

**FOREIGN PATENT DOCUMENTS**

CN	101102009	A	1/2008
TW	I258891	B	7/2006

**OTHER PUBLICATIONS**

Office Action of corresponding CN application, issued on Jun. 26, 2012.  
Office Action of its corresponding TW patent application issued on Nov. 2, 2012.

- (30) **Foreign Application Priority Data**  
Mar. 27, 2009 (TW) ..... 98110256 A

\* cited by examiner

*Primary Examiner* — Michael C Wimer  
*Assistant Examiner* — Hasan Islam  
(74) *Attorney, Agent, or Firm* — Wang Law Firm, Inc.; Li K. Wang; Stephen Hsu


- (51) **Int. Cl.**  
**H01Q 13/10** (2006.01)  
**H01Q 1/00** (2006.01)  
**H01Q 1/24** (2006.01)
- (52) **U.S. Cl.**  
USPC ..... **343/767**; 343/702; 343/729
- (58) **Field of Classification Search**  
USPC ..... 343/700 MS, 702, 846, 729, 767-771;  
455/575.1, 575.7  
See application file for complete search history.

(57) **ABSTRACT**

A monopole slot antenna applicable to a mobile communication device includes a dielectric substrate, a first ground plane, a second ground plane, a monopole slot, and a microstrip feedline. The first ground plane is disposed on the dielectric substrate. The second ground plane is in the vicinity of the first ground plane and electrically connected to the first ground plane via a metal wire. A section of the metal wire is disposed on one surface of the dielectric substrate. The monopole slot is disposed on the first ground plane and has an open end disposed near the metal wire that connects the first and the second ground planes. The microstrip feedline is disposed on a surface of the dielectric substrate opposite to the first ground plane with one end of the microstrip feedline extended across the monopole slot and the other end connected to a signal source.

- (56) **References Cited**  
U.S. PATENT DOCUMENTS  
5,835,063 A 11/1998 Brachat et al.  
6,133,879 A \* 10/2000 Grangeat et al. .... 343/700 MS  
6,762,723 B2 \* 7/2004 Nallo et al. .... 343/700 MS  
6,822,611 B1 \* 11/2004 Kontogeorgakis et al. ... 343/702  
7,042,404 B2 \* 5/2006 Jo et al. .... 343/702  
7,053,848 B2 \* 5/2006 Shoji et al. .... 343/770

**14 Claims, 5 Drawing Sheets**





US008599087B2

(12) **United States Patent**  
**Chiang et al.**

(10) **Patent No.:** **US 8,599,087 B2**  
(45) **Date of Patent:** **Dec. 3, 2013**

(54) **ANTENNAS WITH PERIODIC SHUNT INDUCTORS**  
(75) Inventors: **Bing Chiang**, Cupertino, CA (US); **Gregory Allen Springer**, Sunnyvale, CA (US); **Douglas B. Kough**, San Jose, CA (US); **Enrique Ayala**, Watsonville, CA (US); **Matthew Ian McDonald**, San Jose, CA (US)

6,369,771 B1 4/2002 Chiang et al.  
6,670,923 B1 12/2003 Kadambi et al.  
6,741,214 B1 5/2004 Kadambi et al.  
6,747,601 B2 6/2004 Boyle  
6,774,852 B2 8/2004 Chiang et al.

(Continued)

**FOREIGN PATENT DOCUMENTS**

JP 08242118 9/1996  
WO 03/058758 7/2003  
WO 2007/000749 1/2007

**OTHER PUBLICATIONS**

R. Bancroft "A Commercial Perspective on the Development and Integration of an 802.11a/b/g HiperLan/WLAN Antenna into Laptop Computers", IEEE Antennas and Propagation Magazine, vol. 48, No. 4, Aug. 2006, pp. 12-18.

(Continued)

*Primary Examiner* — Jany Richardson

(74) *Attorney, Agent, or Firm* — Treyz Law Group; G. Victor Treyz; David C. Kellogg

(73) Assignee: **Apple Inc.**, Cupertino, CA (US)  
(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **13/269,884**

(22) Filed: **Oct. 10, 2011**

(65) **Prior Publication Data**

US 2012/0026052 A1 Feb. 2, 2012

**Related U.S. Application Data**

(63) Continuation of application No. 12/759,598, filed on Apr. 13, 2010, now Pat. No. 8,044,873, which is a continuation of application No. 11/958,824, filed on Dec. 18, 2007, now Pat. No. 7,705,795.

(51) **Int. Cl.**  
**H01Q 13/10** (2006.01)

(52) **U.S. Cl.**  
USPC ..... **343/768; 343/772; 343/857**

(58) **Field of Classification Search**  
USPC ..... 343/743, 746, 749, 750, 767, 768, 769, 343/772, 857, 700 MS  
See application file for complete search history.

(56) **References Cited**


**U.S. PATENT DOCUMENTS**

5,955,995 A 9/1999 Silverstein  
6,285,333 B1 9/2001 Reed et al.

(57) **ABSTRACT**

An antenna may be formed from conductive regions that define a gap that is bridged by shunt inductors. The inductors may have equal inductances and may be located equidistant from each other to form a scatter-type antenna structure. The inductors may also have unequal inductances and may be located along the length of the gap with unequal inductor-to-inductor spacings, thereby creating a decreasing shunt inductance at increasing distances from a feed for the antenna. This type of antenna structure functions as a horn-type antenna. One or more scatter-type antenna structures may be cascaded to form a multiband antenna. Antenna gaps may be formed in conductive device housings.

**22 Claims, 21 Drawing Sheets**





US008599088B2

(12) **United States Patent**  
**Chiang et al.**

(10) **Patent No.:** **US 8,599,088 B2**  
(45) **Date of Patent:** **Dec. 3, 2013**

(54) **DUAL-BAND ANTENNA WITH ANGLED SLOT FOR PORTABLE ELECTRONIC DEVICES**

6,856,294 B2 2/2005 Kadambi et al.  
6,888,510 B2 5/2005 Jo et al.  
6,980,154 B2 12/2005 Vance et al.  
7,027,838 B2 4/2006 Zhou et al.  
7,116,267 B2 10/2006 Lee  
7,119,747 B2 10/2006 Lin et al.

(75) Inventors: **Bing Chiang**, Cupertino, CA (US);  
**Gregory Allen Springer**, Sunnyvale, CA (US);  
**Douglas B. Kough**, San Jose, CA (US);  
**Enrique Ayala**, Watsonville, CA (US);  
**Matthew Ian McDonald**, San Jose, CA (US);  
**Hao Xu**, Cupertino, CA (US)

(Continued)

FOREIGN PATENT DOCUMENTS

CN 1700514 11/2005  
CN 1930731 3/2007

(Continued)

OTHER PUBLICATIONS

Jacob, N. et al. "Investigation of Wide-Band Microstrip Slot Antenna." IEEE Transactions on Antennas and Propagation. vol. 52, No. 3, p. 865-872, Mar. 2004.

(Continued)

*Primary Examiner* — Robert Karacsony

(74) *Attorney, Agent, or Firm* — Treyz Law Group; G. Victor Treyz; Michael H. Lyons

(73) Assignee: **Apple Inc.**, Cupertino, CA (US)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 1080 days.

(21) Appl. No.: **11/959,191**

(22) Filed: **Dec. 18, 2007**

(65) **Prior Publication Data**

US 2009/0153411 A1 Jun. 18, 2009

(51) **Int. Cl.**  
**H01Q 13/10** (2006.01)

(52) **U.S. Cl.**  
USPC ..... **343/770**

(58) **Field of Classification Search**  
USPC ..... 343/767, 770  
See application file for complete search history.

(56) **References Cited**


U.S. PATENT DOCUMENTS

6,369,771 B1 4/2002 Chiang et al.  
6,670,923 B1 12/2003 Kadambi et al.  
6,741,214 B1 5/2004 Kadambi et al.  
6,747,601 B2 6/2004 Boyle  
6,774,852 B2 8/2004 Chiang et al.  
6,788,266 B2\* 9/2004 St. Hillaire et al. .... 343/770

(57) **ABSTRACT**

Dual slot antennas are provided for portable electronic devices such as handheld electronic devices. A dual slot antenna may have an open slot that has an open end that is not encircled by conductive material and may have a closed slot in which each end is surrounded by conductor. The closed and open slots may have portions that run parallel to each other. The antenna may be fed using feed terminals that bridge the closed and open slots in the vicinity of the portions of the slots that run parallel to each other. The slots may have portions that are angled with respect to each other. An end portion of one of the slots may be bent and widened for impedance matching and broadened bandwidth. Other portions of the slots may also be angled with respect to their main longitudinal axes.

**5 Claims, 7 Drawing Sheets**







US008599089B2

(12) **United States Patent**  
**Bevelacqua et al.**

(10) **Patent No.:** **US 8,599,089 B2**  
(45) **Date of Patent:** **Dec. 3, 2013**

(54) **CAVITY-BACKED SLOT ANTENNA WITH NEAR-FIELD-COUPLED PARASITIC SLOT**

(75) Inventors: **Peter Bevelacqua**, Cupertino, CA (US);  
**Robert J. Hill**, Salinas, CA (US)

(73) Assignee: **Apple Inc.**, Cupertino, CA (US)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 569 days.

(21) Appl. No.: **12/750,661**

(22) Filed: **Mar. 30, 2010**

(65) **Prior Publication Data**

US 2011/0241948 A1 Oct. 6, 2011

(51) **Int. Cl.**  
**H01Q 13/10** (2006.01)

(52) **U.S. Cl.**  
USPC ..... **343/770; 343/767; 343/775**

(58) **Field of Classification Search**  
USPC ..... **343/767, 770, 769, 775**  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

2,812,514 A	11/1957	Smith	
2,834,959 A	5/1958	Dome	
3,312,976 A	4/1967	Gregory	
4,208,660 A	6/1980	McOwen	
4,245,222 A	1/1981	Eng et al.	
4,710,775 A	12/1987	Coe	
4,733,245 A *	3/1988	Mussler	343/769
5,648,786 A	7/1997	Chung et al.	
5,917,454 A *	6/1999	Hill et al.	343/769
6,002,311 A	12/1999	Wey et al.	
6,081,729 A	6/2000	Bauerschmidt et al.	
6,198,453 B1 *	3/2001	Chew	343/771
6,225,959 B1	5/2001	Gordon	

6,339,400 B1	1/2002	Flint et al.
6,373,351 B1	4/2002	Kubota et al.
6,380,930 B1	4/2002	Van Ruymbeke
6,686,886 B2	2/2004	Flint et al.
6,853,336 B2	2/2005	Asano et al.
6,894,650 B2	5/2005	Darden et al.

(Continued)

**FOREIGN PATENT DOCUMENTS**

GB	2074792	11/1981
JP	61284102	12/1986
WO	2010013982	2/2010

**OTHER PUBLICATIONS**

Chiang et al., U.S. Appl. No. 12/500,570, filed Jul. 9, 2009.

(Continued)


*Primary Examiner* — Hoang V Nguyen  
*Assistant Examiner* — Kyana R McCain

(74) *Attorney, Agent, or Firm* — Treyz Law Group; G. Victor Treyz; David C. Kellogg

(57) **ABSTRACT**

Electronic devices may be provided with antennas. The antennas may include conductive antenna cavities. Antenna resonating elements may be mounted in the antenna cavities to form cavity antennas. An antenna cavity may be formed from metal structures with curved edges that define a curved cavity opening. A flexible printed circuit substrate may be coated with a layer of metal. Slot antenna structures such as a directly fed antenna slot and a parasitic antenna slot may be formed from openings in the metal layer. The flexible printed circuit substrate may be flexed so that the antenna resonating element forms a non-planar curved shape that mates with the opening of the antenna cavity. A ring of solder may be used to electrically seal the edges of the cavity opening to the metal layer in the antenna resonating element. The curved opening may be aligned with curved housing walls in an electronic device.

**18 Claims, 7 Drawing Sheets**





US008599093B2

(12) **United States Patent**  
**Ridgeway**

(10) **Patent No.:** **US 8,599,093 B2**  
(45) **Date of Patent:** **Dec. 3, 2013**

(54) **WIDEBAND ANTENNA FOR PRINTED CIRCUIT BOARDS**

(75) Inventor: **Robert Wayne Ridgeway**, Saratoga Springs, UT (US)

(73) Assignee: **Digi International Inc.**, Minnetonka, MN (US)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 384 days.

(21) Appl. No.: **12/952,669**

(22) Filed: **Nov. 23, 2010**

(65) **Prior Publication Data**

US 2011/0122043 A1 May 26, 2011

**Related U.S. Application Data**

(60) Provisional application No. 61/264,109, filed on Nov. 24, 2009.

(51) **Int. Cl.**  
**H01Q 1/50** (2006.01)

(52) **U.S. Cl.**  
USPC ..... **343/860**

(58) **Field of Classification Search**  
USPC ..... 343/860, 702, 700 MS; 29/601  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

6,515,629 B1 *	2/2003	Kuo et al. ....	343/700 MS
6,529,168 B2 *	3/2003	Mikkola et al. ....	343/702
6,611,235 B2 *	8/2003	Barna et al. ....	343/702
6,734,825 B1 *	5/2004	Guo et al. ....	343/700 MS
6,759,984 B2	7/2004	Wielsma	
7,034,750 B2	4/2006	Asakura et al.	
7,541,984 B2 *	6/2009	Peng et al. ....	343/700 MS

7,903,035 B2 *	3/2011	Mikkola et al. ....	343/702
8,179,322 B2 *	5/2012	Nissinen ....	343/700 MS
2002/0175866 A1 *	11/2002	Gram .....	343/702
2006/0081466 A1 *	4/2006	Nagashima et al. ....	204/298.16

**FOREIGN PATENT DOCUMENTS**

EP	1398847 A1	3/2004
EP	1475859 A1	11/2004
WO	WO-2005076407 A2	8/2005
WO	WO-2011066303 A1	6/2011

**OTHER PUBLICATIONS**

"International Application No. PCT/US2010/057841, International Search Report and Written Opinion mailed Mar. 21, 2011", 11 pgs.  
Yanagi, Masahiro, et al., "A Planar UWB Monopole Antenna Formed on a Printed Circuit Board", 1 pg.  
Yang, H.Y. David, "Printed Straight F Antennas for WLAN and Bluetooth", Dept. of Electrical and Computer Engineering, Univ. of Illinois at Chicago, 4 pgs.

\* cited by examiner


*Primary Examiner* — Huedung Mancuso

(74) *Attorney, Agent, or Firm* — Fogg & Powers LLC

(57) **ABSTRACT**

A planar antenna, such as included as a portion of a wireless communication assembly, can include a dielectric portion, a first conductive portion, extending along a surface of the dielectric portion, and a second conductive portion, parallel to the first conductive portion, extending along the surface of the dielectric portion, the second conductive portion laterally offset from the first portion to provide a specified lateral separation between the first and second conductive portions. The first and second conductive portions can be configured to provide respective resonant operating frequencies ranges offset from each other, and the first and second conductive portions can be configured to follow a commonly-shared path, including at least one bend, along the surface of the dielectric portion.

**20 Claims, 6 Drawing Sheets**





US008599094B2

(12) **United States Patent**  
**Lee**

(10) **Patent No.:** **US 8,599,094 B2**  
(45) **Date of Patent:** **Dec. 3, 2013**

(54) **LOOP ANTENNA**  
(75) Inventor: **Jong-hyuck Lee**, Seongnam-si (KR)  
(73) Assignee: **Samsung Electronics Co., Ltd.**,  
Suwon-si (KR)

5,914,692 A \* 6/1999 Bowers et al. .... 343/742  
6,025,813 A \* 2/2000 Hately et al. .... 343/867  
6,597,318 B1 7/2003 Parsche et al.  
6,861,992 B2\* 3/2005 Kawakami et al. .... 343/741

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 355 days.

EP 0739050 A1 10/1996  
EP 0766200 A2 4/1997  
EP 1494311 A1 1/2005

**FOREIGN PATENT DOCUMENTS**

**OTHER PUBLICATIONS**

(21) Appl. No.: **13/012,383**

Communication dated Sep. 12, 2011 issued by the European Patent Office in counterpart European Application No. 11166800.0.

(22) Filed: **Jan. 24, 2011**

\* cited by examiner

(65) **Prior Publication Data**

US 2011/0291912 A1 Dec. 1, 2011

*Primary Examiner* — Hoanganh Le

(30) **Foreign Application Priority Data**

May 28, 2010 (KR) ..... 10-2010-0050170

(74) *Attorney, Agent, or Firm* — Sughrue Mion, PLLC

(51) **Int. Cl.**  
**H01Q 21/00** (2006.01)

(57) **ABSTRACT**

(52) **U.S. Cl.**  
USPC ..... **343/867**; 343/866

A loop antenna is provided. The loop antenna includes: a substrate; an outer pattern including at least one loop on a surface of the substrate; and an inner pattern in an inner region of the at least one loop of the outer pattern, an end of the inner pattern being connected to an end of the outer pattern, wherein the inner pattern is configured so that an electric current flows in the inner pattern in a direction opposite to a direction in which the electric current flows in the outer pattern. Accordingly, an H-Field characteristic of the loop antenna can be enhanced, thereby allowing the loop antenna to have a decreased size and an improved performance.


(58) **Field of Classification Search**  
USPC ..... 343/860, 861, 866, 867, 741, 742  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

5,248,989 A \* 9/1993 Murdoch ..... 343/841  
5,508,710 A 4/1996 Wang et al.

**18 Claims, 6 Drawing Sheets**





US008599101B2

(12) **United States Patent**  
**Christie et al.**

(10) **Patent No.:** **US 8,599,101 B2**  
(45) **Date of Patent:** **Dec. 3, 2013**

(54) **DIELECTRICALLY LOADED ANTENNA AND RADIO COMMUNICATION APPARATUS**

(75) Inventors: **Andrew Robert Christie**, Northamptonshire (GB); **David Michael Wither**, Northamptonshire (GB); **Martyn Leslie Tongue**, Leicestershire (GB); **Frank Kwasi Frimpong**, Northamptonshire (GB)

(73) Assignee: **Sarantel Limited**, Wellingborough (GB)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 371 days.

(21) Appl. No.: **13/014,984**

(22) Filed: **Jan. 27, 2011**

(65) **Prior Publication Data**

US 2011/0221651 A1 Sep. 15, 2011

**Related U.S. Application Data**

(60) Provisional application No. 61/313,222, filed on Mar. 12, 2010.

(30) **Foreign Application Priority Data**

Jan. 27, 2010 (GB) ..... 1001331.6

(51) **Int. Cl.**  
**H01Q 1/36** (2006.01)

(52) **U.S. Cl.**  
USPC ..... **343/895**; 343/702

(58) **Field of Classification Search**  
USPC ..... 343/895, 700 MS, 702, 906, 850  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

5,092,783 A 3/1992 Suarez et al.  
7,002,530 B1 2/2006 Chung et al.

(Continued)

**FOREIGN PATENT DOCUMENTS**

CN 2 899 134 Y 5/2007  
EP 0 521 511 A2 1/1993

(Continued)

**OTHER PUBLICATIONS**

Search Report from Great Britain Application No. 1001327.4, search dated May 13, 2010.

(Continued)


*Primary Examiner* — Hoanganh Le

(74) *Attorney, Agent, or Firm* — Alston & Bird LLP

(57) **ABSTRACT**

A radio communication apparatus including: (a) a backfire dielectrically loaded antenna for operation at a frequency in excess of 200 MHz comprising: an electrically insulative dielectric core of a solid material having a relative dielectric constant greater than 5 and having an outer surface including oppositely directed distal and proximal surface portions extending transversely of an axis of the antenna and a side surface portion extending between the transversely extending surface portions, the core outer surface defining an interior volume the major part of which is occupied by the solid material of the core; a three-dimensional antenna element structure including at least one pair of elongate conductive antenna elements disposed on or adjacent the side surface portion of the core and extending from the distal core surface portion towards the proximal core surface portion; a feed structure in the form of an axially extending elongate laminate board comprising at least a transmission line section acting as a feed line which extends through a passage in the core from the distal core surface portion to the proximal core surface portion, the antenna having exposed contact areas on or adjacent the core proximal surface portion; and (b) radio communication circuit means having an equipment laminate circuit board with at least one conductive layer, the conductive layer or layers having a plurality of contact terminal support areas to each of which is conductively bonded a respective spring contact positioned so as to bear resiliently against respective ones of the exposed contact areas of the antenna.

**17 Claims, 15 Drawing Sheets**





US008604979B2

(12) **United States Patent**  
**Ge et al.**

(10) **Patent No.:** **US 8,604,979 B2**  
(45) **Date of Patent:** **\*Dec. 10, 2013**

(54) **BROAD BAND ANTENNA**

(75) Inventors: **JunXiang Ge**, Tokyo (JP); **Wasuke Yanagisawa**, Tokyo (JP); **Ryo Horie**, Tokyo (JP)

(73) Assignee: **Yokowo Co., Ltd.**, Tokyo (JP)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 945 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **11/997,696**

(22) PCT Filed: **Aug. 3, 2006**

(86) PCT No.: **PCT/JP2006/315788**  
§ 371 (c)(1),  
(2), (4) Date: **May 7, 2010**

(87) PCT Pub. No.: **WO2007/015583**  
PCT Pub. Date: **Feb. 8, 2007**

(65) **Prior Publication Data**  
US 2010/0220023 A1 Sep. 2, 2010

(30) **Foreign Application Priority Data**  
Aug. 4, 2005 (JP) ..... 2005-227154

(51) **Int. Cl.**  
**H01Q 1/38** (2006.01)  
**H01Q 13/00** (2006.01)

(52) **U.S. Cl.**  
USPC ..... **343/700 MS; 343/772; 343/846**

(58) **Field of Classification Search**  
None  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,944,258	A *	7/1960	Yearout et al.	343/767
3,031,665	A *	4/1962	Robert-Pierre Marie	343/770
4,760,400	A *	7/1988	Lait	343/700 MS
4,843,403	A *	6/1989	Lalezari et al.	343/767
5,146,232	A *	9/1992	Nishikawa et al.	343/713
5,459,471	A *	10/1995	Thomas	342/175
6,313,798	B1 *	11/2001	Bancroft et al.	343/700 MS
6,970,139	B1 *	11/2005	Chew et al.	343/767
7,324,049	B2 *	1/2008	Myoung et al.	343/700 MS
8,068,064	B2 *	11/2011	Yanagisawa et al.	343/772
2004/0100409	A1 *	5/2004	Okado	343/700 MS
2004/0169609	A1 *	9/2004	Song et al.	343/767
2004/0233109	A1 *	11/2004	Ying et al.	343/700 MS
2005/0168383	A1 *	8/2005	Lee	343/700 MS
2006/0071858	A1 *	4/2006	Suh	343/700 MS
2006/0170593	A1 *	8/2006	Watts	343/700 MS

FOREIGN PATENT DOCUMENTS

JP	56-37702	4/1981
JP	1-295503	11/1989

(Continued)

OTHER PUBLICATIONS

International Search Report Dated Sep. 12, 2006.


*Primary Examiner* — Trinh Dinh

(74) *Attorney, Agent, or Firm* — Bachman & LaPointe, P.C.

(57) **ABSTRACT**

Provided is a wide band antenna having ultra-wide band and high performance at a low cost. An antenna element constituting a part of an opening cross section structure of a double cylinder ridge waveguide is spread on a plane. The antenna element has a ridge element portion (21) for adjusting antenna characteristic corresponding to a ridge portion and a radiation element portion (22) for electromagnetic wave radiation. Substantially at a leading end portion of the ridge element portion (21), a feeder terminal (24) is formed. Ground portions (23a and 23b) are maintained at a ground potential and the feeder terminal (24) is guided to an outside as a coplanar waveguide.

**13 Claims, 30 Drawing Sheets**





US008604980B2

(12) **United States Patent**  
**Asrani et al.**

(10) **Patent No.:** **US 8,604,980 B2**  
(45) **Date of Patent:** **Dec. 10, 2013**

(54) **ANTENNA SYSTEM WITH  
NON-RESONATING STRUCTURE**  
(75) Inventors: **Vijay Asrani**, Round Lake, IL (US);  
**Adrian Napoles**, Lake Villa, IL (US);  
**Louis Vannatta**, Crystal Lake, IL (US)

6,686,886 B2 \* 2/2004 Flint et al. .... 343/702  
6,765,536 B2 7/2004 Phillips et al.  
7,026,999 B2 \* 4/2006 Umehara et al. .... 343/702  
7,265,720 B1 9/2007 Ponce De Leon et al.  
7,830,320 B2 \* 11/2010 Shamblin et al. .... 343/747  
2005/0190107 A1 \* 9/2005 Takagi et al. .... 343/702  
2010/0164812 A1 \* 7/2010 Ganeshan et al. .... 343/702

(73) Assignee: **Motorola Mobility LLC**, Libertyville,  
IL (US)

\* cited by examiner

(\* ) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 944 days.

*Primary Examiner* — Tan Ho

(74) *Attorney, Agent, or Firm* — Daniel R. Collopy;  
Ingrassia Fisher & Lorenz, PC; Sylvia Chen

(21) Appl. No.: **12/645,038**

(22) Filed: **Dec. 22, 2009**

(57) **ABSTRACT**

(65) **Prior Publication Data**

US 2011/0148731 A1 Jun. 23, 2011

An antenna system for reception and transmission of radio frequency (RF) signals and a method for tuning the antenna system are provided. The antenna system includes a ground plane, a first element and a second element. The first element includes a driven unbalanced antenna element that resonates within at least one predetermined first frequency band to transmit and receive radio frequency (RF) signals modulated at one or more frequencies within the at least one predetermined first frequency band. The second element is non-resonating within the at least one predetermined first frequency band and is located within an antenna volume of the first element to create a partial loop response within the antenna volume of the first element by capacitively coupling to the first element when connected to the ground plane.

(51) **Int. Cl.**  
**H01Q 1/38** (2006.01)

(52) **U.S. Cl.**  
USPC ..... **343/700 MS; 343/702**


(58) **Field of Classification Search**  
USPC ..... 343/700 MS, 702, 895  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,977,916 A 11/1999 Vannatta et al.  
6,175,334 B1 1/2001 Vannatta et al.

**14 Claims, 21 Drawing Sheets**





US008604988B2

(12) **United States Patent**  
**Desclos et al.**

(10) **Patent No.:** **US 8,604,988 B2**  
(45) **Date of Patent:** **Dec. 10, 2013**

(54) **MULTI-FUNCTION ARRAY FOR ACCESS POINT AND MOBILE WIRELESS SYSTEMS**

(75) Inventors: **Laurent Desclos**, San Diego, CA (US);  
**Sebastian Rowson**, San Diego, CA (US); **Jeffrey Shamblin**, San Marcos, CA (US)

(73) Assignee: **Ethertronic, Inc.**, San Diego, CA (US)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **13/612,833**

(22) Filed: **Sep. 13, 2012**

(65) **Prior Publication Data**  
US 2013/0099987 A1 Apr. 25, 2013

**Related U.S. Application Data**

(63) Continuation-in-part of application No. 13/029,564, filed on Feb. 17, 2011, now Pat. No. 8,362,962, which is a continuation of application No. 12/043,090, filed on Mar. 5, 2008, now Pat. No. 7,911,402.

(60) Provisional application No. 61/533,553, filed on Sep. 12, 2011.

(51) **Int. Cl.**  
**H01Q 9/00** (2006.01)

(52) **U.S. Cl.**  
USPC ..... **343/745; 343/725; 343/813; 343/815**

(58) **Field of Classification Search**

USPC ..... 343/700, 722, 725, 745, 750, 853, 813, 343/815  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,392,603	B1 *	5/2002	Kurz et al.	343/702
6,781,553	B2 *	8/2004	Iguchi et al.	343/725
7,375,694	B2 *	5/2008	Jung et al.	343/745
7,403,165	B2 *	7/2008	Qi et al.	343/702
7,821,467	B2 *	10/2010	Sugiyama	343/745
7,843,397	B2 *	11/2010	Boyle	343/745
7,969,361	B2 *	6/2011	Castaneda et al.	343/700 MS

\* cited by examiner

*Primary Examiner* — Tho G Phan


(74) *Attorney, Agent, or Firm* — Coastal Patent Law Group; Joshua S. Schoonover, P.C.

(57) **ABSTRACT**

A multi-function array is described where several communication system functions are realized using the same antenna architecture. An array of antenna elements where each antenna element can generate multiple radiation patterns is described; the multiple radiation patterns from each antenna element provides increased capability and flexibility in generating a phased array, a MIMO antenna system, a receive diversity antenna system, as well as direction finding feature by way of an interferometer function provided by one or multiple elements. The small volume attributes of the antenna elements populating the array lend this technique to mobile wireless devices as well as access points.

**7 Claims, 13 Drawing Sheets**

**Practical Realization of Modal Array**





US008604998B2

(12) **United States Patent**  
**Choi et al.**

(10) **Patent No.:** **US 8,604,998 B2**  
(45) **Date of Patent:** **\*Dec. 10, 2013**

(54) **GROUND RADIATION ANTENNA**  
(75) Inventors: **Hyeng-cheul Choi**, Seoul (KR); **Jaeseok Lee**, Seoul (KR); **Oul Cho**, Suwon-si (KR); **Hyungjin Lee**, Ansan-si (KR); **Bumki Park**, Seoul (KR)

(73) Assignee: **Radina Co., Ltd**, Seoul (KR)  
(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 296 days.  
This patent is subject to a terminal disclaimer.

(21) Appl. No.: **13/081,014**

(22) Filed: **Apr. 6, 2011**

(65) **Prior Publication Data**  
US 2011/0193762 A1 Aug. 11, 2011

**Related U.S. Application Data**  
(63) Continuation of application No. PCT/KR2010/009338, filed on Dec. 24, 2010.

(30) **Foreign Application Priority Data**  
Feb. 11, 2010 (KR) ..... 10-2010-0012775  
Apr. 9, 2010 (KR) ..... 10-2010-0032922  
May 7, 2010 (KR) ..... 10-2010-0043186  
May 7, 2010 (KR) ..... 10-2010-0043189  
May 7, 2010 (KR) ..... 10-2010-0043190  
Jun. 14, 2010 (KR) ..... 10-2010-0056207  
Dec. 23, 2010 (KR) ..... 10-2010-0133919

(51) **Int. Cl.**  
**H01Q 1/48** (2006.01)  
(52) **U.S. Cl.**  
USPC ..... **343/845; 343/846; 343/847**

(58) **Field of Classification Search**  
USPC ..... 343/845, 846-847  
See application file for complete search history.

(56) **References Cited**  
U.S. PATENT DOCUMENTS  
2004/0095280 A1\* 5/2004 Poilasne et al. .... 343/702


FOREIGN PATENT DOCUMENTS  
EP 1962372 A1 8/2008  
KR 10-2006-0017281 A 2/2006  
KR 10-2007-0112169 A 11/2007  
KR 10-2009-0017964 A 2/2009  
KR 10-2009-0030116 A 3/2009  
KR 10-1003014 B1 12/2010

OTHER PUBLICATIONS  
U.S. Office Action in U.S. Appl. No. 13/081,063 dated Mar. 28, 2013.  
U.S. Office Action in U.S. Appl. No. 13/081,104 dated Mar. 29, 2013.  
International Search Report in International Application No. PCT/KR2010/009338, dated Aug. 16, 2011.  
International Search Report in International Application No. PCT/KR2010/009339, dated Aug. 16, 2011.  
International Search Report in International Application No. PCT/KR2010/009340, dated Aug. 16, 2011.

\* cited by examiner  
*Primary Examiner* — Kristy A Haupt  
(74) *Attorney, Agent, or Firm* — Park, Kim & Suh, LLC

(57) **ABSTRACT**  
A ground radiation antenna is disclosed. Herein, the ground radiation antenna provides a radiator-forming circuit, which is formed to have a simple structure using a capacitive element, as well as a feeding circuit suitable for the provided radiator-forming circuit. Thus, the structure of the antenna becomes simpler and the size of the antenna becomes smaller. Accordingly, the fabrication process of the antenna is simplified, thereby largely reducing the fabrication cost.

**16 Claims, 8 Drawing Sheets**







US008605003B2

(12) **United States Patent**  
**Lai et al.**


(10) **Patent No.:** **US 8,605,003 B2**  
(45) **Date of Patent:** **Dec. 10, 2013**

- (54) **MINIATURE WIRE ANTENNA**
- (75) Inventors: **Ming-Iu Lai**, Taipei (TW);  
**Chun-Hsiung Wang**, Taipei (TW)
- (73) Assignee: **ASUSTeK Computer Inc.**, Taipei (TW)
- (\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 873 days.
- (21) Appl. No.: **12/725,750**
- (22) Filed: **Mar. 17, 2010**
- (65) **Prior Publication Data**  
US 2010/0271266 A1 Oct. 28, 2010
- (30) **Foreign Application Priority Data**  
Apr. 24, 2009 (TW) ..... 98113697 A
- (51) **Int. Cl.**  
**H01Q 1/36** (2006.01)  
**H01Q 1/24** (2006.01)  
**H01Q 1/38** (2006.01)
- (52) **U.S. Cl.**  
USPC ..... **343/895**; 343/702; 343/700 MS
- (58) **Field of Classification Search**  
USPC ..... 343/700 MS, 895, 702, 725, 729, 846, 343/848  
See application file for complete search history.

- (56) **References Cited**  
U.S. PATENT DOCUMENTS  
6,867,746 B2 \* 3/2005 Mendolia et al. .... 343/841  
6,992,633 B2 \* 1/2006 Kim et al. .... 343/700 MS  
7,324,063 B2 \* 1/2008 Bae et al. .... 343/895  
7,362,285 B2 4/2008 Webb et al.  
7,423,599 B2 9/2008 Li et al.  
7,724,193 B2 \* 5/2010 Soora et al. .... 343/700 MS  
7,999,758 B2 \* 8/2011 Bae et al. .... 343/895  
2008/0198073 A1 8/2008 Yeh  
\* cited by examiner  
*Primary Examiner* — Michael C Wimer  
*Assistant Examiner* — Hasan Islam  
(74) *Attorney, Agent, or Firm* — Jianq Chyun IP Office

(57) **ABSTRACT**  
A miniature wire antenna includes N rectangular metal plates located at a first layer of a PCB, a tunable metal plate located at the first layer of the PCB and N serpentine lines located at a second layer of the PCB. The positions of the N serpentine lines correspond to the positions of the rectangular metal plates. A first end of each of the serpentine lines is connected to the corresponding rectangular metal plate, and a second end of each of the serpentine lines is connected to the next rectangular metal plate. A first end of the last serpentine line is connected to the corresponding rectangular metal plate, and a second end of the last serpentine line is connected to the tunable metal plate.

**8 Claims, 10 Drawing Sheets**





US008605922B2

(12) **United States Patent**  
**Pulimi et al.**

(10) **Patent No.:** **US 8,605,922 B2**  
(45) **Date of Patent:** **Dec. 10, 2013**

(54) **ANTENNA SYSTEM WITH PARASITIC ELEMENT FOR HEARING AID COMPLIANT ELECTROMAGNETIC EMISSION**

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,812,855 A \* 3/1989 Coe et al. .... 343/818  
5,568,155 A \* 10/1996 Tsunekawa et al. ... 343/700 MS

(Continued)

FOREIGN PATENT DOCUMENTS

EP 1432068 A2 \* 6/2004  
EP 1796207 A1 6/2007

(Continued)

OTHER PUBLICATIONS

Patent Cooperation Treaty, "Notification of Transmittal of the International Search Report and the Written Opinion of the International Searching Authority, or the Declaration" for International Application No. PCT/US2011/036620, Sep. 1, 2011, 16 pages.

(Continued)

*Primary Examiner* — David Warren  
*Assistant Examiner* — Christina Russell

(74) *Attorney, Agent, or Firm* — Daniel R. Collopy; Ingrassia Fisher & Lorenz, PC; Sylvia Chen

(57) **ABSTRACT**

A system for production of an electromagnetic (EM) field having EM emissions mitigated at one or more predetermined locations within a Hearing Aid Compliant (HAC) measurement plane is provided. The EM field mitigation system includes a ground plane, an antenna element, and a parasitic resonator element. The antenna element is coupled to the ground plane and resonates within at least one predetermined frequency band for transmitting and receiving the radio frequency (RF) signals modulated at one or more frequencies within the at least one predetermined first frequency band. The parasitic resonator element includes at least a half-wavelength resonator portion floating above the ground plane and a second half-wavelength resonator portion floating above the ground plane, crossing an effective electric field mid-line of the ground plane, and located a predetermined distance from the antenna element for mitigation of the EM emissions of the antenna element at the one or more predetermined locations within the HAC measurement plane.

**14 Claims, 36 Drawing Sheets**

(71) Applicant: **Motorola Mobility LLC**, Libertyville, IL (US)

(72) Inventors: **Narendra Pulimi**, Round Lake, IL (US);  
**Hugh K. Smith**, Palatine, IL (US);  
**Istvan J. Szini**, Grayslake, IL (US)

(73) Assignee: **Motorola Mobility LLC**, Libertyville, IL (US)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **13/910,063**

(22) Filed: **Jun. 4, 2013**

(65) **Prior Publication Data**

US 2013/0273963 A1 Oct. 17, 2013

**Related U.S. Application Data**

(62) Division of application No. 12/818,288, filed on Jun. 18, 2010, now Pat. No. 8,483,415.

(51) **Int. Cl.**

**H01Q 1/24** (2006.01)  
**H01Q 1/38** (2006.01)  
**H01Q 1/48** (2006.01)  
**H01Q 9/04** (2006.01)  
**H01Q 19/00** (2006.01)  
**H04B 1/04** (2006.01)


(52) **U.S. Cl.**

USPC ..... **381/312**; 343/700 MS; 343/702;  
343/833; 343/846; 455/129; 455/550.1; 455/575.7

(58) **Field of Classification Search**

USPC ..... 381/312; 455/575.7; 343/700 MS, 702,  
343/833

See application file for complete search history.





US008610626B2

(12) **United States Patent**  
**Chang et al.**

(10) **Patent No.:** **US 8,610,626 B2**  
(45) **Date of Patent:** **Dec. 17, 2013**

(54) **ANTENNA WITH SLOT**

(75) Inventors: **Li-Chi Chang**, Hsinchu (TW);  
**Yung-Chung Chang**, Tuku Township  
(TW); **Meng-Sheng Chen**, Kaohsiung  
(TW); **Chang-Chih Liu**, Xinshe  
Township (TW); **Chang-Sheng Chen**,  
Taipei (TW)

(73) Assignee: **Industrial Technology Research  
Institute (TW)**

(\* ) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 327 days.

(21) Appl. No.: **12/963,935**

(22) Filed: **Dec. 9, 2010**

(65) **Prior Publication Data**

US 2012/0146853 A1 Jun. 14, 2012

(51) **Int. Cl.**  
**H01Q 1/38** (2006.01)

(52) **U.S. Cl.**  
USPC ..... **343/700 MS; 343/767**

(58) **Field of Classification Search**  
USPC ..... **343/700 MS, 702, 725, 767**  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,835,063 A 11/1998 Brachaf et al.  
6,407,710 B2 6/2002 Keilen et al.

6,819,287 B2 11/2004 Sullivan et al.  
6,999,037 B2\* 2/2006 Apostolos ..... 343/767  
7,248,224 B2\* 7/2007 Yuanzhu ..... 343/700 MS  
7,298,343 B2\* 11/2007 Forster et al. .... 343/767  
8,279,125 B2\* 10/2012 Bellows ..... 343/725  
2003/0122722 A1\* 7/2003 Sugiyama et al. .... 343/767

**FOREIGN PATENT DOCUMENTS**

CN 101257139 9/2008  
TW I329385 2/2009  
TW I309487 5/2009

**OTHER PUBLICATIONS**

Office Action dated Aug. 14, 2013 from corresponding application  
No. 201110208959.0.

Lee, Cheng-Tse, et al., "Planar Monopole With a Coupling Feed and  
an Inductive Shorting Strip for LTE/GSM/UMTS Operation in the  
Mobile Phone", IEEE Transactions on Antennas and Propagation,  
vol. 58, No. 7, Jul. 2010, pp. 2479-2483.

\* cited by examiner


*Primary Examiner* — Tan Ho

(74) *Attorney, Agent, or Firm* — Lowe Hauptman & Ham,  
LLP

(57) **ABSTRACT**

An antenna having a signal feeding structure, an antenna  
conductor coupled to the signal feeding structure and forming  
a slot in the antenna conductor. A closing portion capacitively  
closing the at least one slot at a mechanically open end of the  
slot.

**19 Claims, 8 Drawing Sheets**





US008610628B2

(12) **United States Patent**  
**Chen et al.**

(10) **Patent No.:** **US 8,610,628 B2**  
(45) **Date of Patent:** **Dec. 17, 2013**

- (54) **WIDEBAND ANTENNA**
- (75) Inventors: **Wei-Yu Chen**, New Taipei (TW);  
**Shih-Wei Hsieh**, Taipei (TW)
- (73) Assignee: **Mediatek Inc.**, Hsin-Chu (TW)
- (\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 224 days.

7,136,022	B2 *	11/2006	Sato et al.	343/702
7,183,980	B2 *	2/2007	Chang et al.	343/700 MS
7,352,326	B2 *	4/2008	Korva et al.	343/700 MS
7,659,853	B2	2/2010	Chen et al.	
7,825,863	B2	11/2010	Martiskainen et al.	
2009/0153429	A1	6/2009	Su et al.	
2010/0060528	A1	3/2010	Chiu et al.	
2010/0328182	A1	12/2010	Wong et al.	
2011/0095949	A1 *	4/2011	Wong et al.	343/702
2011/0102283	A1	5/2011	Chang et al.	
2011/0156958	A1	6/2011	Wong et al.	
2012/0032862	A1 *	2/2012	Ying	343/749

- (21) Appl. No.: **13/290,406**
- (22) Filed: **Nov. 7, 2011**

**FOREIGN PATENT DOCUMENTS**

EP	2 117 073	11/2009
EP	2 169 763	3/2010

- (65) **Prior Publication Data**  
US 2013/0113661 A1 May 9, 2013

\* cited by examiner

*Primary Examiner* — Tan Ho

- (51) **Int. Cl.**  
**H01Q 1/38** (2006.01)  
**H01Q 1/24** (2006.01)
- (52) **U.S. Cl.**  
USPC ..... **343/700 MS; 343/702**
- (58) **Field of Classification Search**  
USPC ..... **343/700 MS, 702**  
See application file for complete search history.

(74) *Attorney, Agent, or Firm* — McClure, Qualey & Rodack, LLP

(57) **ABSTRACT**

A wideband antenna includes: a substrate, having a first surface and a second surface; a ground plane, disposed on the second surface; an exciting element, disposed on the first surface, and having a feed point coupled to a signal source; a connection element, disposed on the first surface, and coupled to the ground plane; a first branch, disposed on the first surface, and coupled to the connection element; a second branch, disposed on the first surface, and coupled to the connection element; and a coupling element, disposed on the first surface, and coupled to the connection element.

- (56) **References Cited**  
**U.S. PATENT DOCUMENTS**  
6,963,310 B2 \* 11/2005 Horita et al. .... 343/702  
7,113,133 B2 \* 9/2006 Chen et al. .... 343/700 MS

**20 Claims, 7 Drawing Sheets**

